

---

MODULE NAME: RKB

REVISION LEVEL: H

MODULE TYPE: IOMODX

I.D. NUM.: 124

DEVICES TESTED: 1 TO 8 RK06/7 DRIVES ON 1 (OR 2 DUAL  
PORT) RK611 CONTROLLER(S)

DEFAULT PARAMETERS: DVA-177400 VCT-210 BR1-5  
BR2-0 DVC-1 SR0-0

REQUIRED PARAMETERS: FOR DUAL-PORT OPERATION, DVA AND VCT  
ADDRESSES FOR THE SECOND RK611

MEANING OF SR1:

- BIT0 = 1 IF THE RETRY LIMIT IS EXCEEDED  
ON ANY FUNCTION, A HARD ERROR IS ASSUMED  
AND THE DRIVE IS DROPPED.
- BIT0 = 0 IF THE RETRY LIMIT IS EXCEEDED,  
THE FUNCTION IS ABORTED AND THE  
TESTING CONTINUES.
- BIT 1?* BIT6 = 1 INCREMENT DISK ADDRESS EACH  
CYCLE (SEQUENTIAL SEEKS).
- BIT6 = 0 GENERATE RANDOM DISK ADDRESS FOR  
EACH CYCLE.
- BIT2 = 1 TYPE OUT ADDRESS OF ALL BADSPOTS  
NOT IN MODULE TABLE, AND ADD  
TO TABLE.
- BIT2 = 0 ADD NEW BADSPOTS TO MODULE  
TABLE, BUT DO NOT TYPE OUT.

---