

VTV30,VT30-H

VTV30J/H VT30H LOGIC
CVVTAA0

AH F654A MC

COPYRIGHT 1979

FICHE 1 OF 1

NOV 1979

digital

MADE IN USA

1
2
3
4
5

000000

.REPT 0

IDENTIFICATION

PRODUCT CODE: AC-F652A-MC
PRODUCT NAME: CVVTAA0 VTV30J/H-VT30H LOGIC
PRODUCT DATE: OCT 1, 1979
MAINTAINER: COMPUTER SPECIAL SYSTEMS
DIGITAL EQUIPMENT CO. LTD.
READING
BERKS. U.K.

COPYRIGHT (C) 1979 BY
DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASS

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE
USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF
SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE
COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES
THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE
TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE
SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE
WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A
COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR
RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT
SUPPLIED BY DIGITAL.

7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

VTV30-H/J OR VT30-H LOGIC DIAGNOSTIC

PROGRAM DESCRIPTION

1. ABSTRACT

THIS IS THE FIRST PART OF A TWO PART DIAGNOSTIC FOR THE
VTV30-H/J OR VT30-H GRAPHICS DISPLAY CONTROLLER. THIS
PART CONTAINS THE LOGIC TESTS TO CHECK OUT AS MUCH OF
THE HARDWARE AS POSSIBLE. THE PROGRAM WILL PRINT OUT AN
ERROR MESSAGE WHENEVER A FAULT IS FOUND. AFTER
SUCCESSFULLY RUNNING THIS PART OF THE DIAGNOSTIC, PART 2
SHOULD BE RUN. FURTHER LOGIC TESTS ARE CARRIED OUT IN
PART 2.

2. REQUIREMENTS

2.1 EQUIPMENT

- A. PDP-11 COMPUTER
- B. CONSOLE TELETYPE
- C. VTV30-H/J OR VT30-H
- D. DIAGNOSTIC TAPE AND LISTINGS

2.2 STORAGE

THIS PROGRAM REQUIRES A MINIMUM OF 8K WORDS OF MEMORY.

3. LOADING PROCEDURE

THE PROGRAM IS LOADED USING THE ABSOLUTE BINARY LOADER
AND IS IN ABSOLUTE BINARY FORMAT. THE PROGRAM CAN ALSO
BE LOADED AND RUN IN THE NORMAL XXDP MANNER.

4. STARTING PROCEDURE

THE PROGRAM HAS A LOAD AND GO FEATURE WHICH AUTOMATI
CALLY STARTS THE PROGRAM AT ADDRESS 1000 UPON A
SUCCESSFUL LOAD.

102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145

5. RESTARTING PROCEDURE

THE PROGRAM HAS A RESTART ADDRESS AT 1200 WHICH ALLOWS THE PROGRAM TO BE RESTARTED WITHOUT HAVING TO RE-ENTER THE BUS AND VECTOR ADDRESSES. IF IT IS NECESSARY TO RESTART THE PROGRAM WITH NEW BUS AND VECTOR ADDRESSES, THE ADDRESSES 1000 OR 200 SHOULD BE USED AS THE RESTART ADDRESS.

6. PROGRAM AND OPERATOR ACTION

THE FOLLOWING OPERATOR REQUESTS ARE MADE BY THE PROGRAM PRIOR TO THE COMMENCEMENT OF THE ACTUAL TESTS:-

TYPE 6 FOR 625-LINES OR 5 FOR 525-LINE DISPLAY
FIRST BUS ADDRESS IS
FIRST VECTOR ADDRESS IS.....
FIRST PRIORITY LEVEL IS

THE OPERATOR SHOULD REPLY TO REQUESTS ABOVE, BY INPUTTING THE CORRECT DATA.

'SELECT DESIRED SWITCH REGISTER SETTINGS.'

'TYPE CNTRL-C TO CONTINUE'

OR

'SWR = 0.'

IN REPLY TO THE REQUEST ABOVE THE OPERATOR SHOULD SELECT DESIRED SWITCH REGISTER OPTIONS AS SET OUT UNDER SWITCH OPTIONS BELOW.

7. SWITCH REGISTER OPTIONS

THIS PROGRAM IS DESIGNED TO RUN EQUALLY EASILY ON PDP-11 PROCESSORS WITH, OR WITHOUT, A HARDWARE SWITCH REGISTER. ON STARTING, A TEST IS DONE TO SEE IF A HARDWARE SWITCH REGISTER IS PRESENT. IF IT IS PRESENT, IT MAY BE USED IN THE NORMAL MANNER.

147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185

THE SWITCH REGISTER SETTINGS ARE:-

SWR15=1	INHIBIT ERROR HALT
SWR14=1	INHIBIT ERROR PRINT-OUT
SWR13=1	FAST ITERATION
SWR12=1	:
SWR11=1	:SCOPE LOOPS, SEE BELOW
SWR10=1	:FOR A DESCRIPTION, AND
SWR09=1	:APPENDIX A FOR EXAMPLES
SWR08=1	:OF THEIR USE
SWR07=1	:
SWR06=1	SELECTED TEST
SWR05=1	:
SWR04=1	:
SWR03=1	:TEST NOS.
SWR02=1	:
SWR01=1	:
SWR00=1	:

THE SETTING OF BITS 7, 8, 9, 10, 11, AND 12 IN THE SWITCH REGISTER ARE USED TO SELECT THE TRAP OPTIONS PRESENT IN THE PROGRAM. THE SELECTION IS MADE IN THE FOLLOWING MANNER:

BIT(S) SET	TRAP FUNCTION SELECTED
7	TRAP+2
8	TRAP+4
9	TRAP+10
10	TRAP+20
9 AND 10	TRAP+30
11	TRAP+40
9 AND 11	TRAP+50
10 AND 11	TRAP+60
9, 10 AND 11	TRAP+70
12	USES THE SWITCH REGISTER SETTING THAT WAS IN FORCE WHEN THE LAST TRAP INSTRUCTION WAS EXECUTED.

187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238

IF A HARDWARE SWITCH REGISTER IS NOT PRESENT, THE PROGRAM ASSIGNS A LOCATION IN MEMORY AS A SOFTWARE SWITCH REGISTER, THE OPTIONS REMAINING AS ABOVE. THIS MEANS THAT ALL MODIFICATIONS TO THE SWITCH REGISTER MAY BE MADE USING THE CONSOLE TELETYPE VIA A MONITOR ROUTINE. THIS MONITOR IS CALLED BY TYPING CTRL-G AT THE CONSOLE TELETYPE AND RESPONDS BY PRINTING THE CURRENT CONTENTS OF THE SOFTWARE SWITCH REGISTER, FOLLOWED BY A PROMPT CHARACTER (>). THE OPERATOR SHOULD THEN TYPE IN THE NEW SWITCH REGISTER SETTINGS AS AN OCTAL NUMBER, FOLLOWED BY A CARRIAGE RETURN. TYPING CARRIAGE RETURN ALONE WILL CAUSE THE SETTING TO REMAIN UNCHANGED. THE SWITCH REGISTER IS THEN LOADED WITH THE NEW VALUE AND PROGRAM EXECUTION CONTINUES. IF A SETTING IS ENTERED WHICH INCLUDES THE SELECT TEST BIT (SWR06), THE TEST INDICATED BY SWR 00-05 WILL BE SELECTED IMMEDIATELY. THIS DOES NOT APPLY WHEN DEFAULTING ON AN EXISTING SETTING.

THE SWR MONITOR IS ALSO CALLED AUTOMATICALLY IF AN ERROR IS DETECTED AND SWR BIT 15 IS NOT SET. OCTAL EQUIVALENTS FOR THE SWITCHES ARE AS FOLLOWS:

SWR15 =	100000
SWR14 =	40000
SWR13 =	20000
SWR12 =	10000
SWR11 =	4000
SWR10 =	2000
SWR09 =	1000
SWR08 =	400
SWR07 =	200
SWR06 =	100
SWR05 =	40
SWR04 =	20
SWR03 =	10
SWR02 =	4
SWR01 =	2
SWR00 =	1

TO SET A COMBINATION OF THESE SWITCHES, SIMPLY ADD TOGETHER THE CORRESPONDING OCTAL NUMBERS AND ENTER THE TOTAL IN RESPONSE TO "SWR= X>". (LEADING ZEROS MAY BE IGNORED).

FOR WORST CASE TESTING, ALL SWITCHES SHOULD BE ZERO. IT IS POSSIBLE, WITH THESE SWITCH REGISTER OPTIONS, TO EXECUTE ONLY A PRE-SELECTED TEST WITH THE FACILITY TO LOOP ON THAT TEST OR TO START THE PROGRAM PASS OR FINISH THE PROGRAM PASS AT ANY PARTICULAR TEST.

8. ERROR REPORTS

THE FORMAT OF THE ERROR REPORTS IS AS FOLLOWS:-

E# AABB	AT PC:CCCC
GOOD: DDDD	BAD: EEEE
STATUS: FFFF	ADDRESS: GGGG
DATA: KKKK	CALLED FROM: HHHH
	ERROR COUNT = JJJJ

WHERE:

AA IS THE TEST NUMBER
BB IS THE ERROR NUMBER
CCCC IS THE ADDRESS WHERE THE ERROR REPORT OCCURS.
DDDD IS THE DATA EXPECTED
EEEE IS THE DATA RECEIVED
FFFF GGGG AND KKKK ARE CONTENTS OF REGISTERS.
HHHH IS THE ADDRESS IN THE MAINLINE CODE WHERE THE
SUBROUTINE, WHERE THE ERROR REPORT IS
GENERATED, IS CALLED FROM.
JJJJ IS THE NUMBER OF ERRORS REPORTED TO DATE IN
THIS SECTION.

9. ONLINE MODIFICATIONS

AVAILABLE TO THE USER IS A ROUTINE TO MODIFY PROGRAM
LOCATIONS. IT IS ENTERED BY TYPING CNTRL-O DURING THE
RUNNING OF THE TESTS. ON ENTRY, A PROMPT '\$' IS MADE
FOR THE ADDRESS TO BE MODIFIED. IF NO ADDRESS IS GIVEN,
IT IS ASSUMED THAT NO MODIFICATIONS ARE REQUIRED AND THE
ROUTINE WILL COMPLETE. IF AN ADDRESS IS SPECIFIED, IT
WILL BE CHECKED TO SEE IF IT IS EVEN AND IN EXISTANCE.
ONCE IT HAS BEEN CHECKED, ITS CONTENTS ARE DISPLAYED AND
A PROMPT '/' IS MADE FOR THE NEW CONTENTS. IF NO NEW
VALUE IS GIVEN, THE EXISTING VALUE WILL BE LOADED.
HAVING DEALT WITH THAT ADDRESS, THE ROUTINE WILL THEN
EXAMINE THE TERMINATING CHARACTER TO DETERMINE THE NEXT
OPERATION TO PERFORM.

TYPING <ESC> WILL COMPLETE THE MODIFICATIONS BEING
DONE.
<CR> WILL CAUSE A PROMPT FOR THE NEXT ADDRESS
TO BE MODIFIED.
<LF> WILL TAKE THE NEXT ADDRESS TO BE MODIFIED
AS THE CURRENT ADDRESS+2.

10. PROGRAM DESCRIPTION

TEST 0

THIS TEST CHECKS ALL THE READ/WRITE BITS IN THE CONTROL AND STATUS REGISTER, FOR CORRECT SETTING AND CLEARING. IT ALSO CHECKS THE READ-ONLY 525-LINE BIT AGAINST THE ANSWER GIVEN TO THE 525/625 LINE QUESTION AT THE START OF THE PROGRAM.

ERROR 0000 CSR DID NOT INITIALISE ON RESET
0001 525-LINE BIT READ INCORRECTLY
0002 CSR DATA ERROR WHEN TRYING TO SET BIT
0003 CSR DATA ERROR WHEN TRYING TO CLEAR BIT.

TEST 1

THIS TEST CHECKS THAT THE READY AND TIMER INTERRUPTS OPERATE CORRECTLY AND ON THE RIGHT LEVEL. IT DOES NOT CHECK THAT NO INTERRUPT OCCURS WHEN THE READY BIT IS CLEAR (THIS IS DONE IN TEST 5). THE LAST PART OF THIS TEST RINGS THE BELL ON THE CONSOLE DEVICE, TEN TIMES AT ONE SECOND INTERVALS. THE TIMER INTERRUPT IS USED TO SET THE INTERVAL, AND THE OPERATOR SHOULD CHECK THAT THE BELL RINGS ARE EVENLY SPACED OVER ABOUT NINE SECONDS.

ERROR 1000 READY BIT DID NOT SET AFTER INITIALISE
1001 UNEXPECTED INTERRUPT WITH ENABLE CLEAR
1003 NO READY INTERRUPT AT DEVICE LEVEL
1005 NO TIMER INTERRUPT AT DEVICE LEVEL
1006 NO TIMER INTERRUPT WITHIN 40MS OF ENABLE BEING SET
1007 NO SECOND TIMER INTERRUPT IN 20MS OF BIT BEING CLEARED
1010 TIMER BIT WOULD NOT CLEAR AFTER INTERRUPT.

339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388

TEST 2

THE CORRECT LOADING, READING AND INCREMENTING OF THE CHARACTER STORE ADDRESS REGISTER IS CHECKED IN THIS TEST (NOTE THE ADDRESS WILL INCREMENT WHEN THE DATA BYTE IS LOADED, AND ALSO WHEN THE ADDRESS BYTE IS READ).

- ERROR 2000 CHARACTER STORE ADDRESS REGISTER NOT ZEROED BY INITIALISE
- 2001 CHARACTER STORE ADDRESS REGISTER DATA ERROR
- 2002 CHARACTER STORE ADDRESS INCREMENT ERROR WHEN LOADING AND READING CHARACTER REGISTER IN 8V MODE
- 2003 DITTO IN 6V MODE
- 2004 INVISIBLE BITS OF CHARACTER STORE ADDRESS (ROW IN CHARACTER) WERE NOT SET TO ZERO WHEN ADDRESS WAS LOADED.

TEST 3

THE ENTIRE CHARACTER STORE IS CHECKED IN THIS TEST BY LOADING EVERY LOCATION WITH RANDOM DATA AND THEN READING EACH LOCATION BACK AND CHECKING THE DATA.

- ERROR 3001 WRONG DATA READ BACK FROM CHARACTER STORE
- ADDRESS = CHARACTER NUMBER
STATUS = ROW OF CHARACTER

TEST 4

THIS TEST CHECKS THE CURSOR REGISTER FOR CORRECT LOADING AND READING. IT ALSO CHECKS FOR CORRECT INCREMENT WHEN LOADING THE PICTURE STORE AND THE EFFECT ON THE REGISTER OF LINE FEED, CARRIAGE RETURN AND HOME.

- ERROR 4001 LOAD/READ ERROR WITH CURSOR ADDRESS REGISTER
- 4002 REGISTER NOT CLEARED BY "HOME" COMMAND
- 4003 LOAD/READ ERROR ON X ADDRESS

390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443

4004 X INCREMENT ERROR ON CHARACTER LOAD TO
 PICTURE STORE (NOTE: NO INCREMENT SHOULD
 OCCUR WHEN X ADDRESS IS AT MAXIMUM VALUE)

MAXIMUM X IN 6H = 79
 MAXIMUM X IN 8H = 63

4005 DITTO ON "SET BLINK OFF INCREMENT"
 COMMAND

4006 DITTO ON "SET BLINK ON INCREMENT" COMMAND

4007 X ADDRESS DID NOT ZERO ON "CARRIAGE
 RETURN"

4010 Y ADDRESS LOAD/READ ERROR

4011 Y INCREMENT ERROR ON "LINE FEED" (NO
 INCREMENT SHOULD OCCUR WHEN Y ADDRESS IS
 AT MAXIMUM VALUE)

525L 625L

MAXIMUM Y IN 6V = 39 , 47

MAXIMUM Y IN 8V = 29 , 35

TEST 5

THIS TEST CHECKS EVERY LOCATION IN THE PICTURE STORE FOR
 CORRECT LOADING AND READING. IT ALSO CHECKS THE
 OPERATION OF PRESET AND THAT THE READY BIT IS CLEAR
 DURING THE PRESET OPERATION AND THAT NO READY INTERRUPT
 OCCURS WHILST READY IS CLEAR. NOTE THE DISPLAY IS
 TURNED ON DURING THIS TEST.

ERROR 5001 PICTURE STORE DATA ERROR

ADDRESS = STORE X,Y ADDRESS OF LOCA-
 TION WITH ERROR

5002 READY BIT DID NOT CLEAR FOR PRESET

5003 NO READY INTERRUPT WITHIN 40MS AFTER
 PRESET

5004 READY BIT WAS NOT SET WHEN INTERRUPT
 OCCURRED

5005 PICTURE STORE DATA ERROR ATER PRESET

445
446
447
448

5006

PICTURE STORE DATA ERROR AFTER LOADING
PART OF THE PICTURE STORE, USING BLINK
ON/OFF WILL INCREMENT COMMAND (301 OR
300) WHEN BLINK IS REQUIRED.

450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501

APPENDIX A

PDP-11 DIAGNOSTIC LOOPING FACILITIES VIA SWITCH REGISTER OPTIONS

N.B.

THE INTENTION OF THIS APPENDIX IS TO EXPLAIN, IN GENERAL, THE SCOPE FACILITIES WITHIN PROGRAM CODING. THE USER MUST FIRST EXAMINE THE CODING ABOUT THE AREA HE WISHES TO USE SCOPING FACILITIES, TO ASCERTAIN THAT THE PARTICULAR FACILITY HE REQUIRES IS, IN FACT, AVAILABLE.

PROGRAM LOOPING CONTROL CAN BE SELECTED BY USING SWR 12 - 07. THE PROGRAM HANDLES THIS BY USE OF THE TRAPSV ROUTINE, WHICH IS ENTERED USING THE TRAP INSTRUCTION. BASICALLY, THE ROUTINE CHECKS EQUALITY BETWEEN BITS 05 - 00 OF THE TRAP INSTRUCTION AND SWR 12 - 07.

THERE ARE THREE DISTINCT FUNCTIONS CONTROLLED BY THE TRAP ROUTINE:-

- A) RUN - (TRAP + 2 INSTRUCTION AND SWR 07 SET)
USUALLY USED TO INHIBIT TEST NUMBER PRINTOUT; USEFUL IN THE CASE OF NON-INTERVENTION TESTS. WHEN SWR 07 IS SET, ALL TEST NUMBER MESSAGES ARE SUPPRESSED.
NOTE: IT DOES NOT SUPPRESS ERROR PRINTOUTS.
- B) LOOP ON A SUB-TEST - (TRAP + 4 INSTRUCTION AND SWR 08 SET)
THIS IS GENERALLY USED TO ALLOW THE OPERATOR, BY SETTING SWR 08, TO CONTINUOUSLY LOOP ON ONE LOGICAL TEST OR GROUP OF TESTS.
- C) SCOPE ON A SUB-TEST - (TRAP + 10 - 70 INSTRUCTIONS AND SWR 09 - 11)
THIS ALLOWS THE OPERATOR TO SELECT SEVEN LEVELS OF LOOPING FACILITY WITHIN A SELECTION OR TEST.

IT IS USED TYPICALLY WITHIN A TEST WHERE ONE SUB TEST SETS A FLAG AND THE NEXT ONE CLEARS IT. BY USING SCOPE LEVEL 1 (SWR 09) - TRAP + 10), HE COULD LOOP ON THE FIRST SUB-TEST, SCOPE LEVEL 2 (SWR10) - TRAP + 20), HE COULD LOOP ON THE SECOND SUB-TEST OR SCOPE LEVEL 3 (SWR 10 & 09 - TRAP + 30) TO LOOP CONSTANTLY THROUGH BOTH SUB-TESTS SEQUENTIALLY. THE SCOPE RETURN ADDRESS ALWAYS APPEARS AS THE ARGUMENT OR NEXT WORD AFTER THE TRAP INSTRUCTION.

503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521

TO ALLOW THE SCOPE LEVEL TO BE CHANGED WITHOUT STOPPING THE PROGRAM, E.G. TO CHANGE FROM LEVEL 1 TO 2, WHICH WOULD ALMOST CERTAINLY CAUSE LEVEL 3 OR 0 TO BE SEEN MOMENTARILY), A 'PRESERVE SCOPE' FACILITY IS PROVIDED WITH SWR12. WHEN THIS IS SELECTED, THE PROGRAM NO LONGER INSPECTS SWR 11 - 09 BUT USES THE SETTING MEMORISED FROM BEFORE SWR 12 WAS SELECTED. THE SCOPE LEVEL MAY NOW BE CHANGED WITH NO EFFECT UNTIL SWR 12 IS SET TO 0, WHEN THE NEW SCOPE SETTING APPLIES.

N.B. SETTING SWR 12 SHOULD ONLY BE USED TO PRESERVE AS EXISTING SCOPE LEVEL, AS PREVIOUSLY SET ON THE SWITCH REGISTER.

WHICH SCOPE LEVEL TO SELECT MAY BE DETERMINED THE LISTING; LEVELS 1 THROUGH 7 ARE CALLED BY TRAP + 10 (SWR 09) THROUGH TRAP + 70 (SWR 09, 10 AND 11).

EXAMPLE OF SCOPE LOOP FACILITIES WITHIN DIAGNOSTIC

```

;TEST10: MOV      #40,COUNT      ;ITERATION COUNT.
T101:   BIS       #1,STATUS      ;SET GO BIT.
        BIT       #1,STATUS      ;IS GO BIT SET?
        BNE       T10SCP        ;YES, BRANCH.
        JSR       PC,ERROR      ;ERROR!!! GO NOT SET.
        10          ;ERROR NUMBER.
T10SCP: TRAP+10      ;SCOPE TEST10 IF LEVEL 1 SELECTED.
        T101          ;RETURN LABEL FOR SCOPE.
TEST11: BIC       #1,STATUS      ;CLEAR GO BIT
        BIT       #1,STATUS      ;GO BIT CLEAR ?
        BEQ       T11SCP        ;GO BIT CLEAR BRANCH.
        JSR       PC,ERROR      ;NO. GO BIT FAILED TO CLEAR.
        11          ;ERROR!!! NO. 11.
T11SCP: TRAP+30      ;SCOPE TEST 11 IF LEVEL 3 SELECTED.
        TEST11        ;RETURN LABEL FOR SCOPE.
        TRAP+20      ;SCOPE TESTS 10 & 11.
        T101          ;RTURN LABEL.
TEST12: BIS       #100,STATUS    ;NO SCOPE SELECTED. CARRY ON.
        BIT       #100,STATUS    ;IS DONE BIT SET ?
        (ETC.)
        .
        .
T12SCR: TRAP+10      ;SCOPE INT. EN. SET, LEVEL 1.
        TEST 12        ;RETURN LABEL.
TEST13: BIC       #100,STATUS    ;CLEAR INT ENABLE BIT.
        BIT       #100,STATUS    ;IS BIT CLEAR?
        (ETC.)
        .
        .
T13SCP: TRAP+30      ;SCOPE INT CLEAR LEVEL 3.
        TEST13        ;RETURN LABEL.
        TRAP+20      ;SCOPE INT. SET AND CLEAR.
        TEST12        ;LEVEL 2.
        TRAP+4        ;SCOPE LOOP ON THIS SET OF TESTS.
        T101          ;RETURN LABEL.
        DEC        COUNT        ;DO 40 TIMES ANYWAY
        BGT        T101
TEST14: (ETC.)
        .
        .
;

```

523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573

575		.ENDR
576		.TITLE VTV LOGIC TESTS
577		.SBTTL GENERAL DEFINITIONS
578		
579		
580	000000	R0=%00
581	000001	R1=%01
582	000002	R2=%02
583	000003	R3=%03
584	000004	R4=%04
585	000005	R5=%05
586	000006	R6=%06
587	000007	R7=%07
588	000006	SP=%06
589	000007	PC=%07
590	177776	PSW=177776
591	177570	HSWR=177570
592		
593		
594	172340	PAR0=172340
595	172342	PAR1=172342
596	172344	PAR2=172344
597	172346	PAR3=172346
598	172350	PAR4=172350
599	172352	PAR5=172352
600	172354	PAR6=172354
601	172356	PAR7=172356
602		
603	172300	PDR0=172300
604	172302	PDR1=172302
605	172304	PDR2=172304
606	172306	PDR3=172306
607	172310	PDR4=172310
608	172312	PDR5=172312
609	172314	PDR6=172314
610	172316	PDR7=172316
611		
612	177572	SRO=177572
613	177574	SR1=177574
614	177576	SR2=177576
615		
616	177546	LKS=177546
617		
618	177746	CA1170=177746
619		
620		
621	001000	REPCT1=1000
622	000100	REPCT2=100
623	000002	REPCT3=2
624		
625		
626		
627	100000	G=100000
628	040000	D=40000
629	020000	A=20000
630	010000	S=10000

631	004000	C=4000
632		
633		
634	177564	TPS=177564
635	177566	TPB=177566
636	177560	TKS=177560
637	177562	TKB=177562
638		
639		
640		
641		
642		
643		.ENABL ABS
644		.ENABL AMA
645		
646		
647		
648		
649		


```
651          .SBTTL  MACROS
652          :
653          :
654          : SET PROCESSOR PRIORITY
655          :
656          :
657          : .MACRO  PSWSET  $ARG,?LAB
658          : MOV     $ARG,-(SP)      ; SET UP NEW PSW AS $ARG
659          : MOV     #LAB,-(SP)     ; SET RETURN ADDRESS
660          : RTI      ; RTI TO SET PRIORITY
661          LAB:  NOP      ; RETURN ADDRESS
662          : .ENDM
663          :
664          :
665          : READ PROCESSOR PRIORITY
666          :
667          :
668          : .MACRO  PSWREA  $ARG
669          : EMT      ; ISSUE EMT TO READ PSW
670          : MOV     FSAVPW,$ARG    ; READ PSW IN $ARG
671          : .ENDM
672          :
673          :
```



```

675                                     .SBTTL  INITIALISATION
676                                     .ASECT
677                                     .=0
678                                     .=200
679 000200 000137 001000  JMP      @#START      ; JMP TO START AT 200
680                                     .=1000
681
682
683 001000 012706 001000  START:  MOV      #.,SP      ; INITIALISE STACK POINTER
684 001004                                     PSWSET  #340
685
686 001020 012737 014506 000004  MOV      #SWRSET,4    ; TEST FOR HARDWARE SWR
687 001026 012737 000340 000006  MOV      #340,6      ; TRAPS TO 4 IF IT
688 001034 012737 177570 014220  MOV      #HSWR,SWR   ; DOES NOT EXIST
689 001042 005777 013152  TST      @SWR
690 001046 005037 014246  CLR      SSWR      ; INITIALISE SOFTWARE SWR
691
692
693 ; NOW ESTABLISH WHETHER OR NOT WE ARE RUNNING ON A SINGLE
694 ; INTERRUPT LEVEL LSI-11.
695
696 001052 004737 014442  JSR      PC,SILLSI    ; ESTABLISH PROCESSOR TYPE
697
698 001056 004737 014516  JSR      PC,VECTOR    ; FILL 0-574 WITH HALT TRAPS
699 001062 004737 016632  JSR      PC,TYPOUT
700 001066 012272  GOMSG    ; DIAGNOSTIC
701 001070 004737 012062  JSR      PC,SET56
702
703
704 001074 004537 017510  JSR      R5,BUSSET    ; SET UP BUS AND VECTOR ADDRESSES
705 001100 007 004  .BYTE  7,4
706 001102 014222  .WORD  CSR
707 001104 001 001  .BYTE  1,1
708 001106 014242  .WORD  INTVEC
709 001110 014244  .WORD  VECLEV
710 001112 000000  .WORD  0
711
712
713
714 001114 013737 014226 014232  MOV      CAR,CARX
715 001122 013737 014226 014234  MOV      CAR,CARY
716 001130 005237 014234  INC      CARY
717 001134 013737 014230 014236  MOV      CHSR,CHDR
718 001142 013737 014230 014240  MOV      CHSR,CHAR
719 001150 005237 014240  INC      CHAR
720 001154 000137 001200  JMP      RSTART      ; THEN GOTO THE RESTART ADDRESS
721 001200 001200  .=1200
722 001200 012706 001000  RSTART: MOV      #START,SP    ; INITIALISE STACK POINTER
723 001204                                     PSWSET  #340
724
725 001220 004737 016632  JSR      PC,TYPOUT
726 001224 012736  WMSG    ; SELECT DESIRED CONSOLE SWITCHES
727 001226 004737 015344  START1: JSR      PC,MONIT  ; GO TO SWR MONITOR
728
729 001232 012706 001000  START2: MOV      #START,SP    ; INITIALISE STACK POINTER
730 001236                                     PSWSET  #340

```



```
731
732 001252 032777 000100 012740      BIT      #100,@SWR      ;CHECK FOR PRE-SELECTED TEST
733 001260 001002                      BNE      START3
734
735 001262 000137 001332              JMP      TEST0          ;TO TEST 0
736 001266 000137 001272      START3: JMP      TABLE        ;TO LOOK-UP TABLE
737
738
739
740
741
742                                ;INTERFACE REGISTERS AND VECTORS
743
744
745
```


747	001272	017700	012722	TABLE:	MOV	@SWR,R0	;GET SELECTED TEST NO
748	001276	042700	177700		BIC	#177700,R0	
749	001302	022700	000005		CMP	#5,R0	;CHECK FOR VALID TEST NO
750	001306	002734			BLT	RSTART	
751							
752	001310	006300			ASL	R0	
753	001312	000170	001316		JMP	@TABLE1(R0)	;JUMP TO PRE-SELECTED TEST
754							
755							
756							
757							
758							

759	001316	001332	TABLE1:	TEST0
760	001320	002776		TEST1
761	001322	004710		TEST2
762	001324	005734		TEST3
763	001326	006260		TEST4
764	001330	007676		TEST5


```

766      .SBTTL  TEST0
767      ;*****
768      ;THIS TEST CHECKS ALL THE READ/WRITE
769      ;BITS IN THE CSR FOR SETTING & CLEARING
770      ;*****
771
772 001332 012737 000000 014216 TEST0: MOV  #0,TESTNO      ;SET UP TEST NO.
773 001340 104402          TRAP+2
774 001342 001350          T0000
775 001344 004737 014416      JSR  PC,TESTR      ;OUTPUT TEST NO
776
777 001350 005037 014346      T0000: CLR  ERRDIS
778 001354 012704 000100      MOV  #REPC12,R4
779 001360 004737 015104      JSR  PC,FASTSW
780 001364 010437 014250      MOV  R4,REPCNT      ;SET UP TEST ITERATION COUNT
781
782 001370 000005      T0001: RESET
783 001372          PSWSET  #200      ;TURN OFF INTERRUPTS
784 001406 017737 012610 014336      MOV  @CSR,BAD      ;READ CSR
785 001414 042737 002000 014336      BIC  #2000,BAD      ;CLEAR 525 LINE BIT
786 001422 022737 000200 014336      CMP  #200,BAD      ;BAD SHOULD NOW EQUAL 200 OCTAL
787 001430 001411          BEQ  T0002      ;BRANCH IF IT DOES
788 001432 013737 014222 014344      MOV  CSR,ADDRES      ;SET UP FOR ERROR REPORT
789 001440 012737 000200 014334      MOV  #200,GOOD
790 001446 004737 020544      JSR  PC,ERROR
791 001452 120000          G+A+0      ;ERROR0, CSR DID NOT
792 001454 104440          T0002: TRAP+40      ;INITIALISE ON RESET
793 001456 001370          T0001          ;SCOPE LOOP ON RESET (SWR BIT11)
794 001460 032777 002000 012534 T0003: BIT  #2000,@CSR      ;IS 525 LINE BIT SET
795 001466 001004          BNE  1$      ;BRANCH IF SET
796
797          ;*ENTER THIS CODING IF CSR
798 001470 005737 012156          TST  L525      ;*READS SET TO 625 LINES
799          ;TEST TO SEE IF 625 LINES
800 001474 100033          BPL  T0004      ;WAS INPUT AT START REQUEST
801 001476 000403          BR  2$      ;O.K. 625 LINE WAS SELECTED
802          ;BRANCH TO ERROR REPORT
803          ;ENTER THIS CODING IF
804 001500 005737 012156      1$: TST  L525      ;525 LINE WAS READ
805 001504 100427          BMI  T0004      ;TEST TO SEE IF 525 LINE SELECTED
806 001506 013737 014222 014344 2$: MOV  CSR,ADDRES      ;O.K. 525 LINE WAS SELECTED
807 001514 017737 012502 014340      MOV  @CSR,DATA      ;SET UP FOR ERROR REPORT
808 001522 005737 012156          TST  L525
809 001526 100406          BMI  3$
810 001530 104402          TRAP+2
811 001532 001556          4$
812 001534 004737 016632      JSR  PC,TYP0UT      ;SELECT RIGHT ERROR MESSAGE
813 001540 002500          ERMES1      ;SUPPRES PRINTOUT (SWR BIT 7 )
814 001542 000405          BR  4$
815 001544 104402      3$: TRAP+2
816 001546 001556          4$
817 001550 004737 016632      JSR  PC,TYP0UT      ;ERROR MESSAGE 625 LINE EXPECTED
818 001554 002564          ERMES2
819 001556 004737 020544      4$: JSR  PC,ERROR      ;SUPPRES PRINTOUT (SWR BIT 7 )
820 001562 060001          A+D+1      ;ERROR MESSAGE 525 LINE EXPECTED
821 001564 104450      T0004: TRAP+50      ;ERROR 1 , WRONG STATE OF
          ;525 LINE BIT.
          ;SCOPE LOOP ON READING CSR

```



```

822 001566 001460 T0003 ;(SWR BITS 9 & 11 )
823
824 001570 112737 000060 002706 T0005: MOVB #'0,SETBIT ;* SET UP
825 001576 112737 000060 002707 MOVB #'0,SETBIT+1 ;* FOR ERROR
826 001604 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
827 001612 112737 000060 002763 MOVB #'0,CLRBIT+1 ;*
828 001620 012737 000001 002476 MOV #1,BITS ;SET TO TEST DISPLAY ON BIT
829 001626 004737 002210 JSR PC,TSTBIT ;SUBROUTINE FOR TESTING BIT
830
831
832 001632 112737 000060 002706 MOVB #'0,SETBIT ;* SET UP
833 001640 112737 000061 002707 MOVB #'1,SETBIT+1 ;* FOR ERROR
834 001646 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
835 001654 112737 000061 002763 MOVB #'1,CLRBIT+1 ;*
836 001662 012737 000002 002476 MOV #2,BITS ;SET TO TEST CURSOR ON BIT
837 001670 004737 002210 JSR PC,TSTBIT ;SUBROUTINE FOR TESTING BIT
838
839
840 001674 112737 000060 002706 MOVB #'0,SETBIT ;* SET UP
841 001702 112737 000062 002707 MOVB #'2,SETBIT+1 ;* FOR ERROR
842 001710 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
843 001716 112737 000062 002763 MOVB #'2,CLRBIT+1 ;*
844 001724 012737 000004 002476 MOV #4,BITS ;SET TO TEST CURSOR INC BIT
845 001732 004737 002210 JSR PC,TSTBIT ;SUBROUTINE TO TEST BIT
846
847
848
849 001736 112737 000060 002706 MOVB #'0,SETBIT ;* SET UP
850 001744 112737 000066 002707 MOVB #'6,SETBIT+1 ;* FOR ERROR
851 001752 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
852 001760 112737 000066 002763 MOVB #'6,CLRBIT+1 ;*
853 001766 012737 000100 002476 MOV #100,BITS ;TEST READY INT. ENAB. BIT
854 001774 004737 002210 JSR PC,TSTBIT ;SUBROUTINE TO TEST BIT
855
856
857 002000 112737 000060 002706 MOVB #'0,SETBIT ;* SET UP
858 002006 112737 000070 002707 MOVB #'8,SETBIT+1 ;* FOR ERROR
859 002014 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
860 002022 112737 000070 002763 MOVB #'8,CLRBIT+1 ;*
861 002030 012737 000400 002476 MOV #400,BITS ;SET TO TEST 6H BIT
862 002036 004737 002210 JSR PC,TSTBIT ;SUBROUTINE TO TEST BIT
863
864
865 002042 112737 000060 002706 MOVB #'0,SETBIT ;* SET UP
866 002050 112737 000071 002707 MOVB #'9,SETBIT+1 ;* FOR ERROR
867 002056 112737 000060 002762 MOVB #'0,CLRBIT ;* REPORT
868 002064 112737 000071 002763 MOVB #'9,CLRBIT+1 ;*
869 002072 012737 001000 002476 MOV #1000,BITS ;SET TO TEST 6V BIT
870 002100 004737 002210 JSR PC,TSTBIT ;SUBROUTINE TO TEST BITS
871
872
873 002104 112737 000061 002706 MOVB #'1,SETBIT ;* SET UP
874 002112 112737 000065 002707 MOVB #'5,SETBIT+1 ;* FOR ERROR
875 002120 112737 000061 002762 MOVB #'1,CLRBIT ;* REPORT
876 002126 112737 000065 002763 MOVB #'5,CLRBIT+1 ;*
877 002134 012737 100000 002476 MOV #100000,BITS ;SET UP FOR TESTING TIMER BIT
  
```



```

878 002142 004737 002210      JSR      PC,TSTBIT      ;SUBROUTINE FOR TESTING BIT
879
880
881
882 002146 104460      TRAP+60      ;SCOPE LOOP ON SETTING AND
883 002150 001570      T0005        ;CLEARING BITS IN CSR
884                                ;(SWR BITS 10 & 11 )
885
886
887 002152 104404      TRAP+4        ;SET SWR BIT 8 TO
888 002154 001370      T0001        ;LOOP ON TEST
889 002156 005337 014250      DEC      REPCNT      ;DONE ENOUGH ?
890 002162 001402      BEQ      T0007      ;YES
891 002164 000137 001370      JMP      T0001      ;NO
892
893 002170 032777 000100 012022 T0007: BIT      #100,@SWR      ;CHECK FOR PRE-SELECTED TEST
894 002176 001402      BEQ      T0008      ;
895 002200 000137 001232      JMP      START2
896 002204 000137 002776      T0008: JMP      TEST1
897
898
899
  
```



```

901
902
903
904
905
906
907
908 002210 012737 000200 014334 TSTRIT: MOV #200,GOOD ;*SET UP
909 002216 005737 012156 TST L525 ;*GOOD WITH BITS
910 002222 100003 BPL TSTB1 ;*THAT SHOULD ALWAYS
911 002224 052737 002000 014334 BIS #2000,GOOD ;*BE READ AS 1
912 002232 005077 011764 TSTB1: CLR @CSR ;
913 002236 053777 002476 011756 BIS BITS,@CSR ;TRY TO SET BIT IN CSR
914 002244 017737 011752 014336 MOV @CSR,BAD ;READ CSR
915 002252 053737 002476 014334 BIS BITS,GOOD ;SET UP GOOD DATA
916 002260 023737 014334 014336 CMP GOOD,BAD ;DID CSR CONTAIN EXPECTED DATA
917 002266 001415 BEQ TSTB2 ;BRANCH IF O.K.
918 002270 013737 014222 014344 MOV CSR,ADDRES ;SET UP FOR ERROR REPORT
919 002276 011637 014352 MOV @SP,CALLPC ;
920 002302 104402 TRAP+2 ;INHIBIT PRINTOUT (SWR BIT 7 )
921 002304 002314 1$ ;
922 002306 004737 016632 JSR PC,TYPOUT ;ERROR WHEN TRYING TO SET
923 002312 002650 ERMES3 ;BIT ** IN CSR
924 002314 004737 020544 1$: JSR PC,ERROR ;ERROR 2
925 002320 124002 C+A+G+2 ;
926 002322 104410 TSTB2: TRAP+10 ;SCOPE LOOP ON SETTING BIT
927 002324 002232 TSTB1 ;(SWR BIT 9 )
928
929 002326 012777 177767 011666 TSTB3: MOV #177767,@CSR ;SET ALL BITS IN CSR
930 002334 012737 141707 014334 MOV #141707,GOOD ;SET UP GOOD
931 002342 005037 002474 CLR RETRY ;CLEAR RETRY COUNT
932 002346 005737 012156 TST L525 ;
933 002352 100003 BPL 1$ ;
934 002354 052737 002000 014334 BIS #2000,GOOD ;
935 002362 043777 002476 011632 1$: BIC BITS,@CSR ;TRY TO CLEAR BIT IN CSR
936 002370 017737 011626 014336 MOV @CSR,BAD ;READ CSR
937 002376 043737 002476 014334 BIC BITS,GOOD ;SET UP GOOD DATA
938 002404 023737 014334 014336 CMP GOOD,BAD ;DID CSR CONTAIN EXPECTED DATA
939 002412 001423 BEQ TSTB4 ;BRANCH IF O.K.
940 002414 005737 002476 TST BITS ;IF WE ARE NOT TESTING TIMER ENABLE
941 002420 100003 BPL 3$ ;THEN THIS IS A LEGITIMATE ERROR
942 002422 005137 002474 COM RETRY ;ELSE ALLOW ONE RETRY
943 002426 001355 BNE 1$ ;BECAUSE THE TIMER MIGHT HAVE FIRED
944 002430 011637 014352 3$: MOV @SP,CALLPC ;SET UP FOR ERROR REPORT
945 002434 013737 014222 014344 MOV CSR,ADDRES ;
946 002442 104402 TRAP+2 ;INHIBIT PRINTOUT (SWR BIT 7 )
947 002444 002454 2$ ;
948 002446 004737 016632 JSR PC,TYPOUT ;ERROR WHEN TRYING TO CLEAR
949 002452 002722 ERMES4 ;BIT ** IN CSR
950 002454 004737 020544 2$: JSR PC,ERROR ;ERROR 3
951 002460 124003 C+A+G+3 ;
952
953 002462 104420 TSTB4: TRAP+20 ;SCOPE LOOP ON CLEARING BIT
954 002464 002326 TSTB3 ;(SWR BIT 10 )
955 002466 104430 TRAP+30 ;SCOPE LOOP ON SETTING AND CLEARING
956 002470 002232 TSTB1 ;BIT IN CSR (SWR BITS 9 & 10 )

```



```
957 002472 000207          RTS      PC          ;END OF SUBROUTINE.
958
959
960 002474 000000          RETRY: 0
961 002476 000000          BITS: 0
962
963          .NLIST      BEX
964 002500 052133 051505 044524 ERMES1: .ASCII /[TESTING FOR 625 LINES, CSR BIT 10 READS 525 LINES[2/
965 002564 052133 051505 044524 ERMES2: .ASCII /[TESTING FOR 525 LINES, CSR BIT 10 READS 625 LINES[2/
966 002650 042533 051122 051117 ERMES3: .ASCII /[ERROR WHEN TRYING TO SET BIT /
967          .EVEN
968 002706 000000          SETBIT: .WORD 0
969 002710 044440 020116 051503          .ASCII / IN CSR [2/
970 002722 042533 051122 051117 ERMES4: .ASCII /[ERROR WHEN TRYING TO CLEAR BIT /
971          .EVEN
972 002762 000000          CLRBIT: .WORD 0
973 002764 044440 020116 051503          .ASCII / IN CSR [2/
974          .EVEN
975          .LIST      BEX
976
```



```

978 .SBTTL TEST1
979 ;*****
980 ;THIS TEST CHECKS THE READY AND TIMER
981 ;INTERRUPTS. IT DOES NOT CHECK THAT
982 ;NO INTERRUPT OCCURES WHEN THE READY
983 ;BIT IS CLEAR (THIS IS DONE IN TEST 5).
984 ;*****
985
986 002776 012737 000001 014216 TEST1: MOV #1,TESTNO ;SET UP TEST NO.
987 003004 104402 TRAP+2
988 003006 003014 T1000
989 003010 004737 014416 JSR PC,TESTR ;OUTPUT TEST NO
990
991 003014 005037 014346 T1000: CLR ERDIS
992 003020 012704 000100 MOV #REPC2,R4
993 003024 004737 015104 JSR PC,FASTSW
994 003030 010437 014250 MOV R4,REPCNT ;SET UP TEST ITERATION COUNT
995
996 003034 000005 T1001: RESET ;INITIALISE HARDWARE
997 003036 PSWSET #200 ;TURN OFF INTERRUPTS
998 003052 013700 014242 MOV INTVEC,R0
999 003056 012720 004206 MOV #INTSRV,(R0)+ ;SET UP INTERRUPT VECTOR
1000 003062 012710 000200 MOV #200,(R0)
1001 003066 017737 011130 014336 MOV @CSR,BAD ;READ CSR
1002 003074 032737 000200 014336 BIT #200,BAD ;WAS READY BIT SET
1003 003102 001017 BNE 2$ ;BRANCH IF O.K.
1004 003104 013737 014222 014344 MOV CSR,ADDRES ;* SET UP
1005 003112 012737 000200 014334 MOV #200,GOOD ;* FOR ERROR
1006 003120 005737 012156 TST L525 ;* REPORT
1007 003124 100003 BPL 1$
1008 003126 052737 002000 014334 BIS #2000,GOOD
1009 003134 004737 020544 1$: JSR PC,ERROR ;ERROR 10 , READY BIT NOT SET
1010 003140 120000 A+G+0
1011 003142 104410 2$: TRAP+10 ;SCOPE LOOP ON RESET (SWR BIT 9 )
1012 003144 003034 T1001
1013
1014
1015 003146 005037 004272 T1002: CLR INTFLG ;CLEAR INTERRUPT FLAG
1016 003152 017737 011044 014342 MOV @CSR,STATUS
1017 003160 PSWSET #0 ;TURN ON INTERRUPTS
1018 003174 000240 NOP ;WAIT FOR INTERRUPT
1019 003176 000240 NOP
1020 003200 PSWSET #200 ;TURN OFF INTERRUPTS
1021 003214 005737 004272 TST INTFLG ;DID IT INTERRUPT ?
1022 003220 001413 BEQ T1004 ;BRANCH IF NO INTERRUPT OCCURED
1023 003222 013737 014222 014344 MOV CSR,ADDRES ;SET UP FOR ERROR REPORT
1024 003230 104402 TRAP+2 ;INHIBIT ERROR MESSAGE
1025 003232 003242 T1003
1026 003234 004737 016632 JSR PC,TYP0UT ;INTERRUPT WHEN ENABLE CLEAR
1027 003240 004361 ERMS10
1028 003242 004737 020544 T1003: JSR PC,ERROR ;ERROR 1 , UNEXPECTED INTERRUPT
1029 003246 030001 A+S+1
1030 003250 104420 T1004: TRAP+20 ;SCOPE LOOP ON INTERRUPT (SWR BIT 10 )
1031 003252 003146 T1002
1032
1033

```


SEQ 0026

Address	Hex	Hex	Hex	Hex	Assembly	Comment
1034						
1035	003254	005037	004272		T1008: CLR	;CLEAR INTERRUPT FLAG
1036	003260	052777	000100	010734	BIS	#100,@CSR ;SET READY INTERRUPT ENABLE
1037	003266	017737	010730	014342	MOV	@CSR,STATUS ;
1038	003274				PSWSET	#0 ;TURN ON INTERRUPTS
1039	003310	000240			NOP	;WAIT FOR INTERRUPT
1040	003312	000240			NOP	;
1041	003314				PSWSET	#200 ;TURN OFF INTERUPTS
1042	003330	005737	004272		TST	INTFLG ;TEST FOR INTERRUPT
1043	003334	001013			BNE	T1009 ;BRANCH IF INTERRUPT OCCURED
1044	003336	013737	014222	014344	MOV	CSR,ADDRES ;SET UP FOR ERROR REPORT
1045	003344	104402			TRAP+2	;INHIBIT ERROR MESSAGE
1046	003346	003356			1\$	; (SWR BIT 7)
1047	003350	004737	016632		JSR	PC,TYPOUT ;NO INTERRUPT OCCURED
1048	003354	004473				ERMS12 ;
1049	003356	004737	020544		1\$: JSR	PC,ERROR ;ERROR 13 ,
1050	003362	030003				A+S+3 ;
1051	003364	104440			T1009: TRAP+40	;SCOPE LOOP ON INTERRUPT
1052	003366	003254			T1008	;
1053						
1054						
1055						
1056						
1057						

1059	003370	005037	004272		T1012:	CLR	INTFLG	:CLEAR INTERRUPT FLAG
1060	003374	052777	100000	010620		BIS	#100000,@CSR	:SER TIMER BIT
1061	003402	017737	010614	014342		MOV	@CSR,STATUS	
1062	003410					PSWSET	#0	:TURN ON INTERUPTS
1063	003424	000240				NOP		:WAIT FOR INTERRUPT
1064	003426	000240				NOP		
1065	003430					PSWSET	#200	:TURN OFF INTERUPTS
1066	003444	005737	004272			TST	INTFLG	:TEST IF INTERRUPT OCCURED
1067	003450	001013				BNE	T1013	:BRANCH IF INTERRUPT OCCURED
1068	003452	013737	014222	014344		MOV	CSR,ADDRE	:SET UP FOR ERROR REPORT
1069	003460	104402				TRAP+2		:INHIBIT ERROR MESSAGE
1070	003462	003472				1\$		: (SWR BIT 7)
1071	003464	004737	016632			JSR	PC,TYPOUT	:NO INTERRUPT AT DEVICE LEVEL
1072	003470	004473					ERMS12	
1073	003472	004737	020544		1\$:	JSR	PC,ERROR	:ERROR 15 ,
1074	003476	030005					S+A+5	
1075	003500	104460			T1013:	TRAP+60		:SCOPE LOOP ON TIMER INTERRUPT
1076	003502	003370				T1012		: (SWR BITS 10 & 11)
1077								
1078								
1079								
1080								
1081								
1082								
1083								
1084								
1085	003504	005037	004202		T1014:	CLR	WTC1	:*SET UP
1086	003510	012737	000002	004204		MOV	#2,WTCO	:*TIME OUT
1087	003516	005037	004272			CLR	INTFLG	:CLEAR INTERRUPT FLAG
1088	003522	012777	040000	010472		MOV	#40000,@CSR	:ENABLE TIMER INTERRUPT
1089	003530					PSWSET	#0	:TURN ON INTERUPTS
1090	003544	004737	004156		T1015:	JSR	PC,WAIT	:WAIT FOR TIME OUT
1091	003550	103004				BCC	T1016	: BRANCH IF TIMED OUT
1092	003552	005737	004272			TST	INTFLG	:TEST FOR INTERRUPT
1093	003556	001027				BNE	T1017	:BRANCH IF INTERRUPT O.K.
1094	003560	000771				BR	T1015	:GO BACK AND WAIT SOME MORE
1095	003562				T1016:	PSWSET	#200	:TURN OFF INTERUPTS
1096	003576	017737	010420	014342		MOV	@CSR,STATUS	:SET UP FOR ERROR REPORT
1097	003604	013737	014222	014344		MOV	CSR,ADDRES	
1098	003612	005077	010404			CLR	@CSR	:CLEAR CSR
1099	003616	104402				TRAP+2		:INHIBIT ERRER PRINTOUT
1100	003620	003630				1\$		
1101	003622	004737	016632			JSR	PC,TYPOUT	:NO INTERRUPT BEFORE TIMEOUT
1102	003626	004531					ERMS13	
1103	003630	004737	020544		1\$:	JSR	PC,ERROR	:ERROR 16
1104	003634	030006					S+A+6	
1105	003636	032737	100000	014342	T1017:	BIT	#100000,STATUS	:WAS TIMER BIT CLEARED
1106	003644	001415				BEQ	T1017A	:YES,SO BRANCH
1107	003646	013737	014222	014344		MOV	CSR,ADDRES	:NO,SO SET ERROR REPORT
1108	003654	032777	040000	010336		BIT	#40000,@SWR	:SWR BIT 14 TO
1109	003662	001003				BNE	1\$	:INHIBIT PRINTOUT
1110	003664	004737	016632			JSR	PC,TYPOUT	:ERROR TIMER BIT WAS NOT
1111	003670	004602					ERMS14	:CLEARED BY BIC
1112	003672	004737	020544		1\$:	JSR	PC,ERROR	:ERROR 10,
1113	003676	030010					A+S+10 ;	
1114	003700	104470			T1017A:	TRAP+70		:SCOPE LOOP ON INTERRUPT


```
1115 003702 003504          T1014          ;(SWR BITS 9 , 10 & 11 )
1116
1117
1118
1119 003704 005337 014250    DEC      REPCNT    ;DONE ENOUGH ?
1120 003710 001402          BEQ      T1018      ;YES
1121 003712 000137 003034    JMP      T1001      ;NO
1122
1123
1124
```


1126	003716	013700	014242		T1018:	MOV	INTVEC,R0	:*SET UP
1127	003722	012720	004230			MOV	#TIME1,(R0)+	:*INTERRUPT
1128	003726	012710	000340			MOV	#340,(R0)	:*VECTOR
1129	003732	005737	012156			TST	L525	:TEST FOR 625 OR 525 LINES
1130	003736	100404				BMI	1\$	:BRANCH IF 525 LINES
1131	003740	012737	000062	004270		MOV	#50.,SECOND	:SET 50 INTERRUPTS = 1 SECOND
1132	003746	000403				BR	2\$	:
1133	003750	012737	000074	004270	1\$:	MOV	#60.,SECOND	:SET 60 INTERRUPTS = 1 SECOND
1134	003756	004737	016632		2\$:	JSR	PC,TYPOUT	:PRINT INSTRUCTIONS
1135	003762	004276					BELLS	:BELLS WILL RING EVERY SECOND
1136								:FOR 10 SECONDS
1137	003764	012737	000012	004266	T1019:	MOV	#10.,COUNT2	:
1138	003772	013737	004270	004264		MOV	SECOND,COUNT1	:
1139	004000	005037	004272			CLR	INTFLG	:CLEAR INTERRUPT FLAG
1140	004004	012777	040000	010210		MOV	#40000,@CSR	:ENABLE TIMER INTERRUPT
1141	004012	005037	004202		T1019A:	CLR	WTC1	:*SET UP
1142	004016	012737	000002	004204		MOV	#2,WTC0	:*TIME OUT
1143	004024					PSWSET	#0	:TURN ON INTERUPTS
1144	004040	004737	004156		T1020:	JSR	PC,WAIT	:WAIT FOR TIMEOUT
1145	004044	103025				BCC	T1022	:TIMED OUT WAITING FOR INTERRUPT
1146	004046	005737	004272			TST	INTFLG	:TEST FOR INTERRUPT
1147	004052	001001				BNE	T1021	:O.K. BRANCH IF INTERRUPT
1148	004054	000771				BR	T1020	:NO INTERRUPT SO WAIT SOME MORE
1149	004056	005037	004272		T1021:	CLR	INTFLG	:CLEAR INTERRUPT FLAG
1150	004062	005737	004274			TST	BELLS	:SHOULD WE RING BELL ?
1151	004066	001764				BEQ	T1020	:BRANCH IF NO
1152	004070	012700	000007			MOV	#7,R0	:*RING
1153	004074	004737	016710			JSR	PC,PCHR	:*BELL
1154	004100	005037	004274			CLR	BELLS	:CLEAR BELL FLAG
1155	004104	005337	004266			DEC	COUNT2	:DECREMENT BELL COUNT
1156	004110	001340				BNE	T1019A	:BRANCH IF MORE RINGS REQUIRED
1157	004112	005077	010104			CLR	@CSR	:DONE ENOUGH SO CLEAR CSR
1158	004116	000403				BR	T1023	:COMPLETE BRANCH TO END OF TEST
1159								
1160	004120	004737	020544		T1022:	JSR	PC,ERROR	:ERROR TIME OUT
1161	004124	000007					7	
1162								
1163	004126	104410			T1023:	TRAP+10		:LOOP ON BELL
1164	004130	003764				T1019		
1165								
1166	004132	104404			T10WW:	TRAP+4		:SET SWR BIT 8 TO
1167	004134	003034				T1001		:LOOP ON TEST
1168	004136	032777	000100	010054		BIT	#100,@SWR	:CHECK FOR PRE-SELECTED TEST
1169	004144	001402				BEQ	1\$	
1170	004146	000137	001232			JMP	START2	
1171	004152	000137	004710		1\$:	JMP	TEST2	:
1172								
1173								
1174								
1175	004156	005337	004202		WAIT:	DEC	WTC1	:DECREMENT TEMPORARY COUNT
1176	004162	001005				BNE	5\$	:EXIT IF NOT ZERO
1177	004164	005337	004204			DEC	WTC0	:DECREMENT TIMER COUNT
1178	004170	001002				BNE	5\$	:EXIT IF NOT ZERO
1179	004172	000241				CLC		:TIMED OUT
1180	004174	000207				RTS	PC	:EXIT RETURN
1181	004176	000261			5\$:	SEC		:NOT TIMED OUT EXIT


```

1182 004200 000207          RTS      PC      ;
1183
1184 004202 000000          WTC1:    0
1185 004204 000000          WTC0:    0
1186
1187
1188 004206 005237 004272    INTSRV: INC      INTFLG      ;SET INTERRUPT FLAG
1189 004212 042777 140100 010002    BIC      #140100,@CSR ;CLEAR INTERRUPT & ENABLE BITS
1190 004220 017737 007776 014342    MOV      @CSR,STATUS ;SAVE CONTENTS OF CSR
1191 004226 000002          RTI
1192
1193 004230 042777 100000 007764    TIME1: BIC      #100000,@CSR ;CLEAR TIMER BIT
1194 004236 005237 004272          INC      INTFLG      ;SET INTERRUPT BIT
1195 004242 005337 004264          DEC      COUNT1
1196 004246 001005          BNE      TIME1A      ;IS 1 SECOND UP
1197 004250 005237 004274          INC      BELLS
1198 004254 013737 004270 004264    MOV      SECOND,COUNT1 ;YES , SO SET BELL
1199 004262 000002          TIME1A: RTI      ;SET UP TIME TO NEXT BELL
1200
1201 004264 000000          COUNT1: 0
1202 004266 000000          COUNT2: 0
1203 004270 000000          SECOND: 0
1204 004272 000000          INTFLG: 0
1205 004274 000000          BELLS: 0
1206
1207
1208
1209 004276 041133 046105 020114    BELLMS: .NLIST BEX
1210 004361      133 044440 052116    ERMS10: .ASCII /[BELL SHOULD RING 10 TIMES AT 1 SECOND INTERVALS [a/
1211 004427      133 044440 052116    ERMS11: .ASCII /[ INTERRUPT OCCURED WITH ENABLE CLEARa/
1212 004473      133 047040 020117    ERMS12: .ASCII /[ INTERRUPT OCCURED AT WRONG LEVEL a/
1213 004531      133 047040 020117    ERMS13: .ASCII /[ NO INTERRUPT WHEN EXPECTED a/
1214 004602 020133 044524 042515    ERMS14: .ASCII /[ NO TIMER INTERRUPT IN 20 MILLISECONDS a/
1215 004660 040440 052106 051105    .ASCII  /[ TIMER BIT WAS NOT CLEARED BY BIC INSTRUCTION/
1216                                     .ASCII  / AFTER TIMER INTERRUPT a/
1217                                     .EVEN
                                     .LIST BEX

```



```

1219 .SBTTL TEST2
1220 ;*****
1221 ;THIS TEST CHECKS THE OPERATION OF
1222 ;THE CHARACTER STORE ADDRESS REGISTER
1223 ;IN LOADING , READING & INCREMENTING.
1224 ;*****
1225
1226 004710 012737 000002 014216 TEST2: MOV #2,TESTNO ;SET UP TEST NO.
1227 004716 104402 TRAP+2
1228 004720 004726 T2000
1229 004722 004737 014416 JSR PC,TESTR ;OUTPUT TEST NO
1230
1231 004726 005037 014346 T2000: CLR ERRDIS
1232 004732 012704 000100 MOV #REPC2,R4
1233 004736 004737 015104 JSR PC,FASTSW
1234 004742 010437 014250 MOV R4,REPCNT ;SET UP TEST ITERATION COUNT
1235
1236 004746 000005 T2001: RESET
1237 004750 117737 007264 014336 MOVB @CHAR,BAD ;READ CHARACTER STORE ADDRESS REGISTER
1238 004756 105037 014337 CLRB BAD+1
1239 004762 005737 014336 TST BAD ;CHECK WHAT WAS READ
1240 004766 001417 BEQ T2002 ;BRANCH IF IT WAS ZERO
1241 004770 013737 014240 014344 MOV CHAR,ADDRES ;SET UP FOR ERROR REPORT
1242 004776 005037 014334 CLRB GOOD
1243 005002 032777 040000 007210 BIT #40000,@SWR ;SET SWR BIT 14 TO INHIBIT
1244 005010 001003 BNE 1$ ;ERROR PRINTOUT
1245 005012 004737 016632 JSR PC,TYPOUT ;CHARACTER ADDRESS REGISTER ERROR
1246 005016 005662 ERMS20
1247 005020 004737 020544 1$: JSR PC,ERROR ;ERROR 0
1248 005024 120000 A+G+0
1249 005026 104410 T2002: TRAP+10 ;SCOPE LOOP ON RESET
1250 005030 004746 T2001 ;(SWR BIT 9 )
1251
1252 005032 012703 000001 T2003: MOV #1,R3 ;SET R3 FOR FIRST DATA PATTERN
1253 005036 012702 000020 T2003A: MOV #20,R2 ;REPEAT COUNT FOR EACH PATTERN
1254 005042 004737 020246 T2004: JSR PC,GENER ;* SET UP
1255 005046 010037 014334 MOV R0,GOOD ;* DATA PATTERN
1256 005052 105037 014335 CLRB GOOD+1 ;* IN GOOD
1257 005056 113777 014334 007154 T2004A: MOVB GOOD,@CHAR ;LOAD CHARACTER ADDRESS REGISTER
1258 005064 117737 007150 014336 MOVB @CHAR,BAD ;READ IT BACK
1259 005072 105037 014337 CLRB BAD+1
1260 005076 042737 000200 014334 BIC #200,GOOD
1261 005104 023737 014334 014336 CMP GOOD,BAD ;WAS IT LOADED CORRECTLY
1262 005112 001415 BEQ T2005 ;BRANCH IF O.K.
1263 005114 013737 014240 014344 MOV CHAR,ADDRES ;SET UP FOR ERROR REPORT
1264 005122 032777 040000 007070 BIT #40000,@SWR ;SET SWR BIT 14 TO INHIBIT
1265 005130 001003 BNE 1$ ;ERROR PRINTOUT
1266 005132 004737 016632 JSR PC,TYPOUT ;CHARACTER ADDRESS REGISTER ERROR
1267 005136 005662 ERMS20
1268 005140 004737 020544 1$: JSR PC,ERROR ;ERROR 1
1269 005144 120001 A+G+1
1270 005146 104420 T2005: TRAP+20 ;SCOPE LOOP ON THIS PATTERN
1271 005150 005056 T2004A ;( SWR BIT 10 )
1272
1273 005152 104430 TRAP+30 ;SCOPE LOOP ON CHANGING PATTERN
1274 005154 005042 T2004 ;(SWR BITS 9 & 10 )

```


1275					
1276	005156	005302	DEG	R2	;HAVE WE DONE ENOUGH OF THIS PATTERN
1277	005160	001330	BNE	T2004	;BRANCH IF NO
1278	005162	005203	INC	R3	;NEXT PATTERN
1279	005164	020327	CMP	R3,#7	;HAVE WE DONE ALL PATTERNS.
1280	005170	100722	BMI	T2003A	;BRANCH IF NO
1281					


```

1283
1284
1285
1286
1287
1288
1289
1290 005172 000005          T2006: RESET
1291 005174 012701 000004          MOV      #4,R1
1292 005200 012737 000000 014334 T2007: MOV      #0,GOOD
1293 005206 112777 000000 007022      MOVB     #0,@CHDR
1294
1295 005214 117737 007020 014336      MOVB     @CHAR,BAD
1296 005222 105037 014337          CLRB     BAD+1
1297 005226 005737 014336          TST      BAD
1298 005232 001016          BNE      T2008
1299 005234 005301          DEC      R1
1300 005236 001360          BNE      T2007
1301 005240 117737 006774 014336      MOVB     @CHAR,BAD
1302 005246 105037 014337          CLRB     BAD+1
1303 005252 022737 000001 014336      CMP      #1,BAD
1304 005260 001415          BEQ      T2009
1305 005262 012737 000001 014334      MOV      #1,GOOD
1306 005270 032777 040000 006722 T2008: BIT      #40000,@SWR
1307 005276 001003          BNE      1$
1308 005300 004737 016632          JSR      PC,TYP0UT
1309 005304 005662          ERMS20
1310 005306 004737 020544          1$: JSR      PC,ERROR
1311 005312 120002          A+G+2
1312 005314 104440          T2009: TRAP+40
1313 005316 005172          T2006
1314
1315
1316
1317 005320 000005          T2010: RESET
1318 005322 012777 001000 006672      MOV      #1000,@CSR
1319 005330 012701 000003          MOV      #3,R1
1320 005334 012737 000000 014334 T2011: MOV      #0,GOOD
1321 005342 112777 000000 006666      MOVB     #0,@CHDR
1322
1323 005350 117737 006664. 014336      MOVB     @CHAR,BAD
1324 005356 105037 014337          CLRB     BAD+1
1325 005362 005737 014336          TST      BAD
1326 005366 001014          BNE      T2012
1327 005370 005301          DEC      R1
1328 005372 001360          BNE      T2011
1329 005374 117737 006640 014336      MOVB     @CHAR,BAD
1330 005402 022737 000001 014336      CMP      #1,BAD
1331 005410 001415          BEQ      T2013
1332 005412 012737 000001 014334      MOV      #1,GOOD
1333 005420 032777 040000 006572 T2012: BIT      #40000,@SWR
1334 005426 001003          BNE      1$
1335 005430 004737 016632          JSR      PC,TYP0UT
1336 005434 005662          ERMS20
1337 005436 004737 020544          1$: JSR      PC,ERROR
1338 005442 120003          A+G+3

```

```

*****
THIS PART OF THE TEST CHECKS THAT
CHAR (CHSR TOP BYTE )WILL INCREMENT
WHEN :-
CHDR (CHSR LOW BYTE )IS LOADED
OR CHSR IS READ
*****
;INITALISE HARDWARE
;
;SET UP GOOD FOR ERROR REPORT
;LOAD SOMETHING TO CHARACTER STORE
;DATA REGISTER
;READ CHARACTER ADDRESS REGISTER
;
;IT SHOULD READ ZERO
;BRANCH TO ERROR REPORT IF NOT
;DO THIS 4 TIMES
;BRANCH IF MORE TO DO
;READ CHACACTER ADDRESS REGISTER
;
;BAD SHOULD NOW CONTAIN 1
;BRANCH IF O.K.
;SET UP FOR ERROR REPORT
;SET SWR BIT 14 TO INHIBIT
;ERROR PRINTOUT
;CHARACTER STORE ADDRESS REGISTER
;INCREMENT ERROR
;ERROR 2,ADDRESS SHOULD ONLY
;AFTER 8 DATA LOADS OR READS
;SCOPE LOOP ON RESET AND LOAD
;(SWR BIT 11 )

```

```

;INITALISE HARDWARE
;SET 6V BIT
;
;SET UP GOOD FOR ERROR REPORT
;LOAD SOMETHING TO CHARACTER STORE
;DATA REGISTER
;READ CHARACTER ADDRESS REGISTER
;
;IT SHOULD READ ZERO
;BRANCH TO ERROR REPORT IF NOT
;DO THIS 4 TIMES
;BRANCH IF MORE TO DO
;READ CHARACTER ADDRESS REGISTER
;BAD SHOULD NOW CONTAIN 1
;BRANCH IF O.K.
;SET UP FOR ERROR REPORT
;SET SWR BIT 14 TO INHIBIT
;ERROR PRINTOUT
;CHARACTER STORE ADDRESS REGISTER
;INCREMENT ERROR
;ERROR 3,ADDRESS SHOULD ONLY
;AFTER 6 DATA LOADS OR READS

```



```

1339 005444 104450          T2013: TRAP+50          ;SCOPE LOOP ON RESET AND LOAD
1340 005446 005320          T2010          ; (SWR BIT 9 & 11 )
1341
1342
1343
1344
1345
1346 005450 005077 006546    T2014: CLR      @CSR          ;
1347 005454 112777 000000 006556    MOV      #0,@CHAR      ;LOAD CHARACTER ADDRESS REGISTER
1348 005462 112777 000000 006546    MOV      #0,@CHDR      ;DO TWO LOADS TO DATA REGISTER
1349 005470 112777 000000 006540    MOV      #0,@CHDR      ;TO INCREMENT INVISIBLE BITS
1350 005476 112777 000000 006534    MOV      #0,@CHAR      ;LOAD ADDRESS REGISTER AGAIN
1351
1352
1353 005504 012701 000004          MOV      #4,R1          ;
1354 005510 012737 000000 014334    T2015: MOV      #0,GOOD      ;SET UP GOOD FOR ERROR REPORT
1355 005516 112777 000000 006512    MOV      #0,@CHDR      ;LOAD SOMETHING TO CHARACTER STORE
1356
1357 005524 117737 006510 014336    MOV      @CHAR,BAD      ;DATA REGISTER
1358 005532 105037 014337          CLR      BAD+1          ;READ CHARACTER ADDRESS REGISTER
1359 005536 005737 014336          TST      BAD            ;
1360 005542 001016          BNE      T2016          ;IT SHOULD READ ZERO
1361 005544 005301          DEC      R1            ;BRANCH TO ERROR REPORT IF NOT
1362 005546 001360          BNE      T2015          ;DO THIS 4 TIMES
1363 005550 117737 006464 014336    MOV      @CHAR,BAD      ;BRANCH IF MORE TO DO
1364 005556 105037 014337          CLR      BAD+1          ;READ CHACACTER ADDRESS REGISTER
1365 005562 022737 000001 014336    CMP      #1,BAD          ;
1366 005570 001415          BEQ      T2017          ;BAD SHOULD NOW CONTAIN 1
1367 005572 012737 000001 014334    MOV      #1,GOOD          ;BRANCH IF O.K.
1368 005600 032777 040000 006412    T2016: BIT      #40000,@SWR ;SET UP FOR ERROR REPORT
1369 005606 001003          BNE      1$            ;SET SWR BIT 14 TO INHIBIT
1370 005610 004737 016632          JSR      PC,TYP0UT        ;ERROR PRINTOUT
1371 005614 005662          ERMS20          ;CHARACTER STORE ADDRESS REGISTER
1372 005616 004737 020544          1$: JSR      PC,ERROR      ;INCREMENT ERROR
1373 005622 120004          T2017: TRAP+60          ;ERROR 4,ADDRESS SHOULD ONLY
1374 005624 104460          T2014          ;AFTER 8 DATA LOADS OR READS
1375 005626 005450          TRAP+4          ;SCOPE LOOP ON READ AND LOAD
1376 005630 104404          T2003          ; (SWR BIT 10 & 11 )
1377 005632 005032          ;SET SWR BIT 8 TO
1378
1379
1380 005634 005337 014250          DEC      REPCNT          ;DONE ENOUGH ?
1381 005640 001402          BEQ      T2018          ;YES
1382 005642 000137 005032          JMP      T2003          ;NO
1383
1384 005646 032777 000100 006344    T2018: BIT      #100,@SWR ;CHECK FOR PRE-SELECTED TEST
1385 005654 001427          BEQ      TEST3
1386 005656 000137 001232          JMP      START2
1387
1388
1389
1390
1391 005662 020133 044103 051101    ERMS20: .NLIST BEX
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011
3012
3013
3014
3015
3016
3017
3018
3019
3020
3021
3022
3023
3024
3025
3026
3027
3028
3029
3030
3031
3032
3033
3034
3035
3036
3037
3038
3039
3040
3041
3042
3043
3044
3045
3046
3047
3048
3049
3050
3051
3052
3053
3054
3055
3056
3057
3058
3059
3060
3061
3062
3063
3064
3065
3066
3067
3068
3069
3070
3071
3072
3073
3074
3075
3076
3077
3078
3079
3080
3081
3082
3083
3084
3085
3086
3087
3088
3089
3090
3091
3092
3093
3094
3095
3096
3097
3098
3099
3100
3101
3102
3103
3104
3105
3106
3107
3108
3109
3110
3111
3112
3113
3114
3115
3116
3117
3118
3119
3120
3121
3122
3123
3124
3125
3126
3127
3128
3129
3130
3131
3132
3133
3134
3135
3136
3137
3138
3139
3140
3141
3142
3143
3144
3145
3146
3147
3148
3149
3150
3151
3152
3153
3154
3155
3156
3157
3158
3159
3160
3161
3162
3163
3164
3165
3166
3167
3168
3169
3170
3171
3172
3173
3174
3175
3176
3177
3178
3179
3180
3181
3182
3183
3184
3185
3186
3187
3188
3189
3190
3191
3192
3193
3194
3195
3196
3197
3198
3199
3200
3201
3202
3203
3204
3205
3206
3207
3208
3209
3210
3211
3212
3213
3214
3215
3216
3217
3218
3219
3220
3221
3222
3223
3224
3225
3226
3227
3228
3229
3230
3231
3232
3233
3234
3235
3236
3237
3238
3239
3240
3241
3242
3243
3244
3245
3246
3247
3248
3249
3250
3251
3252
3253
3254
3255
3256
3257
3258
3259
3260
3261
3262
3263
3264
3265
3266
3267
3268
3269
3270
3271
3272
3273
3274
3275
3276
3277
3278
3279
3280
3281
3282
3283
3284
3285
3286
3287
3288
3289
3290
3291
3292
3293
3294
3295
3296
3297
3298
3299
3300
3301
3302
3303
3304
3305
3306
3307
3308
3309
3310
3311
3312
3313
3314
3315
3316
3317
3318
3319
3320
3321
3322
3323
3324
3325
3326
3327
3328
3329
3330
3331
3332
3333
3334
3335
3336
3337
3338
3339
3340
3341
3342
3343
3344
3345
3346
3347
3348
3349
3350
3351
3352
3353
3354
3355
3356
3357
3358
3359
3360
3361
3362
3363
3364
3365
3366
3367
3368
3369
3370
3371
3372
3373
3374
3375
3376
3377
3378
3379
3380
3381
3382
3383
3384
3385
3386
3387
3388
3389
3390
3391
3392
3393
3394
3395
3396
3397
3398
3399
3400
3401
3402
3403
3404
3405
3406
3407
3408
3409
3410
3411
3412
3413
3414
3415
3416
3417
3418
3419
3420
3421
3422
3423
3424
3425
3426
3427
3428
3429
3430
3431
3432
3433
3434
3435
3436
3437
3438
3439
3440
3441
3442
3443
3444
3445
3446
3447
3448
3449
3450
3451
3452
3453
3454
3455
3456
3457
3458
3459
3460
3461
3462
3463
3464
3465
3466
3467
3468
3469
3470
3471
3472
3473
3474
3475
3476
3477
3478
3479
3480
3481
3482
3483
3484
3485
3486
3487
3488
3489
3490
3491
3492
3493
3494
3495
3496
3497
3498
3499
3500
3501
3502
3503
3504
350
```



```

1395                      .SBTTL TEST3
1396                      ;*****
1397                      ;THIS TEST CHECKS OUT THE CHARACTER
1398                      ;STORE BY LOADING EVERY LOCATION
1399                      ;WITH RANDOM DATA AND THEN
1400                      ;READING EACH LOCATION BACK AND
1401                      ;CHECKING THE DATA.
1402                      ;*****
1403
1404
1405 005734 012737 000003 014216 TEST3: MOV #3,TESTNO ;SET UP TEST NO.
1406 005742 104402 TRAP+2
1407 005744 005752 T3000
1408 005746 004737 014416 JSR PC,TESTR ;OUTPUT TEST NO
1409
1410 005752 005037 014346 T3000: CLR ERRDIS
1411 005756 012704 000100 MOV #REPCNT,R4
1412 005762 004737 015104 JSR PC,FASTSW
1413 005766 010437 014250 MOV R4,REPCNT ;SET UP TEST ITERATION COUNT
1414
1415 005772 005077 006224 T3001: CLR @CSR ;SET FOR 8X8 MATRIX
1416 005776 105077 006236 CLR @CHAR ;SET CHARACTER ADDRESS TO 0
1417 006002 013705 012060 MOV BUFF,R5 ;SAVE FOR COMPARE IN BUFF
1418 006006 012701 002000 MOV #2000,R1 ;2000 (8) BYTES
1419 006012 006201 ASR R1 ;TWO PER LOAD
1420 006014 012703 000006 T3002: MOV #6,R3 ;GENERATE RANDOM NUMBER
1421 006020 004737 020246 JSR PC,GENER
1422 006024 004737 006146 JSR PC,LOPROM ;LOAD CHARACTER DATA BYTE
1423 006030 113700 014335 MOVB GOOD+1,R0 ;NEXT BYTE IN R0
1424 006034 004737 006146 JSR PC,LOPROM ;LOAD SECOND BYTE
1425 006040 005301 DEC R1 ;IS THERE MORE ?
1426 006042 003364 BGT T3002 ;BRANCH IF YES
1427 006044 013705 012060 T3003: MOV BUFF,R5 ;NO, SO NOW READ & COMPARE
1428 006050 012701 002000 MOV #2000,R1
1429 006054 105077 006160 CLR @CHAR ;SET CHARACTER ADDRESS TO 0
1430 006060 004737 006162 T3004: JSR PC,REPROM ;READ A BYTE
1431 006064 000407 BR T3005 ;O.K. ARG
1432 006066 110037 014336 MOVB R0,BAD ;SET UP FOR ERROR MESSAGE
1433 006072 105037 014337 CLR BAD+1 ;CLEAR OUT RUBBISH
1434 ;ADDRES CONTAINS STORE ADDRESS
1435 ;WRONG DATA IN STORE
1436 006076 004737 020544 JSR PC,ERROR ;ERROR 1,STORE DATA ERROR
1437 006102 130001 G+S+A+1
1438
1439 006104 104410 T3005: TRAP+10 ;SCPOE LOOP ON READING 1ST CHAR.
1440 006106 006044 T3003 ; (SWR BIT 9 )
1441
1442 006110 005301 DEC R1 ;MORE ?
1443 006112 003362 BGT T3004 ;YES
1444 006114 104404 TRAP+4 ;SET SWR BIT 8 TO
1445 006116 005772 T3001 ;LOOP ON TEST
1446
1447
1448 006120 005337 014250 DEC REPCNT ;DONE ENOUGH ?
1449 006124 001402 BEQ T3006 ;YES
1450 006126 000137 005772 JMP T3001 ;NO

```



```

1451
1452 006132 032777 000100 006060 T3006: BIT #100,@SWR ;CHECK FOR PRE-SELECTED TEST
1453 006140 001447 BEQ TEST4
1454 006142 000137 001232 JMP START2
1455
1456
1457
1458 006146 042700 177400 LOPROM: BIC #177400,R0 ;CLEAR TOP RUBBISH
1459 006152 110025 MOV R0,(R5)+ ;STORE IN CORE
1460 006154 110077 006056 MOV R0,@CHDR ;& IN DISPLAY CHARACTER STORE
1461 006160 000207 RTS PC ;RETURN
1462
1463 006162 017702 006042 REPRM: MOV @CHSR,R2 ;READ CHARACTER STORE REGISTER
1464 006166 010200 MOV R2,R0 ;*SET UP R0 WITH
1465 006170 042700 177400 BIC #177400,R0 ;*CHARACTER DATA
1466 006174 000302 SWAB R2 ;*SET UP
1467 006176 042702 177400 BIC #177400,R2 ;*ADDRESS WITH
1468 006202 010237 014344 MOV R2,ADDRES ;*CHARACTER ADDRESS
1469 006206 010537 014342 MOV R5,STATUS
1470 006212 163737 012060 014342 SUB BUFF,STATUS
1471 006220 162737 000001 014342 SUB #1,STATUS
1472 006226 042737 177770 014342 BIC #177770,STATUS ;ROW OF CHARACTER
1473 006234 111537 014334 MOVB (R5),GOOD ;SET UP WITH GOOD DATA
1474 006240 042737 177400 014334 BIC #177400,GOOD
1475 006246 120025 CMPB R0,(R5)+ ;CHECK WHAT WAS READ
1476 006250 001402 BEQ REPRM1 ;BRANCH IF O.K.
1477 006252 062716 000002 ADD #2,(SP) ;NO SO JUMP OVER OK RETURN ADD.
1478 006256 000207 REPRM1: RTS PC ;RETURN
1479
1480

```



```

1482
1483
1484
1485
1486
1487
1488
1489
1490
1491 006260 012737 000004 014216 TEST4: MOV #4,TESTNO ;SET UP TEST NO.
1492 006266 104402 TRAP+2
1493 006270 006276 T4000
1494 006272 004737 014416 JSR PC,TESTR ;OUTPUT TEST NO
1495
1496 006276 005037 014346 T4000: CLR ERRDIS
1497 006302 012704 000100 MOV #REPC2,R4
1498 006306 004737 015104 JSR PC,FASTSW
1499 006312 010437 014250 MOV R4,REPCNT ;SET UP TEST ITERATION COUNT
1500
1501 006316 000005 T4001: RESET ;INITIALISE HARDWARE
1502 006320 012702 000100 T4002A: MOV #100,R2 ;SET REPEAT COUNT
1503 006324 012703 000006 MOV #6,R3 ;*GENERATE RANDOM
1504 006330 004737 020246 T4002: JSR PC,GENER ;*DATA
1505 006334 010077 005666 MOV R0,@CAR ;LOAD CAR
1506 006340 017737 005662 014336 MOV @CAR,BAD ;READ IT BACK
1507 006346 042700 140200 BIC #140200,R0 ;CLEAR BITS THAT READ ZERO
1508 006352 020037 014336 CMP R0,BAD ;WAS IT LOADED & READ CORRECTLY
1509 006356 001410 BEQ T4003 ;BRANCH IF O.K.
1510 006360 010037 014334 MOV R0,GOOD ;*SET UP FOR
1511 006364 013737 014226 014344 MOV CAR,ADDRES ;*ERROR REPORT
1512 006372 004737 020544 JSR PC,ERROR ;ERROR 1, CURSOR ADDRESS REGISTER
1513 006376 120001 A+G+1 ;DATA ERROR
1514 006400 104410 T4003: TRAP+10 ;LOOP ON LOAD
1515 006402 006330 T4002 ;(SWR BIT 9)
1516
1517 006404 012777 000335 005612 MOV #335,@DBUF ;DO HOME CURSOR
1518 006412 017737 005610 014336 MOV @CAR,BAD ;READ CURSOR
1519 006420 005737 014336 TST BAD ;WAS IT CLEARED BY HOME
1520 006424 001410 BEQ T4004 ;BRANCH IF O.K.
1521 006426 005037 014334 CLR GOOD ;SET UP FOR ERROR REPORT
1522 006432 013737 014226 014344 MOV CAR,ADDRES ;
1523 006440 004737 020544 JSR PC,ERROR ;ERROR 2, CAR DID NOT CLEAR
1524 006444 120002 A+G+2 ;ON HOME
1525 006446 104420 T4004: TRAP+20 ;LOOP ON LOAD
1526 006450 006330 T4002 ;(SWR BIT 10)
1527
1528 006452 005302 DEC R2 ;ANY MORE ?
1529 006454 001325 BNE T4002 ;YES SO BRANCH

```



```

1531
1532
1533
1534 006456 013737 014232 014344      MOV    CARX,ADDRES      ;SET UP FOR ANY ERROR REPORT
1535 006464 012777 000404 005530      MOV    #404,@CSR       ;SET FOR 6H & INC
1536 006472 012701 000117              MOV    #79.,R1         ;SET R1 WITH MAX VALUE
1537 006476 110177 005530      T4005: MOV    R1,@CARX    ;LOAD X ADDRESS
1538 006502 117737 005524 014336      MOV    @CARX,BAD      ;READ IT BACK
1539 006510 105037 014337      CLR    BAD+1          ;
1540 006514 010137 014334      MOV    R1,GOOD        ;SET UP GOOD
1541 006520 023737 014334 014336      CMP    GOOD,BAD       ;WAS DATA READ CORRECTLY
1542 006526 001403              BEQ    T4006           ;BRANCH IF O.K.
1543 006530 004737 020544      JSR    PC,ERROR       ;ERROR 3, LOAD/READ ERROR
1544 006534 120003              A+G+3                ;
1545
1546 006536 112777 000000 005460      T4006: MOV    #0,@DBUF  ;DO A LOAD TO PICTURE STORE
1547 006544 117737 005462 014336      MOV    @CARX,BAD      ;READ X ADDRESS
1548 006552 105037 014337      CLR    BAD+1          ;
1549 006556 023727 014334 000117      CMP    GOOD,#79.      ;SHOULD IT HAVE INCREMENTED
1550 006564 001402              BEQ    1$             ;BRANCH IF NO
1551 006566 005237 014334              INC    GOOD           ;YES, SO INC GOOD
1552 006572 023737 014334 014336      CMP    GOOD,BAD       ;DID CARX INCREMENT CORRECTLY
1553 006600 001403              BEQ    T4007           ;BRANCH IF O.K.
1554 006602 004737 020544      JSR    PC,ERROR       ;ERROR 4, CARX INCREMENT ERROR
1555 006606 120004              A+G+4                ;
1556
1557 006610 112777 000300 005406      T4007: MOV    #300,@DBUF ;SET BLINK OFF INCREMENT
1558 006616 117737 005410 014336      MOV    @CARX,BAD      ;READ X ADDRESS
1559 006624 105037 014337      CLR    BAD+1          ;
1560 006630 023727 014334 000117      CMP    GOOD,#79.      ;SHOULD IT HAVE INCREMENTED
1561 006636 001402              BEQ    1$             ;BRANCH IF NO
1562 006640 005237 014334              INC    GOOD           ;YES, SO INCREMENT GOOD
1563 006644 023737 014334 014336      CMP    GOOD,BAD       ;DID CARX INCREMENT CORRECTLY
1564 006652 001403              BEQ    T4008           ;BRANCH IF O.K.
1565 006654 004737 020544      JSR    PC,ERROR       ;ERROR 5, CARX INCREMENT ERROR
1566 006660 120005              A+G+5                ;
1567
1568 006662 112777 000301 005334      T4008: MOV    #301,@DBUF ;SET BLINK ON INCREMENT
1569 006670 117737 005336 014336      MOV    @CARX,BAD      ;READ X ADDRESS
1570 006676 105037 014337      CLR    BAD+1          ;
1571 006702 023727 014334 000117      CMP    GOOD,#79.      ;SHOULD IT HAVE INCREMENTED
1572 006710 001402              BEQ    1$             ;BRANCH IF NO
1573 006712 005237 014334              INC    GOOD           ;YES, SO INCREMENT GOOD
1574 006716 023737 014334 014336      CMP    GOOD,BAD       ;DID CARX INCREMENT CORRECTLY
1575 006724 001403              BEQ    T4009           ;BRANCH IF O.K.
1576 006726 004737 020544      JSR    PC,ERROR       ;ERROR 6, CARX INCREMENT ERROR
1577 006732 120006              A+G+6                ;
1578
1579 006734 112777 000315 005262      T4009: MOV    #315,@DBUF ;DO A CARAGE RETURN
1580 006742 117737 005264 014336      MOV    @CARX,BAD      ;READ X ADDRESS
1581 006750 105037 014337      CLR    BAD+1          ;
1582 006754 005037 014334              CLR    GOOD           ;
1583 006760 023737 014334 014336      CMP    GOOD,BAD       ;DID CARX ZERO ON CR.
1584 006766 001403              BEQ    T4010           ;BRANCH IF O.K.
1585 006770 004737 020544      JSR    PC,ERROR       ;ERROR 7,CARX DID NOT ZERO
1586 006774 120007              A+G+7                ;
  
```



```

1587
1588 006776 104440          T4010: TRAP+40          ;SCOPE LOOP ON LOAD AND INC.
1589 007000 006476          T4005          ;(SWR BIT 11 )
1590 007002 005301          DEC      R1          ;HAVE WE DONE ENOUGH
1591 007004 100234          BPL      T4005          ;BRANCH IF MORE
1592
1593                      ;*****
1594                      ;TEST CARX IN 8H MODE
1595                      ;*****
1596 007006 013737 014232 014344      MOV      CARX,ADDRES      ;SET UP FOR ANY ERROR REPORT
1597 007014 012777 000004 005200      MOV      #4,@CSR          ;SET FOR 8H & INC
1598 007022 012701 000077          MOV      #63.,R1          ;SET R1 WITH MAX VALUE
1599 007026 110177 005200          T4015: MOVB     R1,@CARX      ;LOAD X ADDRESS
1600 007032 117737 005174 014336      MOVB     @CARX,BAD      ;READ IT BACK
1601 007040 105037 014337          CLRB     BAD+1          ;
1602 007044 010137 014334          MOV      R1,GOOD          ;SET UP GOOD
1603 007050 023737 014334 014336      CMP      GOOD,BAD      ;WAS DATA READ CORRECTLY
1604 007056 001403          BEQ      T4016          ;BRANCH IF O.K.
1605 007060 004737 020544          JSR      PC,ERROR      ;ERROR 3, LOAD/READ ERROR
1606 007064 120003          ;
1607
1608 007066 112777 000000 005130      T4016: MOVB     #0,@DBUF      ;DO A LOAD TO PICTURE STORE
1609 007074 117737 005132 014336      MOVB     @CARX,BAD      ;READ X ADDRESS
1610 007102 105037 014337          CLRB     BAD+1          ;
1611 007106 023727 014334 000077      CMP      GOOD,#63.      ;SHOULD IT HAVE INCREMENTED
1612 007114 001402          BEQ      1$          ;BRANCH IF NO
1613 007116 005237 014334          INC      GOOD          ;YES, SO INC GOOD
1614 007122 023737 014334 014336      CMP      GOOD,BAD      ;DID CARX INCREMENT CORRECTLY
1615 007130 001403          BEQ      T4017          ;BRANCH IF O.K.
1616 007132 004737 020544          JSR      PC,ERROR      ;ERROR 4, CARX INCREMENT ERROR
1617 007136 120004          ;
1618
1619 007140 112777 000300 005056      T4017: MOVB     #300,@DBUF      ;SET BLINK OFF INCREMENT
1620 007146 117737 005060 014336      MOVB     @CARX,BAD      ;READ X ADDRESS
1621 007154 105037 014337          CLRB     BAD+1          ;
1622 007160 023727 014334 000077      CMP      GOOD,#63.      ;SHOULD IT HAVE INCREMENTED
1623 007166 001402          BEQ      1$          ;BRANCH IF NO
1624 007170 005237 014334          INC      GOOD          ;YES, SO INCREMENT GOOD
1625 007174 023737 014334 014336      CMP      GOOD,BAD      ;DID CARX INCREMENT CORRECTLY
1626 007202 001403          BEQ      T4018          ;BRANCH IF O.K.
1627 007204 004737 020544          JSR      PC,ERROR      ;ERROR 5, CARX INCREMENT ERROR
1628 007210 120005          ;
1629
1630 007212 112777 000301 005004      T4018: MOVB     #301,@DBUF      ;SET BLINK ON INCREMENT
1631 007220 117737 005006 014336      MOVB     @CARX,BAD      ;READ X ADDRESS
1632 007226 105037 014337          CLRB     BAD+1          ;
1633 007232 023727 014334 000077      CMP      GOOD,#63.      ;SHOULD IT HAVE INCREMENTED
1634 007240 001402          BEQ      1$          ;BRANCH IF NO
1635 007242 005237 014334          INC      GOOD          ;YES, SO INCREMENT GOOD
1636 007246 023737 014334 014336      CMP      GOOD,BAD      ;DID CARX INCREMENT CORRECTLY
1637 007254 001403          BEQ      T4019          ;BRANCH IF O.K.
1638 007256 004737 020544          JSR      PC,ERROR      ;ERROR 6, CARX INCREMENT ERROR
1639 007262 120006          ;
1640
1641 007264 112777 000315 004732      T4019: MOVB     #315,@DBUF      ;DO A CARAGE RETURN
1642 007272 117737 004734 014336      MOVB     @CARX,BAD      ;READ X ADDRESS

```


1643	007300	105037	014337		CLRB	BAD+1	:
1644	007304	005037	014334		CLR	GOOD	:
1645	007310	023737	014334	014336	CMP	GOOD,BAD	: DID CARX ZERO ON C9.
1646	007316	001403			BEQ	T4020	: BRANCH IF O.K.
1647	007320	004737	020544		JSR	PC,ERROR	: ERROR 7,CARX DID NOT ZERO
1648	007324	120007				A+G+7	:
1649							
1650	007326	104440			T4020:	TRAP+40	: SCOPE LOOP ON LOAD AND INC.
1651	007330	007026				T4015	: (SWR BIT 11)
1652	007332	005301			DEC	R1	: HAVE WE DONE ENOUGH
1653	007334	100234			BPL	T4015	: BRANCH IF MORE
1654	007336	013737	014234	014344	MOV	CARY,ADDRES	: SET UP FOR ANY ERROR REPORT
1655	007344	012777	001004	004650	MOV	#1004,@CSR	: SET 6V & INC BITS
1656	007352	013701	012160		MOV	HALF6V,R1	: *SET UP
1657	007356	006301			ASL	R1	: *R1 WITH
1658	007360	005301			DEC	R1	: *MAX VALUE OF Y
1659	007362	010102			MOV	R1,R2	: SAVE IN R2
1660							
1661	007364	110177	004644		T4021:	MOVB	R1,@CARY
1662	007370	117737	004640	014336	MOVB	@CARY,BAD	: LOAD Y ADDRESS
1663	007376	105037	014337		CLRB	BAD+1	: READ IT BACK
1664	007402	010137	014334		MOV	R1,GOOD	:
1665	007406	023737	014334	014336	CMP	GOOD,BAD	: SET UP GOOD
1666	007414	001403			BEQ	1\$	: WAS LOAD/READ CORRECT
1667	007416	004737	020544		JSR	PC,ERROR	: BRANCH IF O.K.
1668	007422	120010				A+G+10	: ERROR 8, LOAD/READ ERROR
1669	007424	112777	000312	004572	1\$:	MOVB	#312,@DBUF
1670	007432	117737	004576	014336	MOVB	@CARY,BAD	: DO A LINE FEED
1671	007440	105037	014337		CLRB	BAD+1	: READ Y
1672	007444	023702	014334		CMP	GOOD,R2	:
1673	007450	001402			BEQ	2\$	: *SET UP
1674	007452	005237	014334		INC	GOOD	: *GOOD WITH
1675	007456	023737	014334	014336	2\$:	CMP	GOOD,BAD
1676	007464	001403			BEQ	T4022	: *EXPECTED DATA
1677	007466	004737	020544		JSR	PC,ERROR	: DID IT INCREMENT CORRECTLY
1678	007472	120011				A+G+11	: BRANCH IF O.K.
1679	007474	104460			T4022:	TRAP+60	: ERROR 9,INC ERROR ON LF
1680	007476	007364				T4021	: SCOPE LOOP ON LOAD & INC
1681	007500	005301			DEC	R1	: (SWR BITS 10 & 11)
1682	007502	100330			BPL	T4021	: ANY MORE TO DO
1683							: BRANCH IF YES
1684	007504	012777	000004	004510	MOV	#4,@CSR	: SET INC BITS
1685	007512	013701	012162		MOV	HALF8V,R1	: *SET UP
1686	007516	006301			ASL	R1	: *R1 WITH
1687	007520	005301			DEC	R1	: *MAX VALUE OF Y
1688	007522	010102			MOV	R1,R2	: SAVE IN R2
1689							
1690	007524	110177	004504		T4023:	MOVB	R1,@CARY
1691	007530	117737	004500	014336	MOVB	@CARY,BAD	: LOAD Y ADDRESS
1692	007536	105037	014337		CLRB	BAD+1	: READ IT BACK
1693	007542	010137	014334		MOV	R1,GOOD	:
1694	007546	023737	014334	014336	CMP	GOOD,BAD	: SET UP GOOD
1695	007554	001403			BEQ	1\$	: WAS LOAD/READ CORRECT
1696	007556	004737	020544		JSR	PC,ERROR	: BRANCH IF O.K.
1697	007562	120010				A+G+10	: ERROR 8, LOAD/READ ERROR
1698	007564	112777	000312	004432	1\$:	MOVB	#312,@DBUF
							: DO A LINE FEED

1699	007572	117737	004436	014336	MOVB	@CARY,BAD	:READ Y
1700	007600	105037	014337		CLRB	BAD+1	:
1701	007604	023702	014334		CMP	GOOD,R2	:*SET UP
1702	007610	001402			BEQ	2\$	:*GOOD WITH
1703	007612	005237	014334		INC	GOOD	:*EXPECTED DATA
1704	007616	023737	014334	014336	CMP	GOOD,BAD	:DID IT INCREMENT CORRECTLY
1705	007624	001403			BEQ	T4024	:BRANCH IF O.K.
1706	007626	004737	020544		JSR	PC,ERROR	:ERROR 9,INC ERROR ON LF
1707	007632	120011				A+G+11	:
1708	007634	104460			T4024:	TRAP+60	:SCOPE LOOP ON LOAD & INC
1709	007636	007524				T4023	:(SWR BITS 10 & 11)
1710	007640	005301			DEC	R1	:ANY MORE TO DO
1711	007642	100330			BPL	T4023	:BRANCH IF YES
1712							:
1713	007644	104404			TRAP+4		:SET SWR BIT 8 TO
1714	007646	006320			T4002A		:LOOP ON TEST
1715	007650	005337	014250		DEC	REPCNT	:DONE ENOUGH ?
1716	007654	001402			BEQ	T40WW	:YES
1717	007656	000137	006320		JMP	T4002A	:NO
1718							:
1719	007662	032777	000100	004330	T40WW:	BIT	:CHECK FOR PRESELECTED TEST
1720	007670	001402				#100,@SWR	:
1721	007672	000137	001232		BEQ	TEST5	:
					JMP	START2	:


```

1723 .SBTTL TEST5
1724 :*****
1725 :THIS TEST CHECKS EVERY LOCATION
1726 :IN THE PICTURE STORE FOR CORRECT
1727 :LOADING AND READING. IT ALSO
1728 :CHECKS PRESET AND THE OPERATION
1729 :OF THE VARIOUS BLINK COMMANDS.
1730 :*****
1731
1732 007676 012737 000005 014216 TEST5: MOV #5,TESTNO ;SET UP TEST NO.
1733 007704 104402 TRAP+2
1734 007706 007714 T5000
1735 007710 004737 014416 JSR PC,TESTR ;OUTPUT TEST NO
1736
1737 007714 005037 014346 T5000: CLR ERRDIS
1738 007720 012704 000100 MOV #REPC2,R4
1739 007724 004737 015104 JSR PC,FASTSW
1740 007730 010437 014250 MOV R4,REPCNT ;SET UP TEST ITERATION COUNT
1741
1742 007734 112777 000302 004262 MOVB #302,ADBUF ;CLEAR BLINK CONTROL
1743 007742 005037 012056 CLR BLNFLG ;CLEAR BLINK FLAG
1744 007746 005077 004254 T5001: CLR ACSR ;CLEAR PICTURE STORE ADDRESS
1745 007752 012777 001405 004242 MOV #1405,ACSR ;SET 6V,6H & CURSOR INC BITS
1746 007760 013705 012060 MOV BUFF,R5 ;SAVE FOR COMPARE IN BUFF
1747 007764 013704 012160 MOV HALF6V,R4 ;SET UP R4 WITH HALF NO OF ROWS
1748 007770 012702 000120 T5002: MOV #80.,R2 ;SET UP R2 WITH CHAR PER LINE
1749 007774 012703 000006 T5003: MOV #6,R3 ;*GENERATE RANDOM
1750 010000 004737 020246 JSR PC,GENER ;*DATA PATTERNS
1751 010004 042737 100200 014334 BIC #100200,GOOD ;*
1752 010012 013700 014334 MOV GOOD,R0 ;*
1753
1754 010016 010025 MOV R0,(R5)+ ;SAVE IN BUFFER
1755 010020 004737 012002 JSR PC,SETBLN ;CHECK BLINK FLAG
1756 010024 042700 000100 BIC #100,R0 ;*MAKE CONTENTS OF R0 INTO
1757 010030 052700 000200 BIS #200,R0 ;*COLOUR COMAND
1758 010034 110077 004164 MOVB R0,ADBUF ;LOAD DATA BYTE
1759 010040 000300 SWAB R0 ;GET NEXT BYTE
1760 010042 110077 004156 MOVB R0,ADBUF ;NOW LOAD CHARACTER
1761 010046 005302 DEC R2 ;ANY MORE CHARACTERS IN LINE
1762 010050 001351 BNE T5003 ;BRANCH IF YES
1763 010052 112777 000315 004144 MOVB #315,ADBUF ;DO CARAGE RETURN
1764 010060 112777 000312 004136 MOVB #312,ADBUF ;DO LINE FEED
1765 010066 005304 DEC R4 ;ANY MORE ROWS IN HALF SCREEN
1766 010070 001337 BNE T5002 ;BRANCH IF YES
1767 010072 013705 012060 MOV BUFF,R5 ;NO, SO SET UP FOR NEXT HALF
1768 010076 013704 012160 MOV HALF6V,R4 ;NUMBER OF ROWS
1769 010102 012702 000120 T5004: MOV #80.,R2 ;NUMBER OF CHARACTER$ PER LINE
1770 010106 012500 T5005: MOV (R5)+,R0 ;GET FIRST TWO BYTES
1771 010110 000300 SWAB R0 ;
1772 010112 004737 012002 JSR PC,SETBLN ;CHECK BLINK FLAG
1773 010116 042700 000100 BIC #100,R0 ;*MAKE CONTENTS OF R0 INTO
1774 010122 052700 000200 BIS #200,R0 ;*COLOUR COMAND
1775 010126 110077 004072 MOVB R0,ADBUF ;LOAD COLOUR
1776 010132 000300 SWAB R0 ;GET NEXT BYTE
1777 010134 110077 004064 MOVB R0,ADBUF ;LOAD CHARACTER
1778 010140 005302 DEC R2 ;ANY MORE CHARACTERS IN LINE

```


1779	010142	001361			BNE	T5005	:BRANCH IF YES
1780	010144	112777	000315	004052	MOVB	#315,@DBUF	:DO CARAGE RETURN
1781	010152	112777	000312	004044	MOVB	#312,@DBUF	:DO LINE FEED
1782	010160	005304			DEC	R4	:ANY MORE ROWS
1783	010162	001347			BNE	T5004	:BRANCH IF YES
1784							:*****
1785							:WE HAVE NOW FINISHED LOADING
1786							:*****
1787							:*****
1788							:NOW START READING TO CHECK STORE
1789							:*****
1790	010164	112777	000335	004032	T5006: MOVB	#335,@DBUF	:HOME CURSOR
1791	010172	042777	000004	004022	BIC	#4,@CSR	:CLEAR INC BIT
1792	010200	013705	012060		MOV	BUFF,R5	:SET UP BUFFER FOR COMPARE
1793	010204	013704	012160		MOV	HALF6V,R4	:SET UP NO OF ROWS IN HALF SCREEN
1794	010210	012702	000120		T5007: MOV	#80.,R2	:SET CHARACTERS PER ROW
1795	010214	012500			T5007A: MOV	(R5)+,R0	:*SET UP R0 WITH EXPECTED DATA
1796	010216	052777	000020	003776	T5008: BIS	#20,@CSR	:SET READ STORE BIT
1797	010224	000240			NOP		:
1798	010226	000240			NOP		:
1799	010230	000240			NOP		:WAIT
1800	010232	000240			NOP		:
1801	010234	000240			NOP		:
1802	010236	017737	003762	014336	MOV	@DBUF,BAD	:READ PICTURE STORE DATA
1803	010244	020037	014336		CMP	R0,BAD	:IS IT CORRECT ?
1804	010250	001410			BEQ	T5009	:YES, SO BRANCH
1805	010252	010037	014334		MOV	R0,GOOD	:NO, SO SET UP FOR ERROR REPORT
1806	010256	017737	003744	014344	MOV	@CAR,ADDRES	:
1807	010264	004737	020544		JSR	PC,ERROR	:ERROR 51,PICTURE STORE DATA ERROR
1808	010270	120001				A+G+1	:
1809							:
1810	010272	104410			T5009: TRAP+10		:SCOPE LOOP READING THIS ADDRESS
1811	010274	010216			T5008		: (SWR BIT 9)
1812							:
1813	010276	105277	003730		INCB	@CARX	:INCREMENT X ADDRESS
1814	010302	005302			DEC	R2	:HAVE WE READ ALL OF ROW
1815	010304	001343			BNE	T5007A	:NO, SO READ SOME MORE
1816	010306	105077	003720		CLRB	@CARX	:YES, SO SET UP ADDRESS OF
1817	010312	105277	003716		INCB	@CARY	:NEXT ROW
1818	010316	005304			DEC	R4	:ANY MORE ROWS
1819	010320	001333			BNE	T5007	:YES, SO BRANCH
1820							:
1821							:
1822	010322	013705	012060		MOV	BUFF,R5 ;SET UP BUFFER	:
1823	010326	013704	012160		MOV	HALF6V,R4	:
1824	010332	012702	000120		T5010: MOV	#80.,R2	:
1825	010336	012500			T5011: MOV	(R5)+,R0	:GET EXPECTED DATA
1826	010340	000300			SWAB	R0	:
1827	010342	052777	000020	003652	T5012: BIS	#20,@CSR	:SET READ STORE BIT
1828	010350	017737	003650	014336	MOV	@DBUF,BAD	:READ PICTURE STORE DATA
1829	010356	020037	014336		CMP	R0,BAD	:IS IT CORRECT
1830	010362	001410			BEQ	T5013	:YES, SO BRANCH
1831	010364	010037	014334		MOV	R0,GOOD	:NO, SO SET UP FOR ERROR REPORT
1832	010370	017737	003632	014344	MOV	@CAR,ADDRES	:
1833	010376	004737	020544		JSR	PC,ERROR	:ERROR 1, PICTURE STORE DATA ERROR
1834	010402	120001				A+G+1	:

1835 010404 104420
1836 010406 010342
1837 010410 005277 003616
1838 010414 005302
1839 010416 001347
1840 010420 105077 003606
1841 010424 105277 003604
1842 010430 005304
1843 010432 001337
1844
1845

T5013: TRAP+20
T5012
INC @CARX
DEC R2
BNE T5011
CLRB @CARX
INCB @CARY
DEC R4
BNE T5010

;LOOP ON THIS ADDRESS
; (SWR BIT 10)
;NEXT ADDRESS
;ANY MORE IN ROW
;YES , SO DO SOME MORE
;NO, SO SET UP NEXT ADDRESS
;
;ANY MORE ROWS ?
;YES , SO DO SOME MORE

1847	010434	013701	014242		MOV	INTVEC,R1	;	*SET
1848	010440	012721	011760		MOV	#RDYINT,(R1)+	;	*UP
1849	010444	012711	000340		MOV	#340,(R1)	;	*INTERRUPT VECTOR.
1850								
1851	010450	005037	004202		CLR	WTC1	;	*SET UP
1852	010454	012737	000002	004204	MOV	#2,WTC0	;	*TIME OUT
1853	010462	005037	004272		CLR	INTFLG	;	CLEAR INTERRUPT FLAG
1854								
1855	010466	012703	000006		MOV	#6,R3	;	*GENERATE
1856	010472	004737	020246		JSR	PC,GENER	;	*RANDOM NUMBER
1857	010476	032700	000100		BIT	#100,R0	;	SHOULD BLINK BE SET
1858	010502	001005			BNE	1\$	;	BRANCH IF YES
1859	010504	112777	000302	003512	MOVB	#302,@DBUF	;	NO, CLEAR BLINK CONTROL
1860	010512	000137	010524		JMP	2\$	;	
1861	010516	112777	000303	003500	1\$: MOVB	#303,@DBUF	;	SET BLINK CONTROL
1862	010524	010001			2\$: MOV	R0,R1	;	*SET
1863	010526	042701	000300		BIC	#300,R1	;	*UP
1864	010532	052701	000200		BIS	#200,R1	;	*COLOUR
1865	010536	110177	003462		MOVB	R1,@DBUF	;	LOAD COLOUR
1866	010542	042700	177600		BIC	#177600,R0	;	*SET UP EXPECTED
1867	010546	010037	011756		MOV	R0,PRESET	;	*DATA AFTER PRESET
1868								
1869	010552	052777	000010	003442	T5015A: BIS	#10,@CSR	;	SET PRESET
1870	010560	105777	003436		TSTB	@CSR	;	TEST READY BIT CLEAR
1871	010564	100011			BPL	4\$	;	BRANCH IF O.K.
1872	010566	017737	003430	014342	MOV	@CSR,STATUS	;	ERROR BIT DID NOT CLEAR
1873	010574	013737	014222	014344	MOV	CSR,ADDRES	;	
1874	010602	004737	020544		JSR	PC,ERROR	;	ERROR 2, READY BIT DID NOT
1875	010606	030002				A+S+2	;	CLEAR FOR RESET
1876	010610	104440			4\$: TRAP+40		;	
1877	010612	010552			T5015A		;	
1878								
1879	010614	052777	000100	003400	BIS	#100,@CSR	;	SET INTERRUPT ENABLE
1880	010622				PSWSET	#0	;	TURN ON INTERUPTS
1881	010636	004737	004156		T5015: JSR	PC,WAIT	;	WAIT FOR TIMEOUT
1882	010642	103004			BCC	T5016	;	BRANCH IF TIMED OUT
1883	010644	005737	004272		TST	INTFLG	;	TEST FOR INTERRUPT
1884	010650	001022			BNE	T5017	;	BRANCH IF INTERRUPT O.K.
1885	010652	000771			BR	T5015	;	WAIT SOME MORE
1886	010654				T5016: PSWSET	#200	;	TURN OFF INTERUPTS
1887	010670	017737	003326	014342	MOV	@CSR,STATUS	;	TIMEOUT ERROR
1888	010676	013737	014222	014344	MOV	CSR,ADDRES	;	
1889	010704	004737	020544		JSR	PC,ERROR	;	ERROR 3,NO READY INTERRUPT
1890	010710	030003				A+S+3	;	IN OVER 40 MILLISECONDS
1891	010712	000137	010754		JMP	T5018	;	
1892								
1893	010716				T5017: PSWSET	#200	;	TURN OFF INTERUPTS
1894	010732	105737	014342		TSTB	STATUS	;	WAS READY BIT SET WHEN
1895	010736	100406			BMI	T5018	;	INTERRUPT OCCURED. BRANCH O.K.
1896	010740	013737	014222	014344	MOV	CSR,ADDRES	;	SET UP FOR ERROR
1897	010746	004737	020544		JSR	PC,ERROR	;	READY BIT WAS NOT SET WHEN
1898	010752	030004				S+A+4	;	INTERRUPT OCCURED ERROR 4
1899	010754	104460			T5018: TRAP+60		;	
1900	010756	010552			T5015A		;	
1901								
1902	010760	005077	003242		CLR	@CAR	;	READ CONTENTS OF PICTURE STORE
							;	SET CURSOR TO ZERO

1903	010764	013737	011756	014334	MOV	PRESET,GOOD	:LOAD GOOD WITH EXPECTED DATA
1904	010772	013704	012160		MOV	HALF6V,R4	:*SET UP
1905	010776	006304			ASL	R4	:*NUMBER OF ROWS
1906	011000	012702	000120		T5018A: MOV	#80.,R2	:NUMBER OF CHARACTERS PER ROW
1907	011004	052777	000020	003210	T5018B: BIS	#20,@CSR	:SET READ PICTURE STORE BIT
1908	011012	017737	003206	014336	MOV	@DBUF,BAD	:READ DATA BUFFER
1909	011020	023737	014334	014336	CMP	GOOD,BAD	:CHECK DATA
1910	011026	001406			BEQ	T5019	:BRANCH IF O.K.
1911	011030	017737	003172	014344	MOV	@CAR,ADDRES	:SET UP FOR ERROR REPORT
1912	011036	004737	020544		JSR	PC,ERROR	:PICTURE STORE DATA ERROR
1913	011042	120005				A+G+5	:AFTER PRESET
1914	011044	104470			T5019: TRAP+70		:
1915	011046	011000			T5018A		:
1916	011050	105277	003156		INCB	@CARX	:INCREMENT X ADDRESS
1917	011054	005302			DEC	R2	:WAS IT MAX
1918	011056	001352			BNE	T5018B	:BRANCH IF NO.
1919	011060	105077	003146		CLRB	@CARX	:YES, SO SET X=0
1920	011064	105277	003144		INCB	@CARY	:INCREMENT Y ADDRESS
1921	011070	005304			DEC	R4	:WAS IT MAX
1922	011072	001342			BNE	T5018A	:BRANCH IF NO
1923							:ALL CHECKED.
1924							:*****
1925							:THE NEXT PART OF THIS TESTS
1926							:LOADING PART OF THE PICTURE
1927							:STORE WITH RANDOM DATA
1928							:WHEN BLINK IS REQUIRED THE
1929							:BLINK ON OR OFF WITH INCREMENT
1930							:COMMAND IS USED. THE CONTENTS
1931							:OF THE PICTURE STORE ARE THEN
1932							:READ BACK TO CHECK THAT IT
1933							:LOADED CORRECTLY.
1934	011074	005037	012056		CLR	BLNFLAG	:CLEAR BLINK FLAG
1935	011100	012777	000302	003116	MOV	#302,@DBUF	:CLEAR BLINK CONTROL
1936	011106	005077	003114		CLR	@CAR	:CLEAR CURSOR ADDRESS
1937	011112	052777	000004	003102	BIS	#4,@CSR	:SET INCREMENT BIT
1938	011120	113777	012160	003106	MOVB	HALF6V,@CARY	:*SET UP
1939	011126	106277	003102		ASRB	@CARY	:*Y ADDRESS
1940	011132	013705	012060		MOV	BUFF,R5	:SAVE FOR COMPARE IN BUFF
1941	011136	013704	012160		MOV	HALF6V,R4	:SET UP R4 WITH HALF ROWS

1943	011142	012702	000120		T5020A: MOV	#80.,R2	;CHARACTERS PER LINE
1944	011146	012703	000006			MOV	#6,R3
1945	011152	004737	020246		T5020B: JSR	PC,GENER	;*GENERATE
1946	011156	042737	100200	014334		BIC	#100200,GOOD
1947	011164	013700	014334			MOV	GOOD,R0
1948	011170	004737	011634			JSR	PC,STBINC
1949	011174	000137	011250			JMP	T5021
1950	011200	010025				MOV	R0,(R5)+
1951	011202	042700	000100			BIC	#100,R0
1952	011206	052700	000200			BIS	#200,R0
1953	011212	110077	003006			MOVB	R0,@DBUF
1954	011216	000300				SWAB	R0
1955	011220	110077	003000			MOVB	R0,@DBUF
1956	011224	005302				DEC	R2
1957	011226	001351				BNE	T5020B
1958	011230	112777	000315	002766		MOVB	#315,@DBUF
1959	011236	112777	000312	002760		MOVB	#312,@DBUF
1960	011244	005304				DEC	R4
1961	011246	001335				BNE	T5020A
1962							*****
1963							;DONE THE LOADING
1964							*****
1965							;NOW START CHECKING
1966							*****
1967	011250	005077	002752		T5021: CLR	@CAR	;SET ADDRESS TO ZERO
1968	011254	042777	000004	002740		BIC	#4,@CSR
1969	011262	013737	011756	014334		MOV	PRESET,GOOD
1970	011270	013700	012160			MOV	HALF6V,R0
1971	011274	006200				ASR	R0
1972	011276	012701	000120		T5022: MOV	#80.,R1	;NUMBER OF ROWS
1973	011302	052777	000020	002712	T5023: BIS	#20,@CSR	;CHARACTERS PER ROW
1974	011310	017737	002710	014336		MOV	@DBUF,BAD
1975	011316	023737	014334	014336		CMP	GOOD,BAD
1976	011324	001406				BEQ	T5024
1977	011326	017737	002674	014344		MOV	@CAR,ADDRES
1978	011334	004737	020544			JSR	PC,ERROR
1979	011340	120006					A+G+6
1980							
1981	011342	005277	002664		T5024: INC	@CARX	;INCREMENT X ADDRESS
1982	011346	005301				DEC	R1
1983	011350	001354				BNE	T5023
1984	011352	105077	002654			CLRB	@CARX
1985	011356	105277	002652			INCB	@CARY
1986	011362	005300				DEC	R0
1987	011364	001344				BNE	T5022
1988							
1989	011366	013705	012060			MOV	BUFF,R5
1990	011372	013700	012160			MOV	HALF6V,R0
1991	011376	012701	000120		T5025: MOV	#80.,R1	;NUMBER OF ROWS
1992	011402	012537	014334		T5026: MOV	(R5)+,GOOD	;CHARACTERS PER ROW
1993	011406	052777	000020	002606		BIS	#20,@CSR
1994	011414	017737	002604	014336		MOV	@DBUF,BAD
1995	011422	023737	014334	014336		CMP	GOOD,BAD
1996	011430	001406				BEQ	T5027
1997	011432	017737	002570	014344		MOV	@CAR,ADDRES
1998	011440	004737	020544			JSR	PC,ERROR
							;STORE DATA ERROR

1999	011444	120006				G+A+6	:
2000							
2001	011446	105277	002560		T5027:	INCB @CARX	:NEXT X ADDRESS
2002	011452	005301				DEC R1	:IS IT END OF ROW
2003	011454	001352				BNE T5026	:BRANCH IF MORE
2004	011456	105077	002550			CLRB @CARX	:SET X TO ZERO
2005	011462	105277	002546			INCB @CARY	:INCREMENT Y ADDRESS
2006	011466	005300				DEC R0	:HAVE WE FINISHED
2007	011470	001342				BNE T5025	:BRANCH IF NO
2008							
2009	011472	013737	011756	014334		MOV PRESET,GOOD	:EXPECTED DATA
2010	011500	013700	012160			MOV HALF6V,R0	:
2011	011504	006200				ASR R0	:SET NUMBER OF ROWS
2012	011506	012701	000120		T5028:	MOV #80.,R1	:CHARACTERS PER ROW
2013	011512	052777	000020	002502	T5029:	BIS #20,@CSR	:READ STORE
2014	011520	017737	002500	014336		MOV @DBUF,BAD	:
2015	011526	023737	014334	014336		CMP GOOD,BAD	:CHECK DATA
2016	011534	001406				BEQ T5030	:BRANCH IF O.K.
2017	011536	017737	002464	014344		MOV @CAR,ADDRES	:SET UP FOR ERROR REPORT
2018	011544	004737	020544			JSR PC,ERROR	:STORE DATA ERROR
2019	011550	120006				G+A+6	:
2020	011552	005277	002454		T5030:	INC @CARX	:INCREMENT X ADDRESS
2021	011556	005301				DEC R1	:HAVE WE FINISHED ROW
2022	011560	001354				BNE T5029	:BRANCH IF MORE
2023	011562	105077	002444			CLRB @CARX	:ZERO X ADDRESS
2024	011566	105277	002442			INCB @CARY	:INCREMENT Y ADDRESS
2025	011572	005300				DEC R0	:ANY MORE ROWS
2026	011574	001344				BNE T5028	:BRANCH IF YES
2027							
2028	011576	104404				TRAP+4	:SET SWR BIT 8 TO
2029	011600	007746				T5001	:LOOP ON TEST
2030	011602	005337	014250			DEC REPCNT	:DONE ENOUGH ?
2031	011606	001402				BEQ T5014	:YES
2032	011610	000137	007746			JMP T5001	:NO
2033							
2034	011614	032777	000100	002376	T5014:	BIT #100,@SWR	:CHECK FOR PRE-SELECTED TEST
2035	011622	001402				BEQ T50WY	
2036	011624	000137	001232			JMP START2	
2037							
2038							
2039	011630	000137	014664		T50WY:	JMP ENDIT	:SIGNAL END OF PASS
2040							
2041	011634	032700	000100		STBINC:	BIT #100,R0	:SHOULD BLINK BE ON
2042	011640	001013				BNE BINC1	:BRANCH IF YES
2043	011642	005737	012056			TST BLNFLG	:CHECK BLINK FLAG
2044	011646	001440				BEQ BINC2	:BRANCH IF CLEAR
2045	011650	112777	000300	002346		MOVB #300,@DBUF	:CLEAR BLINC INC COMMAND
2046	011656	013725	011756			MOV PRESET,(R5)+	:SAVE PICTURE CONTENTS
2047	011662	005037	012056			CLR BLNFLG	:CLEAR FLAG
2048	011666	000413				BR BINC3	:
2049	011670	005737	012056		BINC1:	TST BLNFLG	:CHECK BLINK FLAG
2050	011674	001025				BNE BINC2	:BRANCH IF SET
2051	011676	112777	000301	002320		MOVB #301,@DBUF	:SET BLINK INC COMMAND
2052	011704	013725	011756			MOV PRESET,(R5)+	:SAVE PICTURE CONTENTS
2053	011710	012737	000001	012056		MOV #1,BLNFLG	:SET FLAG
2054	011716	005302			BINC3:	DEC R2	:

2055	011720	001013			BNE	BINC2		;BRANCH IF MORE CHARACTERS
2056	011722	112777	000315	002274	MOVB	#315,@DBUF		;DO CR
2057	011730	112777	000312	002266	MOVB	#312,@DBUF		;DO LF
2058	011736	012702	000120		MOV	#80.,R2		;NUMBER OF CHARACTERS IN ROW
2059	011742	005304			DEC	R4		;ANY MORE ROWS
2060	011744	001001			BNE	BINC2		;BRANCH IF YES
2061	011746	000207			RTS	PC		;END RETURN
2062	011750	062716	000004		BINC2:	ADD	#4,(SP)	;CHANGE RETURN ADDRESS
2063	011754	000207			RTS	PC		;MORE RETURN
2064								
2065	011756	000000			PRESET:	0		
2066								
2067	011760	005237	004272		RDYINT:	INC	INTFLG	;SET FLAG
2068	011764	017737	002232	014342	MOV	@CSR,STATUS		;SAVE CSR
2069	011772	042777	000100	002222	BIC	#100,@CSR		;CLEAR ENABLE
2070	012000	000002			RTI			;RETURN.
2071								
2072								
2073								
2074								
2075								
2076	012002	032700	000100		SETBLN:	BIT	#100,R0	;DO WE WANT BLINK ON
2077	012006	001011			BNE	BLN1		;BRANCH IF YES
2078	012010	005737	012056		TST	BLNFLG		;NO, SO IS FLAG OFF
2079	012014	001417			BEQ	BLN2		;BRANCH IF FLAG IS OFF
2080	012016	012777	000302	002200	MOV	#302,@DBUF		;NO, SO CLEAR BLINK CONTROL
2081	012024	005037	012056		CLR	BLNFLG		;AND CLEAR FLAG
2082	012030	000411			BR	BLN2		;ALL DONE
2083	012032	005737	012056		BLN1:	TST	BLNFLG	;WE WANT BLINK ON
2084	012036	001006			BNE	BLN2		;BLINK ALREADY ON SO O.K.
2085	012040	012777	000303	002156	MOV	#303,@DBUF		;BLINK WAS NOT ON SO SET IT
2086	012046	012737	000001	012056	MOV	#1,BLNFLG		;SET FLAG
2087	012054	000207			BLN2:	RTS	PC	;
2088								
2089								
2090	012056	000000			BLNFLG:	0		
2091	012060	021104			BUFF:	BUFF1		


```

2093                                     .SBTTL UTILITY ROUTINES
2094
2095
2096 012062 004737 016632      SET56: JSR      PC, TYP0UT      ;ASK 525 625
2097 012066 012164              ASK56                      ;
2098 012070 004737 016104      JSR      PC, READ           ;READ
2099 012074 020027 000065      CMP      R0, #'5            ;WAS IT 5
2100 012100 001012              BNE      SET56A             ;BRANCH IF NO
2101 012102 012737 177777 012156 MOV      #177777, L525      ;YES, SO SET FLAG
2102 012110 012737 000017 012162 MOV      #15., HALF8V      ;
2103 012116 012737 000024 012160 MOV      #20., HALF6V      ;
2104 012124 000207              RTS      PC                ;DONE
2105 012126 020027 000066      SET56A: CMP      R0, #'6      ;WAS IT 6
2106 012132 001353              BNE      SET56             ;BRANCH IF NO AND ASK AGAIN
2107 012134 005037 012156      CLR      L525              ;CLEAR FLAG
2108 012140 012737 000022 012162 MOV      #18., HALF8V      ;
2109 012146 012737 000030 012160 MOV      #24., HALF6V      ;
2110 012154 000207              RTS      PC                ;DONE
2111
2112 012156 000000      L525: 0
2113 012160 000030      HALF6V: 24.
2114 012162 000022      HALF8V: 18.
2115
2116
2117
2118
2119
2120                                     .SBTTL ASCII STRINGS
2121                                     .NLIST BEX
2122
2123 012164 020133 051511 052040 ASK56: .ASCII  /[ IS THE CONTROLLER JUMPERED FOR 525 OR 626/
2124 012237 040 044514 042516 .ASCII  / LINES,[ TYPE 5 OR 6.....@/
2125 012272 053133 053124 030063 GOMSG: .ASCII  /[VTV30-H/J OR VT30-H DIAGNOSTIC AND!
2126 012335 040 054105 051105 .ASCII  / EXERCISER/
2127 012347 133 040520 052122 .ASCII  /[PART1-----LOGIC TESTS/
2128 012375 133 052123 051101 .ASCII  /[START ADDRESS IS 1000, OR 200/
2129 012433 133 042522 052123 .ASCII  /[RESTART ADDRESS IS 1200/
2130 012463 133 047531 020125 .ASCII  /[YOU ARE STRONGLY ADVISED TO READ THE/
2131 012530 047533 052120 047511 .ASCII  /[OPTION DESCRIPTION BEFORE PROCEEDING,/
2132 012576 040533 054516 043040 .ASCII  /[ANY FURTHER./
2133 012613 133 047506 020122 .ASCII  /[FOR DETAILS OF BUS AND VECTOR ADDRESSES/
2134 012663 133 046120 040505 .ASCII  /[PLEASE REFER TO THE OPTION DESCRIPTION/
2135 012732 055533 040133 .ASCII  /[[[@/
2136 012736 051533 046105 041505 WMSG: .ASCII  /[SELECT DESIRED SWITCH REGISTER OPTIONS[@/
2137 013007 133 042524 052123 TESMSG: .ASCII  /[TEST NO@/
2138 013020 042533 042116 047440 PASMSG: .ASCII  /[END OF PASS[@/
2139 013036 052133 040522 020120 ILVMSG: .ASCII  /[TRAP TO ILLEGAL VECTOR @/
2140 013070 043133 047522 020115 FRMSG: .ASCII  /[FROM ADDRESS @/
2141 013110 043133 051117 052040 FIRVMS: .ASCII  /[FOR THE FIRST VECTOR GROUP@/
2142 013144 043133 051117 052040 NXTVMS: .ASCII  /[FOR THE NEXT VECTOR GROUP@/
2143 013177 133 047516 020116 NOMEMA: .ASCII  /[NON EXISTANT MEMORY HAS NOT BEEN FOUND@/
2144
2145 013247 133 054524 042520 REDMES: .ASCII  /[TYPE CNTRL-C TO CONTINUE @/
2146 013302 051533 051127 036440 SWRMSG: .ASCII  /[SWR = @/
2147 013314 022133 020040 100 MODADM: .ASCII  /[$ @/
2148 013321 040 020057 100 MODSPA: .ASCII  ? / @?
  
```


2149	013325	133	020052	040040	MODPRM:	.ASCII	/[* @/
2150	013332	043133	051111	052123	BAMSG:	.ASCII	/[FIRST BUS ADDRESS IS@/
2151	013366	043133	051111	052123	VAMSG:	.ASCII	/[FIRST VECTOR ADDRESS IS@/
2152	013425	133	047111	040526	ODAMSG:	.ASCII	/[INVALID ADDRESS @/
2153	013450	040533	042104	042522	OVAMSG:	.ASCII	/[ADDRESS EXCEEDS 772 [@/
2154	013477	133	044506	051522	PRMSG:	.ASCII	/[FIRST PRIORITY LEVEL IS@/
2155	013536	047133	054105	020124	NPRMSG:	.ASCII	/[NEXT PRIORITY LEVEL IS@/
2156	013575	133	047516	020116	NXMSG:	.ASCII	/[NON EXISTANT ADDRESS @/
2157	013625	133	047111	040526	BADPRI:	.ASCII	/[INVALID PRIORITY, PLEASE RE-ENTER/
2158	013667	133	044124	020105		.ASCII	/[THE PRIORITY.....@/
2159	013712	042133	043105	052501	NODEFM:	.ASCII	/[DEFAULT SETTINGS ARE NOT ALLOWED/
2160	013753	133	046120	040505		.ASCII	/[PLEASE RE-ENTER THE VALUE@/
2161	014014	042533	040043		EMSG1:	.ASCII	/[E#@/
2162	014020	020040	052101	050040	EMSG2:	.ASCII	/ AT PC @/
2163	014032	043533	047517	020104	EMSG3:	.ASCII	/[GOOD : @/
2164	014043	040	020040	040502	EMSG4:	.ASCII	/ BAD :@/
2165	014054	042133	052101	020101	EMSG5:	.ASCII	/[DATA : @/
2166	014065	040	020040	042101	EMSG6:	.ASCII	/ ADDRESS :@/
2167	014103	133	052123	052101	EMSG7:	.ASCII	/[STATUS :@/
2168	014116	041533	046101	042514	EMSG8:	.ASCII	/[CALLED FROM :@/
2169	014135	040	020040	051105	EMSG9:	.ASCII	/ ERROR COUNT = @/
2170		014160				.EVEN	
2171	014160	000000	000000	000000	OCTNUM:	.WORD	0,0,0
2172	014166	100	000			.BYTE	100,0
2173	014170	040502	042523	030061	BASE11:	.ASCII	/BASE10@/
2174		014200				.EVEN	
2175	014200	000000	000000	000000	DECMSG:	.WORD	0,0,0
2176	014206	000000	000000	000000	OCTMSG:	.WORD	0,0,0,0
2177						.EVEN	
2178						.LIST	BEX

			.SBTTL PROGRAM VARIABLES
2180			
2181			
2182	014216	000000	TESTNO: 0
2183	014220	177570	SWR: HSWR
2184	014222	164000	CSR: 164000
2185	014224	164002	DBUF: 164002
2186	014226	164004	CAR: 164004
2187	014230	164006	CHSR: 164006
2188	014232	164004	CARX: 164004
2189	014234	164005	CARY: 164005
2190	014236	164006	CHDR: 164006
2191	014240	164007	CHAR: 164007
2192	014242	000170	INTVEC: 170
2193	014244	000004	VECLEV: 4
2194	014246	000000	SSWR: 0
2195	014250	000000	REPCNT: 0
2196	014252	000137	JM600: JMP @#START
2197	014256	000001	FSTCNT: 1
2198	014260	000000	TRPARG: 0
2199	014262	000000	TRPSEL: 0
2200	014264	000000	TRPMEM: 0
2201	014266	000000	SAVPC: 0
2202	014270	000000	SAVPC1: 0
2203	014272	000000	SAVSTA: 0
2204	014274	000000	TYPOTA: 0
2205	014276	000000	RAND: 0
2206	014300	000000	TYPD1: 0
2207	014302	000000	MODADR: 0
2208	014304	000000	MODSAV: 0
2209	014306	000000	MASK: 0
2210	014310	000000	BASADD: 0
2211	014312	000000	TRPERR: 0
2212	014314	000000	CHWORD: 0
2213	014316	000000	ERR: 0
2214	014320	000000	PARITY: 0
2215	014322	000000	BCCHAR: 0
2216	014324	052525	RANDN: 52525
2217	014326	000001	RANSEL: 1
2218	014330	000006	RANMTA: 6
2219	014332	052525	RANST: 52525
2220	014334	000000	GOOD: 0
2221	014336	000000	BAD: 0
2222	014340	000000	DATA: 0
2223	014342	000000	STATUS: 0
2224	014344	000000	ADDRES: 0
2225	014346	000000	ERRDIS: 0
2226	014350	000000	ERRARG: 0
2227	014352	000000	CALLPC: 0
2228	014354	000000	TRXVAD: 0
2229	014356	000000	TRXPAR: 0
2230	014360	000000	TRXEXM: 0
2231	014362	000000	NXMADR: 0
2232	014364	000000	SAVEXM: 0
2233	014366	000000	SAVPAR: 0
2234	014370	000000	SAVLT4: 0
2235	014372	000000	SAVLT6: 0

001000

2236	014374	000000	CNVFLG: 0
2237	014376	000000	STRADD: 0
2238	014400	000000	STRLEN: 0
2239	014402	000000	LOWCHR: 0
2240	014404	000000	UPPCHR: 0
2241	014406	000000	RUBFLG: 0
2242	014410	000000	RANDC: 0
2243	014412	000000	FSAVPW: 0
2244	014414	000000	BCOUNT: 0

2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300

014416 004737 016632
014422 013007
014424 013700 014216
014430 004737 016722
014434 004737 016576
014440 000207

.SBTTL PRINT TEST NUMBER

DESCRIPTION:

ROUTINE TO PRINT THE TEST NUMBER IN OCTAL

CALLING SEQUENCE:

JSR PC,TESTR

INPUT PARAMETERS:

TESTNO CONTAINS THE OCTAL TEST NUMBER TO BE
PRINTED

IMPLICIT INPUT PARAMETERS:

THE LABEL TESMSG IS THE START ADDRESS OF AN
ASCII STRING 'TEST NO'

OUTPUT PARAMETERS:

RO WILL BE CORRUPTED

IMPLICIT OUTPUT PARAMETERS:

THE MESSAGE 'TEST NO N' WILL BE PRINTED ON THE
CONSOLE TERMINAL

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

TESTR: JSR PC,TYPOUT ;TEST NO
TESMSG MOV TESTNO,RO ;PRINT OCTAL TEST NO
JSR PC,PROCT
JSR PC,CRLF
RTS PC ;EXIT


```

2302      .SBTTL 'SILLSI' SUBROUTINE
2303
2304
2305      DESCRIPTION:
2306
2307          ROUTINE TO ESTABLISH WHETHER OR NOT THE
2308          DIAGNOSTIC IS RUNNING ON A PROCESSOR
2309          WHICH POSSESSES ONLY ONE INTERRUPT BUS
2310          PRIORITY LEVEL.
2311
2312
2313      CALLING SEQUENCE:
2314
2315          JSR      PC,SILLSI
2316
2317
2318      INPUT PARAMETERS:
2319
2320          NONE
2321
2322
2323      IMPLICIT INPUT PARAMETERS:
2324
2325          NCNE
2326
2327
2328      OUTPUT PARAMETERS:
2329
2330          THE VARIABLE 'LSIFLG' WILL BE SET UP TO
2331          REFLECT WHETHER OR NOT THE PROCESSOR HAS
2332          A SINGLE INTERRUPT PRIORITY LEVEL.
2333
2334          LSIFLG = 0 => MULTIPLE INT. PRIORITIES
2335                  <> 0 => SINGLE INT. PRIORITY
2336
2337
2338      IMPLICIT OUTPUT PARAMETERS:
2339
2340          NONE
2341
2342
2343      COMPLETION CODES:
2344
2345          NONE
2346
2347
2348      POSSIBLE ERROR CODES:
2349
2350          NONE
2351
2352
2353
2354
2355      SILLSI: CLR      LSIFLG      ;SET UP FLAG FOR NON-LSI
2356              MOV      #18,4      ;INSTALL TRAP THRU 4 VECTOR
2357              MOV      #340,6      ;AND CORRESPONDING PRIORITY
  
```

```

014442 005037 014504
014446 012737 014472 000004
014454 012737 000340 000006
  
```

2358				:				
2359	014462	005737	177776	:	TST	PSW		;TRY ADDRESSING THE PSW --
2360	014466	000240		:	NOP			;IF NOT THERE, TRAP THRU 4
2361	014470	000404		:	BR	2\$		;WILL OCCUR, ELSE BRANCH.
2362				:				
2363	014472	022626		1\$:	CMP	(SP)+,(SP)+		;PERFORM A DUMMY RTI
2364	014474	012737	177777 014504	:	MOV	#-1,LSIFLG		;PROCESSOR HAS ONE INT.LEVEL
2365				:				
2366	014502	000207		2\$:	RTS	PC		;RETURN TO MAINLINE, CALL.
2367				:				
2368				:				
2369				:				
2370	014504	000000		:				
2371				:	LSIFLG: 0			;0 => MULTIPLE INT.PRIORITIES
2372				:				; -1=> SINGLE INT. PRIORITY
2373				:				
2374				:				

2376 .SBTTL NON EXISTANT SWR TRAP

2377
 2378
 2379
 2380 DESCRIPTION:

2381 THE TRAP WHEN TESTING FOR THE HARDWARE
 2382 SWITCH REGISTER WILL OCCUR HERE
 2383 THE LOCATION SWR WILL BE SET TO CONTAIN THE
 2384 ADDRESS OF THE SOFTWARE SWITCH REGISTER SSWR
 2385
 2386
 2387
 2388

2389 ENTRY POINT
 2390

2391 SWRSET
 2392

2393 INPUT PARAMETERS:
 2394

2395 OCCURS IF A HARDWARE SWITCH REGISTER IN NOT
 2396 PRESENT
 2397
 2398

2399 IMPLICIT INPUT PARAMETERS:
 2400

2401 NONE
 2402

2403 OUTPUT PARAMETERS:
 2404

2405 THE LOCATION SWR WILL BE SET TO CONTAIN SSWR
 2406
 2407

2408 IMPLICIT OUTPUT PARAMETERS:
 2409

2410 NONE
 2411

2412 COMPLETION CODES:
 2413

2414 AN RTI IS PERFORMED
 2415
 2416

2417 POSSIBLE ERROR CODES:
 2418

2419 NONE
 2420
 2421

2422
 2423
 2424
 2425

2426
 2427

2428 014506 012737 014246 014220 SWRSET: MOV #SSWR,SWR
 2429 014514 000002 RTI

.SBTTL SET UP ILLEGAL VECTOR TRAPS

DESCRIPTION:

ROUTINE TO SET CATCHES FOR TRAPS TO ILLEGAL
VECTORS IN THE RANGE 0 TO 772, DURING THE
RUNNING OF THE TESTS.

THE CATCH IS TO FORCE THE EXECUTION OF AN IOT
TRAP.

THE VECTOR 14 (ODT VECTOR) IS LEFT FREE,
34 (TRAP VECTOR) IS SET TO THE ADDRESS TRAPSV
TO SERVICE THE TRAP INSTRUCTION. THE VECTOR
20 (IOT) IS SET TO ILLVEC TO SERVICE ILLEGAL
VECTOR TRAPS, AND THE ADDRESSES 200 AND 202
ARE SET WITH A JUMP TO START, THUS ALLOWING
THE BE BE RESTARTED FROM ADDRESS 200.
LOCATIONS 30 AND 32 AND SET TO CATCH EMT CALLS
AND HENCE READ THE PROCESSOR PRIORITY.

LOCATION 40 IS LEFT FREE TO CONTAIN THE LOAD
MEDIUM INDICATORS, LOCATION IS LEFT FREE TO
CONTAIN THE XXDP
RETURN ADDRESS (IF PRESENT). LOCATION 46 IS SET TO
CONTAIN A POINTER TO THE XXDP RETURN ADDRESS AND
LOCATION 52 IS SET TO ZERO.

CALLING SEQUENCE:

JSR PC,VECTOR

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

R0 AND R1 WILL BE CORRUPTED

ADDRESSES 0 THRU TO 774 WILL BE SET WITH
APPROPRIATE VALUES

IMPLICIT OUTPUT PARAMETERS:

NONE


```

2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501 014516 005000 VECTOR: CLR R0 ;FILL 0-572 WITH IOT TRAPS
2502 014520 012701 000002 MOV #2,R1
2503 014524 020027 000014 FILL: CMP R0,#14 ;ODT TRAP?
2504 014530 001002 BNE 1$
2505 014532 022020 CMP (R0)+,(R0)+ ;YES BUMP R0
2506 014534 000410 BR FILL1
2507 014536 020027 000040 1$: CMP R0,#40 ;XXDP RETURN ADDRESS
2508 014542 001002 BNE 2$ ;NO
2509 014544 022020 CMP (R0)+,(R0)+ ;YES BUMP R0
2510 014546 000403 BR FILL1
2511 014550 010120 2$: MOV R1,(R0)+ ;'.+2'
2512 014552 012720 000004 MOV #4,(R0)+ ;'IOT'
2513 014556 062701 000004 FILL1: ADD #4,R1
2514 014562 020027 000774 CMP R0,#774
2515 014566 002756 BLT FILL
2516 014570 012737 015124 000034 FILL2: MOV #TRAPSV,34 ;TRAP (LOOP CONTROL)
2517 014576 012737 000340 000036 MOV #340,36
2518 014604 012737 014754 000030 MOV #FADR,30 ; PLUG EMT FOR READING
2519 014612 012737 000340 000032 MOV #340,32 ; THE PROCESSOR STATUS
2520 014620 012737 015024 000020 MOV #ILLVEC,20 ;PLUG 20 FOR IOTS
2521 014626 012737 000340 000022 MOV #340,22
2522 014634 013737 014252 000200 MOV JM600,200 ;SET UP JMP START IN LOC 200
2523 014642 013737 014254 000202 MOV JM600+2,202
2524 014650 012737 014740 000046 MOV #SENDAD,46 ;POINT TO RETURN TO XXDP
2525 014656 005037 000052 CLR 52 ;CLEAR 52
2526 014662 000207 RTS PC ;THEN EXIT
  
```

2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583

.SBTTL XXDP END OF PASS HOOKS

DESCRIPTION:

ROUTINE TO SIGNIFY END OF PASS, AND IF THE
PROGRAM HAS BEEN LOADED USING AN XXDP MONITOR A CALL
WILL BE MADE BACK TO THE MONITOR. THE LOCATIONS USED BY
XXDP ARE 40, AND 41 FOR THE LOAD MEDIUM AND 42, 43 FOR
THE RETURN ADDRESS.
IF A PRESELECTED TEST IS IN OPERATION THE PROGRAM WILL
GO AND SELECT THAT TEST.

ENTRY POINT:

ENDIT

INPUT PARAMETERS:

LOCATION 42/43 CONTAINS THE XXDP RETURN ADDRESS

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

IF LOCATIONS 42/43 ARE NON ZERO THEY ARE
ASSUMED TO CONTAIN THE XXDP MONITOR RETURN ADDRESS

POSSIBLE ERROR CODES:

NONE


```

2584
2585
2586 014664 012706 001000      :
2587 014670      : ENDIT: MOV      #START,SP      : RESET THE STACK
2588 014704 032777 000100 177306 PSWSET #340      : AND PROCESSOR PRIORITY
2589 014712 001402      : BIT      #100,@SWR      : IS THERE A PRESELECT ON
2590 014714 000137 001232      : BEQ      1$      : NO
2591      : JMP      START2      : YES GO SELECT THE TEST
2592      : NO PRESELECT ON SO SIGNAL END OF PASS
2593
2594 014720 004737 015632      1$: JSR      PC,TYPOUT      : END OF PASS
2595 014724 013020      : PASMSG
2596 014726 013700 000042      : MOV      @#42,R0      : GET RETURN ADDRESS TO XXDP
2597 014732 001002      : BNE      $ENDAD      : IF IT IS ZERO THERE IS NO
2598 014734 000137 001232      : JMP      START2      : MONITOR SO RESTART DIAG
2599
2600      :
2601      : $ENDAD: JSR      PC,(R0)      : CALLED VIA XXDP SO RETURN
2602 014740 004710      : NOP      : THERE
2603 014742 000240      : NOP
2604 014744 000240      : NOP
2605 014746 000240      : NOP
2606 014750 000137 001232      : JMP      START2      : ALLOW A SLIGHT PAUSE
2607      : THEN RESTART THE DIAGNOSTIC
2608      :
2609      :

```

2611
 2612
 2613
 2614
 2615
 2616
 2617
 2618
 2619
 2620
 2621
 2622
 2623
 2624
 2625
 2626
 2627
 2628
 2629
 2630
 2631
 2632
 2633
 2634
 2635
 2636
 2637
 2638
 2639
 2640
 2641
 2642
 2643
 2644
 2645
 2646
 2647
 2648
 2649
 2650
 2651

.SBTTL READ PROCESSOR PRIORITY

DESCRIPTION:

THIS IS THE EMT HANDLER AND IS USED TO READ
 THE PROCESSOR PRIORITY OFF THE STACK AND RETURNING
 IT IN FSAVPW

CALLING SEQUENCE:

CALLED BY ISSUING AN EMT

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

THE LOCATIONS 30 AND 32 MUST HAVE BEEN SET
 UP TO POINT TO THIS ROUTINE

OUTPUT PARAMETERS:

THE CONTENTS OF THE PROCESSOR PRIORITY
 ARE RETURNED IN THE LOCATION FSAVPW

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

014754 016637 000002 014412 FADR: MOV 2(SP),FSAVPW ; READ PRIORITY
 014762 000002 RTI ; RETURN TO CALLER

2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708

.SBTTL RING TTY BELL

DESCRIPTION:

ROUTINE TO RING THE BELL ON THE CONSOLE
TERMINAL, IF BIT 5 IS SET IN THE SWITCH
REGISTER.

CALLING SEQUENCE:

JSR PC,BELL

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

THE SWITCH REGISTER MUST HAVE BEEN
SET UP

OUTPUT PARAMETERS:

THE TELETYPE BELL WILL BE RUNG IF
APPROPRIATE

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

014764	032777	000040	177226	BELL:	BIT	#40,ASWR	
014772	001401				BEQ	BELL1	
014774	000207				RTS	PC	
014776	004737	015074		BELL1:	JSR	PC,TPREDY	;WAIT FOR PRINTER READY
015002	112737	000007	177566		MOVB	#7,TPB	
015010	004737	015074			JSR	PC,TPREDY	;WAIT FOR PRINTER READY

VTV LOGIC TESTS MACY11 30A(1052) 06-SEP-79 15:10 PAGE 39-1
CVVTAA.SRC 06-SEP-79 15:03 RING TTY BELL

M 5

SEQ 0064

2709 015014 112737 000000 177566
2710 015022 000207

MOVB #0,TPB
RTS PC

;PRINT NULL
;GO OUT

2712
 2713
 2714
 2715
 2716
 2717
 2718
 2719
 2720
 2721
 2722
 2723
 2724
 2725
 2726
 2727
 2728
 2729
 2730
 2731
 2732
 2733
 2734
 2735
 2736
 2737
 2738
 2739
 2740
 2741
 2742
 2743
 2744
 2745
 2746
 2747
 2748
 2749
 2750
 2751
 2752
 2753
 2754
 2755
 2756
 2757
 2758
 2759
 2760
 2761
 2762
 2763
 2764
 2765
 2766
 2767

.SBTTL ILLEGAL VECTOR TRAP CATCH

DESCRIPTION:

TRAPS TO ILLEGAL VECTORS WILL BE
 REPORTED HERE. THE VECTOR TO WHICH
 THE TRAP OCCURRED WILL BE PRINTED
 AS WELL AS THE ADDRESS IN THE MAIN
 LINE CODE FROM WHICH THE TRAP OCCURRED.
 A PROGRAM RESTART IS THEN PERFORMED,
 UNLESS A NEW TEST HAS BEEN SELECTED
 WHILE RUNNING UNDER A SOFTWARE
 SWITCH REGISTER.

ENTRY POINT

ILLVEC

INPUT PARAMETERS:

ENTRY IS CAUSED BY AN ILLEGAL
 VECTOR TRAP

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

THE VECTOR AND MAINLINE ADDRESS
 WILL BE PRINTED

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

A PROGRAM RESTART OR A NEW
 TEST SELECTION .

POSSIBLE ERROR CODES:

NONE

2768
2769
2770
2771
2772
2773
2774 015024 004737 016632
2775 015030 013036
2776 015032 012600
2777 015034 162700 000004
2778 015040 004737 016722
2779 015044 004737 016632
2780 015050 013070
2781 015052 005726
2782 015054 012600
2783 015056 004737 016722
2784 015062 005726
2785 015064 004737 015344
2786 015070 000137 001200

;
:
:
; A TRAP TO AN UNRECOGNISED VECTOR WILL
; BE REPORTED FROM HERE.
:
ILLVEC: JSR PC, TYP0UT
ILVMSG
MOV (SP)+, R0
SUB #4, R0
JSR PC, PROCT ; PRINT VECTOR
JSR PC, TYP0UT
FRMMSG ; PRINT MAINLINE ADDRESS
TST (SP)+
MOV (SP)+, R0
JSR PC, PROCT
TST (SP)+
JSR PC, MONIT
JMP RSTART

2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837

.SBTTL WAIT FOR PRINTER READY

DESCRIPTION:

ROUTINE TO WAIT UNTIL THE PRINTER
ON THE CONSOLE TERMINAL IS READY,
IE: IT IS READY TO PRINT THE NEXT
CHARACTER.

CALLING SEQUENCE:

JSR PC,TPREDY

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

TPREDY: TSTB TPS ;ROUTINE TO WAIT FOR PRINTER READY
BPL TPREDY
RTS PC

015074 105737 177564
015100 100375
015102 000207

2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894

.SBTTL SET ITERATION COUNT

DESCRIPTION:

-- ROUTINE TO SET UP THE TEST ITERATION
COUNT. A PROPOSED COUNT IS SET IN R4
THEN UNLESS BIT 13 IN THE SWITCH REGISTER
IS SET, THE SAME VALUE IS RETURNED.
IF BIT 13 IS SET THEN FAST ITERATION IS
ASSUMED AND A VALUE OF 1 IS RETURNED IN
R4.

CALLING SEQUENCE:

JSR PC,FASTSW

INPUT PARAMETERS:

R4 CONTAINS THE PROPOSED ITERATION
COUNT

IMPLICIT INPUT PARAMETERS:

SETTING BIT 13 IN THE SWR WILL INDICATE
FAST ITERATION, AND A SINGLE PASS
WILL BE REQUESTED

OUTPUT PARAMETERS:

R4 WILL CONTAIN THE ACTUAL ITERATION
COUNT

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

015104 032777 020000 177106 FASTSW: BIT #20000,@SWR

VTV LOGIC TESTS MACY11 30A(1052) 06-SEP-79 15:10 PAGE 42-1
CVVTAA.SRC 06-SEP-79 15:03 SET ITERATION COUNT

E 6

SEQ 0069

2895	015112	001001		BNE	1\$
2896	015114	000207		RTS	PC
2897	015116	013704	014256	MOV	FSTCNT,R4
2898	015122	000207		RTS	PC

2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955

.SBTTL TRAP SERVICE ROUTINE

DESCRIPTION:

TRAP HANDLING ROUTINE. THE TRAP HANDLER IS ENTERED UPON THE EXECUTION OF ANY TRAP INSTRUCTION. IT COMPARES THE LOWER BYTE OF THE TRAP INSTRUCTION WITH THE CONTENTS ON THE SWITCH REGISTER, AND IF A MATCH IS FOUND TAKES THE CONTENTS OF THE ADDRESS FOLLOWING THE TRAP INSTRUCTION AS THE RETURN ADDRESS.

THE EXPECTED FORMAT IS:

TRAP+N
ADDR

WHERE ADDR IS THE ADDRESS TO PROCEED TO IF N MATCHES THE SWITCH REGISTER SETTINGS. THE TRAP ARGUMENT IS RELATED TO THE SWITCH REGISTER SETTINGS THUS:

TRAP ARG	SWR SETTING
2	200
4	400
10	1000
20	2000
30	3000
40	4000
50	5000
60	6000
70	7000

THE SETTING OF SWR BIT 12, WILL FORCE THE TRAP HANDLER TO USE THE SWR SETTINGS THAT WERE IN FORCE WHEN THE LAST TRAP INSTRUCTION WAS EXECUTED.

IF A CNTRL-G IS OUTSTANDING ON THE CONSOLE TERMINAL WHEN THE TRAP WAS EXECUTED, THEN MONIT IS CALLED. IF CNTRL-O WAS OUTSTANDING THEN MODIFY IS CALLED

ENTRY POINT

TRAPSV

INPUT PARAMETERS:

ON EXECUTION OF ANY TRAP INSTRUCTION

IMPLICIT INPUT PARAMETERS:

THE SWR HAS BEEN SET UP

OUTPUT PARAMETERS:

EXIT TO THE CONTENTS OF THE ADDRESS FOLLOWING
 THE TRAP INSTRUCTION IF A MATCH WAS FOUND, ELSE THE
 PROGRAM WILL CONTINUE FROM THE ADDRESS AFTER THAT.

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011

015124 004737 015536
 015130 011600
 015132 016037 177776 014260
 015140 105737 177560
 015144 100015
 015146 004737 016104
 015152 120027 000017
 015156 001003
 015160 004737 017162
 015164 000405
 015166 120027 000007
 015172 001002
 015174 004737 015344
 015200 017737 177014 014262
 015206 132737 000020 014263
 015214 001012
 015216 013737 014262 014264
 015224 042737 170777 014264
 015232 132737 000016 014263
 015240 001412
 015242 013700 014260
 015246 006000
 015250 006000
 015252 000300

TRAPSV: JSR PC, SAVREG ;SAVE REGS
 MOV (SP), RO
 MOV -2(RO), TRPARG ;GET TRAP CALL
 TSTB TKS ;LOOK FOR MONITOR CALL
 BPL 3\$
 JSR PC, READ
 CMPB RO, #17 ;IS IT CNTRL-O ?
 BNE 1\$;NO
 JSR PC, MODIFY ;YES CALL MODIFIER ROUTINE
 BR 3\$
 1\$: CMPB RO, #7 ;IS IT CTRL-G?
 BNE 3\$
 JSR PC, MONIT ;YES, GO TO SWR MONITOR
 3\$: MOV @SWR, TRPSEL
 BITB #20, TRPSEL+1 ;IS IT PRESERVE SCOPE
 BNE TRPSCP ;YES
 MOV TRPSEL, TRPMEM ;NO SO SAVE SWITCH SETTING
 BIC #170777, TRPMEM ;GET IT SO WE CAN COMPARE
 BITB #16, TRPSEL+1 ;ANY SCOPE LEVELS SET
 BEQ TRPLP ;NO
 TRPSCP: MOV TRPARG, RO ;YES
 ROR RO ;GET TO POSITION FOR COMPARE
 ROR RO ;FOR 10 & ABOVE
 SWAB RO ;ONLY FOR SCOPE BITS(9-11)

3012	015254	042700	170777		BIC	#170777,R0	:ARGUMENT SCOPE BITS
3013	015260	020037	014264		CMP	R0,TRPMEM	:AS SELECTED ?
3014	015264	001422			BEQ	TRPBAK	:YES, GO BACK
3015	015266	013700	014262	TRPLP:	MOV	TRPSEL,R0	:NO, TEST LOOP
3016	015272	006100			ROL	R0	:FOR BITS 7&8
3017	015274	006100			ROL	R0	
3018	015276	000300			SWAB	R0	
3019	015300	142700	000371		BICB	#371,R0	:CUT OUT SW06
3020	015304	142737	000370	014260	BICB	#370,TRPARG	:ONLY SWITCHES 7 OR 8 NOW
3021	015312	130037	014260		BITB	R0,TRPARG	:ANY SELECTED ?
3022	015316	001005			BNE	TRPBAK	:YES
3023	015320	004737	015634		JSR	PC,RSTREG	
3024	015324	062716	000002		ADD	#2,(SP)	:NO SCOPE OR LOOP,SO RUN
3025	015330	000002			RTI		:PAST ARGUMENT AND RETURN
3026	015332	004737	015634	TRPBAK:	JSR	PC,RSTREG	:RESTORE REGS
3027	015336	017616	000000		MOV	@(SP),(SP)	:RETURN ADDRESS TO STACK
3028	015342	000002			RTI		:EXIT, LOOPING

3030
3031
3032
3033
3034
3035
3036
3037
3038
3039
3040
3041
3042
3043
3044
3045
3046
3047
3048
3049
3050
3051
3052
3053
3054
3055
3056
3057
3058
3059
3060
3061
3062
3063
3064
3065
3066
3067
3068
3069
3070
3071
3072
3073
3074
3075
3076
3077
3078
3079
3080
3081
3082
3083
3084
3085

.SBTTL SWITCH REGISTER MONITOR

DESCRIPTION:

SWITCH REGISTER MONITOR. CALLED BY AN ERROR WITH SWR BIT 15 CLEAR, OR BY TYPING CTRL-G ON THE CONSOLE TELETYPE. IF USING HARDWARE SWR, SIMPLY ASKS FOR CTRL-C TO CONTINUE. OTHERWISE, IT PRINTS THE CURRENT CONTENTS OF THE SOFTWARE SWITCH REGISTER, FOLLOWED BY A PROMPT (>). THE NEW SWITCH REGISTER SETTINGS SHOULD THEN BE ENTERED AS AN OCTAL NUMBER, TERMINATED BY CARRIAGE RETURN. TYPING CARRIAGE RETURN ALONE WILL CAUSE THE SWITCH REGISTER CONTENTS TO REMAIN UNCHANGED. IF THE SWITCH REGISTER IS UPDATED TO SELECT A TEST (BIT 6 SET) THE NEW TEST WILL BE ENTERED IMMEDIATELY.

CALLING SEQUENCE:

JSR PC,MONIT

INPUT PARAMETERS:

BY TYPING CNTRL-G DURING THE RUNNING OF THE TESTS.

IMPLICIT INPUT PARAMETERS:

THE SOFTWARE SWITCH REGISTER, IF BEING USED MUST HAVE BEEN SET UP.

OUTPUT PARAMETERS:

IF RUNNING UNDER SOFTWARE SWITCH REGISTER MODE A NEW SETTING OF THE SWR COULD HAVE BEEN SET UP.

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

```

3086
3087
3088
3089 015344 010046
3090 015346 023727 014220 177570
3091 015354 001430
3092 015356 004737 016632
3093 015362 013302
3094 015364 013700 014246
3095 015370 004737 016722
3096 015374 012700 000076
3097 015400 004737 016710
3098 015404 004737 015732
3099 015410 005737 014276
3100 015414 001413
3101 015416 010037 014246
3102 015422 032737 000100 014246
3103 015430 001405
3104 015432 000137 001232
3105 015436 004737 015454
3106 015442 000775
3107 015444 004737 016576
3108 015450 012600
3109 015452 000207

      :
      :
      :
MONIT: MOV    RO,-(SP)      ;SAVE RO
      CMP    SWR,#HSWR     ;HARDWARE SWR?
      BEQ    MONITA        ;IF YES, GO TO END
      JSR    PC,TYP0UT     ;SWR=
      SWRMSG
      MOV    SSWR,RO
      JSR    PC,PROCT
      MOV    #76,RO
      JSR    PC,PCHR       ;PRINT ">"
      JSR    PC,OCTIN      ;GET NEW SETTING
      TST    RAND         ;ANY INPUT?
      BEQ    MONITX
      MOV    RO,SSWR       ;YES UPDATE SSWR
      BIT    #100,SSWR     ;TEST SELECTED?
      BEQ    MONITX
      JMP    START2        ;YES GO DO IT
MONITA: JSR    PC,TYPCTC   ;CIRL-C TO CONTINUE
      BR     MONITA
MONITX: JSR    PC,CRLF
      MOV    (SP)+,RO      ;RESTORE RO
      RTS    PC
  
```


3111
3112
3113
3114
3115
3116
3117
3118
3119
3120
3121
3122
3123
3124
3125
3126
3127
3128
3129
3130
3131
3132
3133
3134
3135
3136
3137
3138
3139
3140
3141
3142
3143
3144
3145
3146
3147
3148
3149
3150
3151
3152
3153
3154
3155
3156
3157
3158
3159
3160
3161
3162
3163
3164
3165
3166

.SBTTL WAIT FOR CNTRL-C

DESCRIPTION:

ROUTINE TO WAIT FOR THE USER TO TYPE
 CNTRL-C ON THE CONSOLE. IF CNTRL-O IS HIT MODIFY
 IS CALLED, AND IF CNTRL-G IS HIT MONIT IS CALLED.
 IF NONE OF THESE ARE HIT, THE ROUTINE WILL RETURN
 TO THE NEXT LOCATION AFTER THE CALL. IF CNTRL-C WAS
 HIT THE ROUTINE WILL RETURN TO THE NEXT LOCATION+2.

CALLING SEQUENCE:

JSR PC,TYPCTC

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

INPUT IS REQUESTED FROM THE CONSOLE

OUTPUT PARAMETERS:

RO IS CORRUPTED

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

A RETURN TO THE FIRST OR SECOND LOCATION AFTER
 THE CALL IS PERFORMED.

POSSIBLE ERROR CODES:

NONE

TYPCTC:	JSR	PC,TYPOUT	;PRINTS TYPE CTRL/C WHEN READY
	REDMES		
QEXIT:	JSR	PC,READ	;CTRL/C ENTERED
	CMP	RO,#3	
	BNE	QEXIT2	;NO

015454	004737	016632
015460	013247	
015462	004737	016104
015466	020027	000003
015472	001005	

3167	015474	004737	016576		JSR	PC,CRLF	
3168	015500	062716	000002		ADD	#2,(SP)	;YES SO JUMP OVER NO FIND RETURN
3169	015504	000207		QEXIT1:	RTS	PC	;GO BACK
3170	015506	020027	000017	QEXIT2:	CMP	R0,#17	;CNTRL-O ?
3171	015512	001003			BNE	QEXIT3	;NO
3172	015514	004737	017162		JSR	PC,MODIFY	;YES CALL MODIFY PROGRAM
3173	015520	000755			BR	TYPCTC	;THEN GO BACK TO START
3174	015522	020027	000007	QEXIT3:	CMP	R0,#7	;CTRL-G?
3175	015526	001366			BNE	QEXIT1	
3176	015530	004737	015344		JSR	PC,MONIT	;GO TO SWR MONITOR
3177	015534	000747			BR	TYPCTC	;LOOK FOR CTRL-C AGAIN
3178							
3179							

3181
3182
3183
3184
3185
3186
3187
3188
3189
3190
3191
3192
3193
3194
3195
3196
3197
3198
3199
3200
3201
3202
3203
3204
3205
3206
3207
3208
3209
3210
3211
3212
3213
3214
3215
3216
3217
3218
3219
3220
3221
3222
3223
3224
3225
3226
3227
3228
3229
3230
3231
3232
3233
3234
3235
3236

.SBTTL SAVE REGISTERS

DESCRIPTION:

ROUTINE TO SAVE ALL THE GENERAL PURPOSE
 REGISTERS ON THE STACK, AND LEAVE THE ADDRESS OF THE
 CALLING ROUTINE ON THE STACK. THE ROUTINE WILL RUN AT
 PRIORITY 7 TO AVOID ANY INTERRUPTS

CALLING SEQUENCE:

JSR PC,SAVREG

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

REGISTERS 0 THRU 5 ARE SAVED ON THE STACK
 AND THE RETURN ADDRESS OF THE CALLING ROUTINE IS
 SET AS THE LAST ENTRY ON THE STACK

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

SAVREG: PSWREA SAVSTA
 PSWSET #340
 MOV (SP)+,SAVPC ;SAVE PC FOR RETURN FROM THIS
 ; ROUTINE
 MOV (SP)+,SAVPC1

015536
 015546
 015562 012637 014266
 015566 012637 014270

3237	015572	010546		MOV	R5,-(SP)	
3238	015574	010446		MOV	R4,-(SP)	
3239	015576	010346		MOV	R3,-(SP)	
3240	015600	010246		MOV	R2,-(SP)	
3241	015602	010146		MOV	R1,-(SP)	
3242	015604	010046		MOV	R0,-(SP)	
3243	015606	013746	014270	MOV	SAVPC1,-(SP)	
3244	015612	013746	014266	MOV	SAVPC,-(SP)	;PUT PC READY FOR
3245	015616			PSWSET	SAVSTA	
3246	015632	000207		RTS	PC	;RETURN
3247						
3248						
3249						

3251 .SBTTL RESTORE REGISTERS

3252
 3253
 3254
 3255
 3256
 3257
 3258
 3259
 3260
 3261
 3262
 3263
 3264
 3265
 3266
 3267
 3268
 3269
 3270
 3271
 3272
 3273
 3274
 3275
 3276
 3277
 3278
 3279
 3280
 3281
 3282
 3283
 3284
 3285
 3286
 3287
 3288
 3289
 3290
 3291
 3292
 3293
 3294
 3295
 3296

DESCRIPTION:

RESTORE TO RESTORE THE GENERAL PURPOSE
 REGISTERS. THE STACK IS LEFT IN THE SAME STATE AS IT
 WAS WHEN SAVREG WAS CALLED.

CALLING SEQUENCE:

JSR PC,RSTREG

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

R0 THRU R5 RESTORED

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

3297 015634
 3298 015644
 3299 015660 012637 014266
 3300 015664 012637 014270
 3301 015670 012600
 3302 015672 012601
 3303 015674 012602
 3304 015676 012603
 3305 015700 012604
 3306 015702 012605

RSTREG: PSWREA SAVSTA
 PSWSET #340
 MOV (SP)+,SAVPC
 MOV (SP)+,SAVPC1
 MOV (SP)+,R0
 MOV (SP)+,R1
 MOV (SP)+,R2
 MOV (SP)+,R3
 MOV (SP)+,R4
 MOV (SP)+,R5

3307	015704	013746	014270	MOV	SAVPC1,-(SP)	
3308	015710	013746	014266	MOV	SAVPC,-(SP)	;PUT PC READY FOR
3309	015714			PSWSET	SAVSTA	
3310	015730	000207		RTS	PC	;RETURN

.SBTTL ENTER AN OCTAL NUMBER

DESCRIPTION:

ROUTINE TO ENTER AN OCTAL NUMBER ON THE CONSOLE.
THE NUMBER ENTERED IS RETURNED IN R0, AND THE VALUE RAND
IS SET TO NON ZERO IF ANY CHARACTERS WERE ENTERED.
TYPING CARRIAGE RETURN, LINE FEED OR ESCAPE WILL
TERMINATE THE LINE BEING ENTERED.
RUBOUT WILL DELETE THE LAST CHARACTER ENTERED,
CNTRL-U WILL RUBOUT THE WHOLE LINE, AND CNTRL-R
WILL TYPE OUT THE CHARACTERS SO FAR ENTERED.
RAND WILL BE SET TO NON ZERO IF ANY CHARACTERS
WERE HIT AND RANDC WILL CONTAIN THE TERMINATING
CHARACTER.

A '!' WILL BE PRINTED IF AN OVERFLOW CONDITION IS
DETECTED AND A '?' IF AN INVALID CHARACTER WAS
ENTERED.

CALLING SEQUENCE:

JSR PC,OCTIN

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

R0 CONTAINS THE NUMBER ENTERED.
RAND=0 IF NO CHARACTERS WERE ENTERED.

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

3312
3313
3314
3315
3316
3317
3318
3319
3320
3321
3322
3323
3324
3325
3326
3327
3328
3329
3330
3331
3332
3333
3334
3335
3336
3337
3338
3339
3340
3341
3342
3343
3344
3345
3346
3347
3348
3349
3350
3351
3352
3353
3354
3355
3356
3357
3358
3359
3360
3361
3362
3363
3364
3365
3366
3367

```

3368
3369
3370
3371 015732 004737 015536
3372 015736 005000
3373 015740 005037 014276
3374 015744 012737 014206 014376
3375 015752 012737 000006 014400
3376 015760 012737 000060 014402
3377 015766 012737 000067 014404
3378 015774 005037 014374
3379 016000 004737 016130
3380 016004 013701 014400
3381 016010 001420
3382 016012 012702 014206
3383 016016 112203
3384 016020 162703 000060
3385 016024 000241
3386 016026 006300
3387 016030 103417
3388 016032 006300
3389 016034 103415
3390 016036 006300
3391 016040 050300
3392 016042 005237 014276
3393 016046 005301
3394 016050 001362
3395 016052 010037 014274
3396 016056 004737 015634
3397 016062 013700 014274
3398 016066 000207
3399 016070 012700 000041
3400 016074 004737 016710
3401 016100 000137 015736
3402

:
:
:
OCTIN: JSR PC, SAVREG ; SAVE THE REGISTERS*
TYPOTB: CLR RO ; CLEAR RO
CLR RAND ; CLEAR FLAG WORD
MOV #OCTMSG, STRADD ; SET START ADDRESS OF STRING
MOV #6, STRLEN ; AND ITS SIZE
MOV #60, LOWCHR ; MINIMUM CHAR
MOV #67, UPPCHR ; MAXIMUM CHAR
CLR CNVFLG ; DON'T CONVERT TO UPPER CASE
JSR PC, GETSTR ; GET A STRING
MOV STRLEN, R1 ; ZERO LENGTH ?
BEQ TYPOTD ; YES
MOV #OCTMSG, R2 ; NO GET START ADDRES OF STRING
TYPOTC: MOVB (R2)+, R3 ; GET A CHARACTER
SUB #60, R3 ; PUT IN RANGE
CLC
ASL RO ; SHIFT OUT RESULT
BCS TYPOTE ; C BIT SET ERROR
ASL RO ; TIMES 4
BCS TYPOTE ; C BIT ERROR
ASL RO ; TIMES 8
BIS R3, RO ; SET NEW BITS IN
INC RAND ; SET GOOD
DEC R1
BNE TYPOTC ; LOOP IF MORE TO COME
TYPOTD: MOV RO, TYPOTA ; SAVE FINAL NUMBER
JSR PC, RSTREG ; RESTORE REGISTERS
MOV TYPOTA, RO ; GET RESULT
RTS PC
TYPOTE: MOV #41, RO ; OVERFLOW
JSR PC, PCHR ; PRINT A !
JMP TYPOTB ; THEN GO AGAIN
:

```


3404
3405
3406
3407
3408
3409
3410
3411
3412
3413
3414
3415
3416
3417
3418
3419
3420
3421
3422
3423
3424
3425
3426
3427
3428
3429
3430
3431
3432
3433
3434
3435
3436
3437
3438
3439
3440
3441
3442
3443
3444
3445
3446
3447
3448
3449
3450
3451
3452
3453
3454
3455

.SBTTL READ A SINGLE CHARACTER

DESCRIPTION:

ROUTINE TO READ A SINGLE CHARACTER
 FROM THE CONSOLE. THE CHARACTER IS RETURN IN R0
 AND HAS THE 200 BIT STRIPPED OFF.

CALLING SEQUENCE:

JSR PC,READ

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

R0 CONTAINS THE CHARACTER READ IN.

IMPLICIT OUTPUT PARAMETERS:

THE CHARACTER IS ECHOED ON THE TERMINAL

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

READ: -TSTB TKS
 BPL READ
 MOV TKB,R0
 BIC #177600,R0
 JSR PC,PCHR
 RTS PC

016104 105737 177560
 016110 100375
 016112 013700 177562
 016116 042700 177600
 016122 004737 016710
 016126 000207

3457
3458
3459
3460
3461
3462
3463
3464
3465
3466
3467
3468
3469
3470
3471
3472
3473
3474
3475
3476
3477
3478
3479
3480
3481
3482
3483
3484
3485
3486
3487
3488
3489
3490
3491
3492
3493
3494
3495
3496
3497
3498
3499
3500
3501
3502
3503
3504
3505
3506
3507
3508
3509
3510
3511
3512

.SBTTL ENTERING A CHARACTER STRING

DESCRIPTION:

ROUTINE TO ENTER A STRING OF CHARACTERS ON
THE CONSOLE TERMINAL. VARIOUS CONTROL CODES
ARE USED TO CONTROL HOW THE CHARACTERS ARE
INTERPTED:

ESCAPE, CARRIAGE RETURN AND LINE FEED ARE USED
TO TERMINATE THE STRING. RUBOUT WILL DELETE THE
LAST CHARACTER ENTERED, CNTRL-U WILL DELETE THE
ALL THE CHARACTERS ENTERED, AND CNTRL-R WILL ECHO
THOSE CHARACTERS ALREADY ENTERED.

ON ENTRY THE FOLLOWING POINTERS ARE USED:
STRADD TO INDICATE THE START OF THE CHARACTER STRING
STRLEN TO INDICATE ITS SIZE
CVNFLG SET TO CONVERT LOWER CASE TO UPPER CASE
UPPCHR TO INDICATE THE HIGHEST CHARACTER CODE
LOWCHR TO INDICATE THE LOWEST CHARACTER CODE

ON EXIT THE LOCATION STRLEN WILL INDICATE THE
NUMBER OF CHARACTERS ENTERED AND RANDC WILL CONTAIN
THE TERMINATING CHARACTER

IF AN INVALID CHARACTER WAS HIT A '?' IS PRINTED

CALLING SEQUENCE:

JSR PC,GETSTR

INPUT PARAMETERS:

STRADD THE START ADDRESS OF THE STRING
STRLEN THE NUMBER OF CHARACTERS TO READ
UPPCHR THE HIGHEST CHARACTER CODE ALLOWED
LOWCHR THE LOWEST CHARACTER CODE ALLOWED
CNVFLG TO INDICATE LOWER TO UPPER CASE CONVERSION

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

STRLEN THE NUMBERS OF CHARACTERS READ
RANDC THE TERMINATING CHARACTER


```

3513 ; IMPLICIT OUTPUT PARAMETERS:
3514 :
3515 :     NONE
3516 :
3517 :
3518 : COMPELETION CODES:
3519 :
3520 :     NONE
3521 :
3522 :
3523 : POSSIBLE ERROR CONDITIONS:
3524 :
3525 :
3526 :     A '?' IS PRINTED IF AN INVALID CHARACTER IS ENTERED
3527 :
3528 :
3529 :
3530 :
3531 :
3532 :
3533 GETSTR: JSR      PC,SAVREG      ; SAVE REGISTERS
3534 GETCH1: CLR      RUBFLG        ; CLEAR RUBOUT FLAG
3535         MOV      STRADD,R2     ; GET STARTING POINTER
3536         CLR      R1           ; SET INTITAL LENGTH
3537 GETCH2: TSTB     TKS          ; ANY TTY INPUT
3538         BPL      GETCH2       ; NO WAIT FOR IT
3539         MOV      TKB,R0       ; GET CHARACTER
3540         BIC      #177600,R0   ; CLEAR RUBBISH
3541 :
3542 : CHECK FOR CONTROL CODES
3543 :
3544         CMP      R0,#15      ; WAS IT <CR> ?
3545         BNE      1$          ; NO
3546         JMP      CHRFIN
3547 1$:      CMP      R0,#12      ; WAS IT <LF>
3548         BNE      3$          ; NO
3549         JMP      CHRFIN
3550 3$:      CMP      R0,#33      ; WAS IT <ESC>
3551         BNE      5$          ; NO
3552         JMP      CHRFIN
3553 5$:      CMP      R0,#177     ; RUBOUT ?
3554         BNE      7$          ; NO
3555         JMP      RUBCHR      ; YES
3556 7$:      CMP      R0,#22      ; CNTRL-R
3557         BNE      9$          ; NO
3558         JMP      LINECH      ; YES EXCO LINE
3559 9$:      CMP      R0,#25      ; CNTRL-U
3560         BNE      GETCH3      ; NO
3561         JMP      LINDEL      ; YES DELETE LINE
3562 :
3563 : IT WAS NOT A CONTROL CODE CHECK
3564 : FOR LEGALITY ?
3565 :
3566 :
3567 GETCH3: CMP      R0,#140      ; IS IT LOWER CASE
3568         BLT      3$          ; NO
  
```

```

3569 016266 005737 014374          TST      CNVFLG      : YES DO WE CONVERT TO UPPER
3570 016272 001402                   BEQ      3$          : NO
3571 016274 042700 000040          BIC      #40,R0      : YES STRIP 40 OFF
3572 016300 020037 014402          3$: CMP      R0,LOWCHR    : IS THE CHAR TOO SMALL
3573 016304 002002                   BGE      5$          : NO
3574 016306 000137 016534          JMP      ILLCHR      : YES
3575 016312 020037 014404          5$: CMP      R0,UPPCHR    : IS THE CHAR TOO BIG ?
3576 016316 003402                   BLE      GETCH4      : NO
3577 016320 000137 016534          JMP      ILLCHR      : YES ITS ILLEGAL
3578                                     :
3579                                     : WE HAVE A LEGAL CHARACTER
3580
3581 016324 010003                   GETCH4: MOV     R0,R3      : SAVE CHAR
3582 016326 005737 014406          TST      RUBFLG      : IS RUBOUT SET
3583 016332 001406                   BEQ      3$          : NO
3584 016334 012700 000057          MOV     #57,R0      : YES PRINT A '/'
3585 016340 004737 016710          JSR     PC,PCHR      :
3586 016344 005037 014406          CLR     RUBFLG      : CLEAR RUBOUT FLAG
3587 016350 005201                   3$: INC      R1          : UPDATE CHAR COUNT
3588 016352 020137 014400          CMP     R1,STRLEN    : END OF STRING SEEN
3589 016356 003403                   BLE      5$          : NO
3590 016360 005000                   CLR     R0          : YES, FORCE A NULL TERMINATOR
3591 016362 000137 016554          JMP     CHRFIN        : AND COMPLETE
3592 016366 010300                   5$: MOV     R3,R0      : RESTORE CHAR
3593 016370 004737 016710          JSR     PC,PCHR      : ECHO IT
3594 016374 110022                   MOV     R0,(R2)+      : SAVE IT IN BUFFER
3595 016376 000137 016146          JMP     GETCH2        : NO GET NEXT ONE
3596
3597                                     : RUBOUT WAS HIT
3598
3599 016402 005701                   RUBCHR: TST     R1          : ANY CHARACTERS TO RUBOUT
3600 016404 001002                   BNE      3$          : YES
3601 016406 000137 016470          JMP     LINDL1        : NO
3602 016412 005737 014406          3$: TST     RUBFLG      : IS RUBOUT SET ALREADY ?
3603 016416 001006                   BNE      5$          : YES
3604 016420 012700 000057          MOV     #57,R0      : NO PRINT A '/'
3605 016424 004737 016710          JSR     PC,PCHR      :
3606 016430 005237 014406          INC     RUBFLG      : SET RUBOUT
3607 016434 114200                   5$: MOV     -(R2),R0    : GET LAST CHAR ENTERED
3608 016436 004737 016710          JSR     PC,PCHR      : PRINT IT
3609 016442 005301                   DEC     R1          : REDUCE COUNT
3610 016444 000137 016146          JMP     GETCH2        : GET ANOTHER CHAR
3611
3612                                     : RUBOUT LINE WAS HIT
3613
3614 016450 012700 000136                   LINDEL: MOV     #136,R0    : PRINT A ^
3615 016454 004737 016710          JSR     PC,PCHR      :
3616 016460 012700 000125                   MOV     #125,R0        : THEN U
3617 016464 004737 016710          JSR     PC,PCHR      :
3618 016470 004737 016576          LINDL1: JSR     PC,CRLF   : START ON A NEWLINE
3619 016474 000137 016134          JMP     GETCH1        : A GO BACK TO BEGINNING
3620
3621                                     : CNTRL-R WAS HIT
3622
3623 016500 112712 000100                   LINECH: MOV     #'@,(R2)  : PUT IN A TERMINATOR
3624 016504 004737 016576          JSR     PC,CRLF      : START ON A NEW LINE

```


3625	016510	013737	014376	016526	MOV	STRADD,3\$	; SET START ADDRESS
3626	016516	005037	014406		CLR	RUBFLG	; CLEAR RUBOUTS
3627	016522	004737	016632		JSR	PC,TYPOUT	; PRINT LINE
3628	016526	000000		3\$: 0			
3629	016530	000137	016146		JMP	GETCH2	; AND GET ANOTHER CHAR
3630							
3631							
3632							
3633	016534	004737	016710		ILLCHR: JSR	PC,PCHR	; ECHO IT
3634	016540	012700	000077		MOV	#'?,RO	; PRINT A ?
3635	016544	004737	016710		JSR	PC,PCHR	
3636	016550	000137	016500		JMP	LINECH	; THE ECHO LINE
3637							
3638							
3639							
3640	016554	010037	014410		CHRFIN: MOV	RO,RANDC	; SAVE TERMINATOR
3641	016560	163702	014376		SUB	STRADD,R2	; CALCULATE BYTE COUNT
3642	016564	010237	014400		MOV	R2,STLEN	; SET IT FOR RETURN
3643	016570	004737	015634		JSR	PC,RSTREG	; RESTORE REGISTERS
3644	016574	000207			RTS	PC	; AND EXIT

3646
3647
3648
3649
3650
3651
3652
3653
3654
3655
3656
3657
3658
3659
3660
3661
3662
3663
3664
3665
3666
3667
3668
3669
3670
3671
3672
3673
3674
3675
3676
3677
3678
3679
3680
3681
3682
3683
3684
3685
3686
3687
3688
3689
3690
3691
3692
3693
3694
3695
3696
3697
3698
3699
3700
3701

.SBTTL CARRIAGE RETURN LINE FEED

DESCRIPTION:

ROUTINE TO DO A <CR> <LF> ON THE
 CONSOLE TERMINAL

CALLING SEQUENCE:

JSR PC,CRLF

INPUT PARAMETERS:

NONE

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

THE CARRIAGE WILL BE PLACED ON A NEW LINE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

```
CRLF:  MOV    R0,-(SP)
        MOV    #15,R0          ;PRINT A RETURN - LINE FEED
        JSR    PC,PCHR
        CLR    R0              ;DUMMY
        JSR    PC,PCHR
        MOV    #12,R0
        JSR    PC,PCHR
        MOV    (SP)+,R0
        RTS    PC
```

```
016576 010046
016600 012700 000015
016604 004737 016710
016610 005000
016612 004737 016710
016616 012700 000012
016622 004737 016710
016626 012600
016630 000207
```


VTU LOGIC TESTS MACY11 30A(1052) 06-SEP-79 15:10 PAGE 51-1
CVVTAA.SRC 06-SEP-79 15:03 CARRIAGE RETURN LINE FEED

L 7

SEQ 0089

3702

3704
3705
3706
3707
3708
3709
3710
3711
3712
3713
3714
3715
3716
3717
3718
3719
3720
3721
3722
3723
3724
3725
3726
3727
3728
3729
3730
3731
3732
3733
3734
3735
3736
3737
3738
3739
3740
3741
3742
3743
3744
3745
3746
3747
3748
3749
3750
3751
3752
3753
3754
3755
3756
3757
3758
3759

.SBTTL PRINT AN ASCII MESSAGE

DESCRIPTION:

ROUTINE TO PRINT A STRING OF ASCII
CHARACTERS ON THE CONSOLE TERMINAL. CERTAIN
CHARACTERS WITHIN THE STRING ARE INTERPRETED
AS CONTROL CODES, THESE ARE:

133 ([) WILL GENERATE A <CR>,<LF>
100 (@) WILL SIGNIFY END OF MESSAGE

THE ADDRESS OF THE MESSAGE STRING TO BE PRINTED
WILL BE HELD IN THE LOCATION FOLLOWING THE CALL
TO THE ROUTINE, IE:

JSR PC,TYPOUT
ADDR

CALLING SEQUENCE:

JSR PC,TYPOUT

INPUT PARAMETERS:

THE ADDRESS OF THE MESSAGE STRING FOLLOWS
THE SUBROUTINE CALL.

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

THE SPECIFIED MESSAGE WILL BE PRINTED

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

3760				:		
3761				:		
3762				:		
3763	016632	004737	015536	TYPOUT:	JSR	PC, SAVREG
3764	016636	017601	000000		MOV	@(SP), R1
3765	016642	062716	000002		ADD	#2, (SP)
3766	016646	111100		PMSG1:	MOVB	@R1, R0
3767	016650	022700	000100		CMP	#100, R0
3768	016654	001412			BEQ	PMSG4
3769	016656	022700	000133		CMP	#133, R0
3770	016662	001003			BNE	PMSG2
3771	016664	004737	016576		JSR	PC, CRLF
3772	016670	000402			BR	PMSG3
3773	016672	004737	016710	PMSG2:	JSR	PC, PCHR
3774	016676	005201		PMSG3:	INC	R1
3775	016700	000762			BR	PMSG1
3776	016702	004737	015634	PMSG4:	JSR	PC, RSTREG
3777	016706	000207			RTS	PC

;SAVE REGS
 ;R1 POINTS AT STRING
 ;JUMPS OVER ARGUMENT
 ;PRINT THE MESSAGE POINTED
 ;TO BY R1 UNTIL @, WHICH IS END.
 ;[MEANS CR-LF
 ;RESTORE REGS

3779
3780
3781
3782
3783
3784
3785
3786
3787
3788
3789
3790
3791
3792
3793
3794
3795
3796
3797
3798
3799
3800
3801
3802
3803
3804
3805
3806
3807
3808
3809
3810
3811
3812
3813
3814
3815
3816
3817
3818
3819
3820
3821
3822
3823
3824
3825
3826

016710 004737 015074
 016714 010037 177566
 016720 000207

.SBTTL PRINT A CHARACTER

DESCRIPTION:

ROUTINE TO PRINT A CHARACTER ON THE
 CONSOLE. RO CONTAINS THE CHARACTER TO BE PRINTED

CALLING SEQUENCE:

JSR PC,PCHR

INPUT PARAMETERS:

RO CONTAINS THE CHARACTER TO BE PRINTED

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

THE CHARACTER SELECTED WILL BE PRINTED

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

PCHR: JSR PC,TPREDY ;PRINTER READY
 MOV RO,TPB
 RTS PC

3828
3829
3830
3831
3832
3833
3834
3835
3836
3837
3838
3839
3840
3841
3842
3843
3844
3845
3846
3847
3848
3849
3850
3851
3852
3853
3854
3855
3856
3857
3858
3859
3860
3861
3862
3863
3864
3865
3866
3867
3868
3869
3870
3871
3872
3873
3874
3875
3876
3877
3878
3879
3880
3881
3882
3883

016722 004737 015536
 016726 012701 014160
 016732 112721 000040
 016736 020127 014166
 016742 001373
 016744 000241
 016746 010002
 016750 042702 177770
 016754 062702 000060

.SBTTL PRINT AN OCTAL NUMBER

DESCRIPTION:

ROUTINE TO PRINT AN OCTAL NUMBER ON
 THE CONSOLE TERMINAL. R0 CONTAINS THE BINARY
 REPRESENTATION ON THE NUMBER THAT IS TO BE
 PRINTED.

CALLING SEQUENCE:

JSR PC,PROCT

INPUT PARAMETERS:

R0 CONTAINS THE NUMBER THAT IS TO BE
 PRINTED

IMPLICIT INPUT PARAMETERS:
 NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

THE NUMBER SPECIFIED WILL BE PRINTED

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

PROCT: JSR PC,SAVREG ;SAVE REGS
 MOV #OCTNUM,R1 ;POINTER TO MESSAGE
 PROCT1: MOVB #40,(R1)+ ;FILL WITH SPACES
 CMP R1,#OCTNUM+6 ;ALL DONE
 BNE PROCT1 ;NO
 PRCT1A: CLC ;CLEAR AT START
 PROCT2: MOV R0,R2 ;SAVE CHARS
 BIC #177770,R2 ;CLEAR ALL BUT BOTTOM 3 BITS
 ADD #60,R2 ;NOW ASCII

3884	016760	110241			MOVB	R2,-(R1)		;STORE IT IN MESSAGE
3885	016762	042700	000007		BIC	#7,R0		;NOW CLEAR BOTTOM 3 BITS
3886	016766	001404			BEQ	PROCT3		;ALL DONE
3887	016770	006000			ROR	R0		;ROTATE NEXT 3 BITS
3888	016772	006000			ROR	R0		
3889	016774	006000			ROR	R0		
3890	016776	000763			BR	PROCT2		;GO DO NEXT
3891	017000	004737	016632		PROCT3: JSR	PC,TYPOUT		;TYPE MESSAGE
3892	017004	014160			OCTNUM			;MESSAGE ADD.
3893	017006	004737	015634		JSR	PC,RSTREG		;RESTORE REGS
3894	017012	000207			RTS	PC		
3895					:			
3896					:			
3897					:			
3898					:			
3899					:			
3900	017014	004737	015536		PRNT3: JSR	PC,SAVREG		
3901	017020	042700	177000		BIC	#177000,R0		;CLEAR UNWANTER
3902	017024	012737	002040	014160	MOV	#2040,OCTNUM		;SET UP MESSAGE
3903	017032	012737	040040	014162	MOV	#40040,OCTNUM+2		;WITH END CODE
3904	017040	012701	014163		MOV	#OCTNUM+3,R1		;8 POINTER
3905	017044	000737			BR	PRCT1A		;JUMP INTO MAIN ROUTINE
3906								;WITH POINTERS SET UP

3908
3909
3910
3911
3912
3913
3914
3915
3916
3917
3918
3919
3920
3921
3922
3923
3924
3925
3926
3927
3928
3929
3930
3931
3932
3933
3934
3935
3936
3937
3938
3939
3940
3941
3942
3943
3944
3945
3946
3947
3948
3949
3950
3951
3952
3953
3954
3955
3956
3957
3958
3959
3960
3961
3962
3963

.SBTTL PRINT A DECIMAL NUMBER

DESCRIPTION:

ROUTINE TO PRINT A SIGNED, OR UNSIGNED
 DECIMAL NUMBER ON THE CONSOLE. RO CONTAINS THE
 BINARY REPRESENTATION ON THE NUMBER TO BE PRINTED

CALLING SEQUENCE:

JSR PC,BASE10 FOR UNSIGNED
 JSR PC,BASM10 FOR SIGNED

INPUT PARAMETERS:

RO CONTAINS THE NUMBER TO BE PRINTED

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

NONE

IMPLICIT OUTPUT PARAMETERS:

THE NUMBER SPECIFIED WILL BE PRINTED

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE

ROUTINE TO PRINT A SIGNED DECIMAL NO.
 ENTER WITH IT HELD IN RO
 RO :IS IT -VE
 BASE10 :NO
 RO :YES SO MAKE +VE
 #55,BASE11 :PUT '-' IN MESSAGE
 BAS10A :GO DO IT

ROUTINE TO PRINT UNSIGNED DECIMAL NO.

017046 005700
 017050 100005
 017052 005400
 017054 112737 000055 014170
 017062 000403

BASM10: TST
 BPL
 NEG
 MOVB
 BR

3964								
3965	017064	112737	000040	014170	BASE10: MOVB	#40, BASE11		;PUT SPACE AS 1ST CHARA
3966	017072	004737	015536		BAS10A: JSR	PC, SAVREG		;SAVE REGS
3967	017076	012703	014171			MOV	#BASE11+1, R3	;REST OF MESSAGE WITH SPACES
3968	017102	112723	000040		BASE1A: MOVB	#40, (R3)+		
3969	017106	022703	014176			CMP	#BASE11+6, R3	;ALL DONE
3970	017112	001373				BNE	BASE1A	;NO
3971	017114	005001			BASE1D: CLR	R1		;R1 IS RECEIVER
3972	017116	020027	000012		BASE1B: CMP	R0, #12		;MORE THAN 10
3973	017122	103404				BLO	BASE1C	;YES SO DONE THIS TIME
3974	017124	162700	000012			SUB	#12, R0	;NO SO SUB 10 & ADD 1 TO R1
3975	017130	005201				INC	R1	
3976	017132	000771				BR	BASE1B	;GO DO AGAIN
3977	017134	062700	000060		BASE1C: ADD	#60, R0		;MAKE ASCII & STORE
3978	017140	110043				MOVB	R0, -(R3)	
3979	017142	010100				MOV	R1, R0	
3980	017144	001363				BNE	BASE1D	
3981	017146	004737	015634			JSR	PC, RSTREG	;RESTORE REGS
3982	017152	004737	016632			JSR	PC, TYP0UT	;TYPE MESSAGE
3983	017156	014170				BASE11		;ADDRESS OF MESSAGE
3984	017160	000207			RTS	PC		


```
3986 .SBTTL MODIFY THE PROGRAM
3987
3988
3989
3990 DESCRIPTION:
3991 ROUTINE TO MODIFY A LOCATION IN MEMORY
3992 ENTERED BY TYPING CNTRL-O ON THE CONSOLE
3993 TERMINAL.
3994
3995
3996
3997
3998 PROMPTS ($) FOR AN ADDRESS TO EXAMINE
3999 AND PRINTS IT IN THE FORM
4000
4001 ADDR CONTENTS /
4002
4003 THEN A NEW VALUE CAN BE ENTERED
4004
4005 VIS:
4006
4007 ADDR CONTENTS / NEW VALUE
4008
4009
4010 THE NEW VALUE CAN BE TERMINATED USING
4011 <CR>, <LF>, OR <ESC>
4012
4013
4014
4015
4016 <LF> TO EXAMINE THE NEXT LOC
4017 <CR> TO SELECT ANOTHER ADDRESS
4018 <ESC> TO EXIT
4019
4020
4021
4022
4023 CALLING SEQUENCE:
4024 JSR PC,MODIFY
4025
4026 INPUT PARAMETERS:
4027
4028 NONE
4029
4030
4031 IMPLICIT INPUT PARAMETERS:
4032
4033 ENTERED BY TYPING CNTRL-O DURING
4034 THE RUNNING OF THE TESTS
4035
4036
4037 OUTPUT PARAMETERS:
4038
4039 NONE
4040
4041
```


4098	017412	004737	016576		JSR	PC,CRLF	; NEWLINE
4099	017416	062737	000002	014302	ADD	#2,MODADR	;UPDATE THE ADDRESS BY 2
4100	017424	000704			BR	MOD12	; THEN TRY THIS ADDRESS
4101	017426	020027	000033		MOD15: CMP	RQ,#33	;WAS IT EXIT ?
4102	017432	001405			BEQ	MODXIT	;YES DISSAPPEAR
4103	017434	012700	000077		MOV	#77,R0	;ELSE GIVE A ?
4104	017440	004737	016710		JSR	PC,PCHR	;AS AN ERROR
4105	017444	000751			BR	MOD14	;THEN TRY AGAIN
4106	017446	012737	000006	000004	MODXIT: MOV	#6,4	;PLUG BACK TRAP THRU 4
4107	017454	012737	000004	000006	MOV	#4,6	;WITH WHAT IS WAS
4108	017462	004737	016576		JSR	PC,CRLF	;PUT OURSELVES ON A NEW LINE
4109	017466				PSWSET	MODSAV	
4110	017502	004737	015634		JSR	PC,RSTREG	;RESTORE REGISTERS
4111	017506	000207			RTS	PC	;AND GO AWAY
4112							

4114
4115
4116
4117
4118
4119
4120
4121
4122
4123
4124
4125
4126
4127
4128
4129
4130
4131
4132
4133
4134
4135
4136
4137
4138
4139
4140
4141
4142
4143
4144
4145
4146
4147
4148
4149
4150
4151
4152
4153
4154
4155
4156
4157
4158
4159
4160
4161
4162
4163
4164
4165
4166
4167
4168
4169

.SBTTL SET BUS AND VECTOR ADDRESSES

DESCRIPTION:

ROUTINE TO SET UP THE BUS AND VECTOR ADDRESSES AND PRIORITY LEVELS OF THE DEVICE UNDER TEST. THE VALIDITY OF THE VARIOUS ADDRESSES ARE CHECKED. THE ARGUMENTS AFTER THE CALL MUST BE SET TO INDICATE THE NUMBER OF BUS AND VECTOR ADDRESSES AND THE NUMBER OF PRIORITIES REQUIRED, AND THE LOCATIONS WHERE THE VARIOUS PARAMTERES ARE TO BE STORED

IT IS CALLED THUS:

JSR R5,BUSSET
 .BYTE A,B
 .WORD C
 .BYTE D,E
 .WORD F,G
 .BYTE H,J
 .WORD K,L

WHERE A IS EITHER 7 IF THERE ARE 4 OR LESS BUS ADDRESSES OR 17 IF THERE ARE 5-8 ADDRESSES, OR 37 IF THERE 9-16, AND SO ON. B IS THE NUMBER OF BUS ADDRESSES. C IS THE ADDRESS INTO WHICH THE FIRST BUS ADDRESS WILL BE LOADED, SUBSEQUENT BUS ADDRESSES WIL BE LOADED INTO THE LOCATION FOLLOWING THE ADDRESS C.HENCE IF THERE A 4 BUS ADDRESSES THE C MUST POINT TO A FOUR WORD BUFFER THAT WILL CONTAIN THE 4 BUS ADDRESSES. D IS THE NUMBER OF VECTOR ADDRESSES E IS THE NUMBER OF PRIORITY LEVELS, AND IF THE VECTOR IS TO BE ON A 10 BYTE BOUNDARY, BIT 7 OF E MUST BE SET AS A FLAG. F IS THE ADDRESS INTO WHICH THE FIRST VECTOR ADDRESS WILL BE LOADED.G IS THE ADDRESS INTO WHICH THE FIRST PRIORITY WILL BE LOADED. H AND J ARE EQUIVALENT TO D AND E INCASE MORE THAN ONE VECTOR GROUP ARE PRESENT. K AND L ARE THE ADDRESSES EQUIVALENT TO F AND G. THE SEQUENCE H,J,K,L CAN BE REPEATED FOR AS MANY VECTOR PAIRS AS REQUIRED. THE SEQUENCE IS TERMINATED BY SETTING H AND J TO ZERO

CALLING SEQUENCE:

JSR R5,BUSSET

INPUT PARAMETERS:

THE ARGUMENTS TO SET UP THE ADDRESSES, VECTORS AND PRIORITIES MUST BE SET UP, AS DESCRIBED ABOVE

IMPLICIT INPUT PARAMETERS:


```

4170      :      NONE
4171      :
4172      :
4173      :      OUTPUT PARAMETERS:
4174      :
4175      :      NONE
4176      :
4177      :
4178      :      IMPLICIT OUTPUT PARAMETERS:
4179      :
4180      :      THE BUS AND VECTOR ADDRESSES WILL
4181      :      BE SET UP AS SPECIFIED BY THE ARGUEMENTS
4182      :
4183      :
4184      :      COMPLETION CODES:
4185      :
4186      :      NONE
4187      :
4188      :
4189      :      POSSIBLE ERROR CODES:
4190      :
4191      :      NONE
4192      :
4193      :
4194      :
4195 017510 004737 015536 BUSSET: JSR    PC,SAVREG    ;SAVE REGISTER CONTENTS
4196 017514 012737 020232 000004      MOV    #NXMTRP,4    ;SET UP MEMORY ERROR TRAP
4197 017522 012737 000340 000006      MOV    #340,6
4198      :
4199 017530 012537 014306      MOV    (R5)+,MASK    ;GET MASK AND NO OF ADDRESSES
4200 017534 012537 014310      MOV    (R5)+,BASADD    ;GET BASE BUS ADDRESS
4201      :
4202 017540 004737 016632 BUSSE1: JSR    PC,TYPOUT
4203 017544 013332      BMSG    ;FIRST BUS ADDRESS IS....
4204 017546 004737 015732 1$: JSR    PC,OCTIN    ;INPUT OCTAL ADDRESS
4205 017552 005737 014276      TST    RAND
4206 017556 001004      BNE    2$
4207 017560 004737 016632      JSR    PC,TYPOUT
4208 017564 013712      NODEFM
4209 017566 000767      BR     1$
4210 017570 133700 014306 2$: BITB    MASK,R0    ;CHECK INPUT
4211 017574 001406      BEQ    BUSSE2
4212      :
4213 017576 004737 016632      JSR    PC,TYPOUT
4214 017602 013425      ODMSG    ;INVALID ADDRESS
4215 017604 004737 016722 BUSS1A: JSR    PC,PROCT
4216 017610 000753      BR     BUSSE1
4217      :
4218 017612 005037 014312 BUSSE2: CLR    TRPERR
4219 017616 113701 014307      MOVB   MASK+1,R1    ;SET UP COUNT
4220 017622 013702 014310      MOV    BASADD,R2    ;SET UP ADDRESS BASE
4221 017626 010022      MOV    R0,(R2)+    ;SET UP ADDRESS
4222 017630 005710      TST    (R0)    ;CHECK ADDRESS EXISTS
4223 017632 005737 014312      TST    TRPERR    ;CHECK NON-EXISTANT MEMORY FLAG
4224 017636 001362      BNE    BUSS1A
4225 017640 062700 000002      ADD     #2,R0    ;UPDATE TO NEXT ADDRESS
  
```

4226						
4227	017644	005301		DEC	R1	
4228	017646	001367		BNE	BUSSE3	
4229	017650	004737	016632	JSR	PC,TYPOUT	; PROMPT FOR VECTOR GROUP
4230	017654	013110		FIRVMS		
4231						
4232	017656	012537	014306	MOV	(R5)+,MASK	;GET NO OF VECTORS
4233	017662	012537	014310	BUSSE3A: MOV	(R5)+,BASADD	;GET BASE VECTOR ADDRESS
4234						
4235	017666	004737	016632	BUSSE4: JSR	PC,TYPOUT	
4236	017672	013366		VAMSG		;FIRST VECTOR ADDRESS IS....
4237	017674	004737	015732	1\$: JSR	PC,OCTIN	;INPUT OCTAL ADDRESS
4238	017700	005737	014276	TST	RAND	
4239	017704	001004		BNE	2\$	
4240	017706	004737	016632	JSR	PC,TYPOUT	
4241	017712	013712		NODEFM		
4242	017714	000767		BR	1\$	
4243	017716	005737	014306	2\$: TST	MASK	;CHECK MASK TYPE
4244	017722	100007		BPL	BUSSE6	
4245						
4246	017724	032700	000007	BIT	#7,R0	;CHECK ADDRESS
4247	017730	001404		BEQ	BUSSE6	
4248						
4249	017732	004737	016632	BUSSE5: JSR	PC,TYPOUT	
4250	017736	013425		ODAMSG		;INVALID ADDRESS
4251	017740	000752		BR	BUSSE4	
4252						
4253	017742	032700	000003	BUSSE6: BIT	#3,R0	;CHECK ADDRESS
4254	017746	001371		BNE	BUSSE5	
4255						
4256	017750	022700	000774	CMP	#774,R0	;CHECK ADDRESS LESS THAN 772
4257	017754	002004		BGE	BUSSE7	
4258						
4259	017756	004737	016632	JSR	PC,TYPOUT	
4260	017762	013450		OVAMSG		;ADDRESS EXCEEDS 772
4261	017764	000740		BR	BUSSE4	
4262						
4263	017766	113701	014306	BUSSE7: MOVB	MASK,R1	;SET UP COUNT
4264	017772	013702	014310	MOV	BASADD,R2	;SET UP ADDRESS BASE
4265	017776	010022		BUSSE10: MOV	R0,(R2)+	;SET UP ADDRESS
4266	020000	022020		CMP	(R0)+,(R0)+	
4267	020002	005301		DEC	R1	
4268	020004	001374		BNE	BUSSE10	
4269	020006	042737	100000 014306	BIC	#100000,MASK	
4270						
4271	020014	113701	014307	MOVB	MASK+1,R1	
4272	020020	012537	014310	MOV	(R5)+,BASADD	;GET BASE PRIORITY ADDRESS
4273						
4274	020024	005737	014504	TST	LSIFLG	;SINGLE INT.LEVEL PROCESSOR ?
4275	020030	001403		BEQ	3\$	;IF NOT THEN BRANCH AWAY.
4276	020032	012700	000004	MOV	#4,R0	;ELSE SET PRIORITY LEVEL AT 4
4277	020036	000416		BR	BUSSE11B	;THEN GO INSTALL IT.
4278						
4279	020040	004737	016632	3\$: JSR	PC,TYPOUT	
4280	020044	013477		PRMSG		;FIRST PRIORITY LEVEL IS...
4281	020046	013702	014310	MOV	BASADD,R2	

4282	020052	004737	015732	BUSS11:	JSR	PC,OCTIN	;INPUT OCTAL PRIORITY
4283	020056	005737	014276		TST	RAND	
4284	020062	001004			BNE	BUS11B	
4285	020064	004737	016632		JSR	PC,TYPOUT	
4286	020070	013712			NODEFM		
4287	020072	000767			BR	BUSS11	
4288	020074	020027	000007	BUS11B:	CMP	R0,#7	;IS THE PRIORITY LEGAL ?
4289	020100	101404			BLOS	2\$	;YES
4290	020102	004737	016632		JSR	PC,TYPOUT	
4291	020106	013625			BADPRI		;NO, RE-ENTER VALUE
4292	020110	000760			BR	BUSS11	
4293	020112	042700	177770	2\$:	BIC	#-10,R0	;CLEAR UNWANTED BITS
4294	020116	000300			SWAB	R0	
4295	020120	006200			ASR	R0	
4296	020122	006200			ASR	R0	
4297	020124	006200			ASR	R0	
4298	020126	010022			MOV	R0,(R2)+	;SET UP PRIORITY
4299							
4300	020130	005301			DEC	R1	
4301	020132	001412			BEQ	BUSS12	
4302				:			
4303	020134	005737	014504		TST	LSIFLG	;SINGLE INT.LEVEL PROCESSOR ?
4304	020140	001403			BEQ	4\$	;IF NOT THEN BRANCH AWAY
4305	020142	012700	000004		MOV	#4,R0	;ELSE SET UP PRIORITY AS 4
4306	020146	000752			BR	BUS11B	;AND GO INSTALL IT.
4307				:			
4308	020150	004737	016632	4\$:	JSR	PC,TYPOUT	
4309	020154	013536			NPRMSG		;NEXT PRIORITY LEVEL IS....
4310	020156	000735			BR	BUSS11	
4311							
4312	020160	012537	014306	BUSS12:	MOV	(R5)+,MASK	; GET NEXT VECTOR PAIR
4313	020164	001405			BEQ	BUSS13	; ZERO MEANS END
4314	020166	004737	016632		JSR	PC,TYPOUT	
4315	020172	013144			NXTVMS		; ELSE PROMPT FOR NEXT GROUP
4316	020174	000137	017662		JMP	BUSS3A	
4317	020200	010537	014306	BUSS13:	MOV	R5,MASK	
4318	020204	012737	000006		MOV	#6,4	
4319	020212	012737	000004		MOV	#4,6	
4320							
4321	020220	004737	015634		JSR	PC,RSTREG	;RESTORE REGISTER
4322	020224	013705	014306		MOV	MASK,R5	
4323	020230	000205			RTS	R5	
4324							
4325							
4326							
4327							
4328	020232	004737	016632	NXMTRP:	JSR	PC,TYPOUT	
4329	020236	013575			NXMSG		;NON-EXISTANT ADDRESS
4330	020240	005237	014312		INC	TRPERR	
4331	020244	000002			RTI		
4332							
4333							
4334							
4335							
4336							

4338
4339
4340
4341
4342
4343
4344
4345
4346
4347
4348
4349
4350
4351
4352
4353
4354
4355
4356
4357
4358
4359
4360
4361
4362
4363
4364
4365
4366
4367
4368
4369
4370
4371
4372
4373
4374
4375
4376
4377
4378
4379
4380
4381
4382
4383
4384
4385
4386
4387
4388
4389
4390
4391
4392
4393

.SBTTL NUMBER GENERATOR

DESCRIPTION:

ROUTINE TO GENERATE DATA PATTERNS,
THE TYPE OF PATTERN IS SELECTED BY R3, AND THE
PATTERN GENERATED IS RETURNED IN R0 AND LOCATION
GOOD.

CALLING SEQUENCE:

JSR PC,GENER

INPUT PARAMETERS:

R3 CONTAINS THE PATTERN NUMBER

R3=0	ALL ZEROES
1	ALL ONES
2	010101 ETC BIT PATTERN
3	101010 ETC BIT PATTERN
4	ROTATING 1 IN A ZERO WORD
5	ROTATING 0 IN AN ALL ONE WORD
6	PSEUDO RANDOM NUMBER
7	INCREMENTING DATA PATTERN, GOOD CONTAINS THE VALUE TO BE UPDATED

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

THE NUMBER GENERATED IS HELD IN
R0 AND GOOD.

IMPLICIT OUTPUT PARAMETERS:

NONE

COMPLETION CODES:

NONE

POSSIBLE ERROR CODES:

NONE


```

4394
4395
4396
4397 020246 042703 177770
4398 020252 004737 015536
4399 020256 006303
4400 020260 000173 020264
4401 020264 020304
4402 020266 020310
4403 020270 020316
4404 020272 020324
4405 020274 020332
4406 020276 020342
4407 020300 020400
4408 020302 020520
4409 020304 005000
4410 020306 000507
4411 020310 005000
4412 020312 005100
4413 020314 000504
4414 020316 012700 052525
4415 020322 000501
4416 020324 012700 125252
4417 020330 000476
4418 020332 000241
4419 020334 004737 020354
4420 020340 000472
4421 020342 000241
4422 020344 004737 020354
4423 020350 005100
4424 020352 000465
4425 020354 006037 020376
4426 020360 001003
4427 020362 012737 100000 020376
4428 020370 013700 020376
4429 020374 000207
4430 020376 000001
4431 020400 012737 000005 014326
4432 020406 004737 020420
4433 020412 013700 014324
4434 020416 000443
4435 020420 013702 014324
4436 020424 001002
4437 020426 013702 014332
4438 020432 032737 000777 014326
4439 020440 001003
4440 020442 012737 000001 014326
4441 020450 013703 014326
4442 020454 013702 014324
4443 020460 033702 014330
4444 020464 001405
4445 020466 005102
4446 020470 033702 014330
4447 020474 001401
4448 020476 000402
4449 020500 000241

:
:
:
GENER: BIC #177770,R3
JSR PC,SAVREG
ASL R3
JMP @GENSEL(R3)
GENSEL: GEN0
GEN1
GEN52
GEN25
GENR1
GENRO
GENRAN
GENINC
;ALL ZERO WORD
;ALL ONE WORD
;52 PATTERN
;25 PATTERN
;ROTATE '1' EACH CALL
;ROTATE '0' EACH CALL
;RANDOM NUMBER
;INCREMENTING COUNT
;0>R0
GEN0: CLR RO
BR GENEX
GEN1: CLR RO
COM RO
BR GENEX
GEN52: MOV #52525,R0
BR GENEX
GEN25: MOV #125252,R0
BR GENEX
GENR1: CLC
JSR PC,GENROT
BR GENEX
GENRO: CLC
JSR PC,GENROT
COM RO
BR GENEX
GENROT: ROR GENISH
BNE GENER1
MOV #100000,GENISH
GENER1: MOV GENISH,R0
RTS PC
GENISH: 1
GENRAN: MOV #5,RANSEL
JSR PC,RANGEN
MOV RANDN,R0
BR GENEX
RANGEN: MOV RANDN,R2
BNE RAN1
MOV RANST,R2
RAN1: BIT #777,RANSEL
BNE RAN2
MOV #1,RANSEL
RAN2: MOV RANSEL,R3
MOV RANDN,R2
BIT RANMTA,R2
BEQ RANCLC
COM R2
BIT RANMTA,R2
BEQ RANCLC
BR RANSEC
RANCLC: CLC
;NOT0>R0
;5252>R0
;125252>R0
;SHIFT 1 > R0
;SHIFT 0 > R0
;ROTATE 1 PATTERN
;= 0?
;YES, SET MSB
;PUT 1 IN R0
;AND EXIT
;SET SELECT VALUE TO 5
;GENERATE RANDOM NUMBER IN R0
;
;
;IS RANDOM = 0
;YES, PUT RANDOM START VALUE IN
;NO;IS RANSEL SELECT VALUE = 0
;NO
;YES: SET RANSEL = 1
;
;GET R2 <0 AND 1>
;

```

4450	020502	000401	
4451	020504	000261	
4452	020506	006037	014324
4453	020512	005303	
4454	020514	001357	
4455	020516	000207	
4456	020520	013700	014334
4457	020524	005200	
4458	020526	010037	014334
4459	020532	010066	000002
4460	020536	004737	015634
4461	020542	000207	

	BR	RAN4
RANSEC:	SEC	
RAN4:	ROR	RANDN
	DEC	R3
	BNE	RAN2+4
RANEX:	RTS	PC
GENINC:	MOV	GOOD,RO
	INC	RO
GENEX:	MOV	RO,GOOD
	MOV	RO,2(SP)
	JSR	PC,RSTREG
	RTS	PC

:ROTATE C TO B15
:IS THIS NUMBER REQUIRED?
:NO, GET ANOTHER
:YES, EXIT
:INCREMENTS LOC. 'GOOD'

:LOAD RO,MAINROUTINE

4463
4464
4465
4466
4467
4468
4469
4470
4471
4472
4473
4474
4475
4476
4477
4478
4479
4480
4481
4482
4483
4484
4485
4486
4487
4488
4489
4490
4491
4492
4493
4494
4495
4496
4497
4498
4499
4500
4501
4502
4503
4504
4505
4506
4507
4508
4509
4510
4511
4512
4513
4514
4515
4516
4517
4518

.SBTTL PRINT ERROR MESSAGES

DESCRIPTION:

ROUTINE TO PRINT ERROR MESSAGES
IF BIT 14 IN THE SWR IS SET NO MESSAGES WILL BE
PRINTED, IF BIT 15 IS SET THE PROGRAM WILL NO WAIT
AFTER AN ERROR HAS BEEN PRINTED. IT IS CALLED THUS:

JSR PC,ERROR
ARG

WHERE ARG CONTAINS THE ERROR CODE AND IS OF THE FORM
X+N, WHERE N IS THE ERROR NUMBER IN THE RANGE 0-177
AND X IS A COMBINATION OF FLAGS THAT INDICATE WHAT
VALUES ARE TO BE PRINTED. THESE VALUES SHOULD BE LOADED
BEFORE THE ERROR ROUTINE IS CALLED AND ARE DEFINED
AS FOLLOWS:

FLAG SETTING	NUMBER	LOCATION	MESSAGE
-----	-----	-----	-----
C	4000	CALLPC	CALLED FROM
S	10000	STATUS	STATUS
A	20000	ADDRES	ADDRESS
D	40000	DATA	DATA
G	100000	GOOD, BAD	GOOD= BAD =

IN ADDITION THE ERROR NUMBER WILL BE COMBINED WITH
THE TEST NUMBER TO INDICATE IN WHICH TEST THE ERROR
OCCURRED.
AN ERROR COUNT IS MAINTAINED AN ON EACH ERROR THE
COUNT IS UPDATED. IF RUNNING UNDER A SOFTWARE SWITCH
REGISTER, IT IS POSSIBLE TO SELECT NEW OPTIONS

CALLING SEQUENCE:

JSR PC,ERROR

INPUT PARAMETERS:

THE LOACTION FOLLOWING THE CALL
CONTAINS THE ERROR CODE AND FLAG SETTINGS

IMPLICIT INPUT PARAMETERS:

NONE

OUTPUT PARAMETERS:

```

4519      :
4520      :
4521      :
4522      :
4523      :
4524      :
4525      :
4526      :
4527      :
4528      :
4529      :
4530      :
4531      :
4532      :
4533      :
4534      :
4535      :
4536      :
4537      :
4538      :
4539      :
4540 020544 004737 015536 ERROR: JSR 15/11/78
4541 020550 005237 014346 INC PC,SAVREG
4542 020554 032777 040000 173436 BIT ERRDIS ;INC COUNT
4543 020562 001133 BNE #40000,@SWR ;SUPPRESS PRINTOUT
4544 020564 017637 000000 014350 MOV ERHALT ;YES
4545 020572 004737 016632 JSR @ (SP),ERRARG ;NO
4546 020576 014014 MSG1 PC,TYPOUT ;TYPE MESSAGE
4547 020600 013700 014216 MOV TESTNO,R0
4548 020604 000300 SWAB R0
4549 020606 006300 ASL R0
4550 020610 153700 014350 BISB ERRARG,R0
4551 020614 004737 016722 JSR PC,PROCT
4552 020620 004737 016632 JSR PC,TYPOUT
4553 020624 014020 MSG2
4554 020626 011600 MOV (SP),R0
4555 020630 004737 016722 JSR PC,PROCT ;PRINT 6 DIGITS
4556 020634 132737 000200 014351 BITB #200,ERRARG+1
4557 020642 001416 BEQ ERRSV1
4558 020644 004737 016632 JSR PC,TYPOUT
4559 020650 014032 MSG3
4560 020652 013700 014334 MOV GOOD,R0
4561 020656 004737 016722 JSR PC,PROCT
4562 020662 004737 016632 JSR PC,TYPOUT
4563 020666 014043 MSG4
4564 020670 013700 014336 MOV BAD,R0
4565 020674 004737 016722 JSR PC,PROCT
4566 020700 132737 000100 014351 ERRSV1: BITB #100,ERRARG+1 ;D SET ?
4567 020706 001407 BEQ ERRSV2 ;NO
4568 020710 004737 016632 JSR PC,TYPOUT
4569 020714 014054 MSG5
4570 020716 013700 014340 MOV DATA,R0
4571 020722 004737 016722 JSR PC,PROCT
4572 020726 132737 000040 014351 ERRSV2: BITB #40,ERRARG+1 ;A SET ?
4573 020734 001407 BEQ ERRSV3 ;NO
4574 020736 004737 016632 JSR PC,TYPOUT
  
```



```

4575 020742 014065          MSG6
4576 020744 013700 014344    MOV    ADDRES,RO
4577 020750 004737 016722    JSR    PC,PROCT
4578 020754 132737 000020 014351 ERRSV3: BITB    #20,ERRARG+1    ;S SET ?
4579 020762 001407          BEQ    ERRSV4    ;NO
4580 020764 004737 016632    JSR    PC,TYP0UT
4581 020770 014103          MSG7
4582 020772 013700 014342    MOV    STATUS,RO
4583 020776 004737 016722    JSR    PC,PROCT
4584 021002 132737 000010 014351 ERRSV4: BITB    #10,ERRARG+1    ;C SET
4585 021010 001407          BEQ    ERRSV5    ;NO
4586 021012 004737 016632    JSR    PC,TYP0UT
4587 021016 014116          MSG8
4588 021020 013700 014352    MOV    CALLPC,RO
4589 021024 004737 016722    JSR    PC,PROCT
4590 021030 004737 016576    ERRSV5: JSR    PC,CRLF
4591 021034 004737 016632    JSR    PC,TYP0UT
4592 021040 014135          MSG9
4593 021042 013700 014346    MOV    ERRDIS,RO
4594 021046 004737 017064    JSR    PC,BASE10
4595 021052 032777 100000 173140 ERHALT: BIT    #100000,@SWR
4596 021060 001004          BNE    NOHALT
4597 021062 013700 014346    MOV    ERRDIS,RO    ;DISPLAY ERROR COUNT
4598 021066 004737 015344    JSR    PC,MONIT    ;GO TO SWR
4599 021072 004737 015634    NOHALT: JSR    PC,RSTREG
4600 021076 062716 000002    ADD    #2,(SP)
4601 021102 000207          RTS    PC
4602 021104 000000          BUFF1: 0
4603          001000          .END    START    ;PROGRAM END, SELF-START.
  
```

A = 020000	CHRFIN 016554	GENER 020246	MONITA 015436	RANDC 014410
ADDRES 014344	CHSR 014230	GENER1 020370	MONITX 015444	RANDN 014324
ASK56 012164	CHWRD 014314	GENEX 020526	NODEFM 013712	RANEX 020516
BAD 014336	CLRB1T 002762	GENINC 020520	NOHALT 021072	RANGEN 020420
BADPR1 013625	CNVFLG 014374	GENISH 020376	NOMEMA 013177	RANMTA 014330
BAMSG 013332	COUNT1 004264	GENRAN 020400	NPRMSG 013536	RANSEC 020504
BASADD 014310	COUNT2 004266	GENROT 020354	NXMADR 014362	RANSEL 014326
BASE1A 017102	CRLF 016576	GENRO 020342	NXMSG 013575	RANST 014332
BASE1B 017116	CSR 014222	GENR1 020332	NXMTRP 020232	RAN1 020432
BASE1C 017134	D = 040000	GENSEL 020264	NXTVMS 013144	RAN2 020450
BASE1D 017114	DATA 014340	GENO 020304	OCTIN 015732	RAN4 020506
BASE10 017064	DBUF 014224	GEN1 020310	OCTMSG 014206	RDYINT 011760
BASE11 014170	DECMMSG 014200	GEN25 020324	ODAMSG 013425	READ 016104
BASM10 017046	EMSG1 014014	GEN52 020316	OVAMSG 013450	REDMES 013247
BAS10A 017072	EMSG2 014020	GETCH1 016134	PARITY 014320	REPCNT 014250
BCCHAR 014322	EMSG3 014032	GETCH2 016146	PAR0 = 172340	REPC11= 001000
BCOUNT 014414	EMSG4 014043	GETCH3 016260	PAR1 = 172342	REPC12= 000100
BELL 014764	EMSG5 014054	GETCH4 016324	PAR2 = 172344	REPC13= 000002
BELLMS 004276	EMSG6 014065	GETSTR 016130	PAR3 = 172346	REPRM1 006256
BELLS 004274	EMSG7 014103	GOMSG 012272	PAR4 = 172350	REPROM 006162
BELL1 014776	EMSG8 014116	GOOD 014334	PAR5 = 172352	RETRY 002474
BINC1 011670	EMSG9 014135	HALF6V 012160	PAR6 = 172354	RSTART 001200
BINC2 011750	ENDIT 014664	HALF8V 012162	PAR7 = 172356	RSTREG 015634
BINC3 011716	ERHALT 021052	HSWR = 177570	PASMSG 013020	RUBCHR 016402
BITS 002476	ERMES1 002500	ILLCHR 016534	PCHR 016710	RUBFLG 014406
BLNFLG 012056	ERMES2 002564	ILLVEC 015024	PDR0 = 172300	R6 = %000006
BLN1 012032	ERMES3 002650	ILVMSG 013036	PDR1 = 172302	R7 = %000007
BLN2 012054	ERMES4 002722	INTFLG 004272	PDR2 = 172304	S = 010000
BUFF 012060	ERMS10 004361	INTSRV 004206	PDR3 = 172306	SAVEXM 014364
BUFF1 021104	ERMS11 004427	INTVEC 014242	PDR4 = 172310	SAVLT4 014370
BUSSET 017510	ERMS12 004473	JM600 014252	PDR5 = 172312	SAVLT6 014372
BUSSE1 017540	ERMS13 004531	LINDEL 016450	PDR6 = 172314	SAVPAR 014366
BUSSE2 017612	ERMS14 004602	LINDL1 016470	PDR7 = 172316	SAVPC 014266
BUSSE3 017626	ERMS20 005662	LINECH 016500	PMSG1 016646	SAVPC1 014270
BUSSE4 017666	ERR 014316	LKS = 177546	PMSG2 016672	SAVREG 015536
BUSSE5 017732	ERRARG 014350	LOPRM 006146	PMSG3 016676	SAVSTA 014272
BUSSE6 017742	ERRDIS 014346	LOWCHR 014402	PMSG4 016702	SECOND 004270
BUSSE7 017766	ERROR 020544	LSIFLG 014504	PRCT1A 016744	SETBIT 002706
BUSS1A 017604	ERRSV1 020700	L525 012156	PRESET 011756	SETBLN 012002
BUSS10 017776	ERRSV2 020726	MASK 014306	PRMSG 013477	SET56 012062
BUSS11 020052	ERRSV3 020754	MODADM 013314	PRNT3 017014	SET56A 012126
BUSS12 020160	ERRSV4 021002	MODADR 014302	PROCT 016722	SILLS1 014442
BUSS13 020200	ERRSV5 021030	MODIFY 017162	PROCT1 016732	SRO = 177572
BUSS3A 017662	FADR 014754	MOD11 017212	PROCT2 016746	SR1 = 177574
BUS11B 020074	FASTSW 015104	MOD12 017236	PROCT3 017000	SR2 = 177576
C = 004000	FILL 014524	MOD13 017256	PSW = 177776	SSWR 014246
CALLPC 014352	FILL1 014556	MOD14 017370	QEXIT 015462	START 001000
CAR 014226	FILL2 014570	MOD15 017426	QEXIT1 015504	START1 001226
CARX 014232	FIRVMS 013110	MODPRM 013325	QEXIT2 015506	START2 001232
CARY 014234	FRMMMSG 013070	MODSAV 014304	QEXIT3 015522	START3 001266
CA1170= 177746	FSAVPW 014412	MODSPA 013321	RANCLC 020500	STATUS 014342
CHAR 014240	FSTCNT 014256	MODXIT 017446	RAND 014276	STBINC 011634
CHDR 014236	G = 100000	MONIT 015344		STRADD 014376

STRLEN	014400	TSTB2	002322	T1019	003764	T4000	006276	T5011	010336
SWR	014220	TSTB3	002326	T1019A	004012	T4001	006316	T5012	010342
SWMSG	013302	TSTB4	002462	T1020	004040	T4002	006330	T5013	010404
SWRSET	014506	TYPCIC	015454	T1021	004056	T4002A	006320	T5014	011614
TABLE	001272	TYPD1	014300	T1022	004120	T4003	006400	T5015	010636
TABLE1	001316	TYPOTA	014274	T1023	004126	T4004	006446	T5015A	010552
TESMSG	013007	TYPOTB	015736	T2000	004726	T4005	006476	T5016	010654
TESTNO	014216	TYPOTC	016016	T2001	004746	T4006	006536	T5017	010716
TESTR	014416	TYPOTD	016052	T2002	005026	T4007	006610	T5018	010754
TEST0	001332	TYPOTE	016070	T2003	005032	T4008	006662	T5018A	011000
TEST1	002776	TYPOUT	016632	T2003A	005036	T4009	006734	T5018B	011004
TEST2	004710	T0000	001350	T2004	005042	T4010	006776	T5019	011044
TEST3	005734	T0001	001370	T2004A	005056	T4015	007026	T5020	011106
TEST4	006260	T0002	001454	T2005	005146	T4016	007066	T5020A	011142
TEST5	007676	T0003	001460	T2006	005172	T4017	007140	T5020B	011152
TIME1	004230	T0004	001564	T2007	005200	T4018	007212	T5021	011250
TIME1A	004262	T0005	001570	T2008	005270	T4019	007264	T5022	011276
TKB =	177562	T0007	002170	T2009	005314	T4020	007326	T5023	011302
TKS =	177560	T0008	002204	T2010	005320	T4021	007364	T5024	011342
TPB =	177566	T10WW	004132	T2011	005334	T4022	007474	T5025	011376
TPREDY	015074	T1000	003014	T2012	005420	T4023	007524	T5026	011402
TPS =	177564	T1001	003034	T2013	005444	T4024	007634	T5027	011446
TRAPSV	015124	T1002	003146	T2014	005450	T50WY	011630	T5028	011506
TRPARG	014260	T1003	003242	T2015	005510	T5000	007714	T5029	011512
TRPBAK	015332	T1004	003250	T2016	005600	T5001	007746	T5030	011552
TRPERR	014312	T1008	003254	T2017	005624	T5002	007770	UPPCHR	014404
TRPLP	015266	T1009	003364	T2018	005646	T5003	007774	VAMSG	013366
TRPMEM	014264	T1012	003370	T3000	005752	T5004	010102	VECLEV	014244
TRPSCP	015242	T1013	003500	T3001	005772	T5005	010106	VECTOR	014516
TRPSEL	014262	T1014	003504	T3002	006014	T5006	010164	WAIT	004156
TRXEXM	014360	T1015	003544	T3003	006044	T5007	010210	WMSG	012736
TRXPAR	014356	T1016	003562	T3004	006060	T5007A	010214	WTCO	004204
TRXVAD	014354	T1017	003636	T3005	006104	T5008	010216	WTC1	004202
TSTBIT	002210	T1017A	003700	T3006	006132	T5009	010272	SENDAD	014740
TSTB1	002232	T1018	003716	T40WW	007662	T5010	010332	.	= 021106

. ABS. 021106 C00

ERRORS DETECTED: 0

CVVTAA.BIN, CVVTAA.SEQ=CVVTAA.SRC
 RUN-TIME: 13 26 1 SECONDS
 RUN-TIME RATIO: 172/41=4.1
 CORE USED: 11K (21 PAGES)